HIGH PERFORMANCE LIGHT WEIGHT
AND TONAL BACK BLOCKOUT FABRIC,
INHERENTLY FLAME RETARDANT

Climate Ready® Fabrics

CR Bloc

Blockout

- 100% light blockout and glare control
- PVC free
- High performance / light weight
- Inherently flame retardant - Trevira CS

Roller Shades

Panel Glide Shades

Vertical Shades

Suitable for internal installation only.

Technical Data

Openness Factor:	0%
Fabric Width:	240 cm
Thickness:	0.4 mm
Weight:	300 - 350 g/m^2
Composition:	100% Polyester Trevira CS
Opacity:	Acrylic foam coating - Blockout tested to AS-2663-1999
Fire Retardancy:	Compliant to AS1530.2 and AS1530.3 Certificates available on request.

Fenestration Properties

Design	OF (%)	As (%)	Rs (%)	Ts (%)	Tuv (%)	Tv (%)	Rv (%)	Gtot Value: A Glaze	Gtot Value: B Glaze	Gtot Value: C Glaze	Gtot Value: D Glaze
White B111	0	33	67	0	0	0	80	-	-	-	-
Beige B112	0	48	52	0	0	0	61	-	-	-	-
Grey B113	0	67	33	0	0	0	37	-	-	-	-
Bronze B114	0	86	14	0	0	0	16	-	-	-	-
Black B115	0	93	7	0	0	0	8	-	-	-	-

G tot: Total solar factor, ratio of the energy transmitted through a window and solar protection device. Classification and reference glazing according to standard EN 14501

Data is current at time of printing. Please check website for most current information.

Openess Factor / **OF**
Ultraviolet Transmittance / **Tuv**
Light Transmittance / **Tv**
Light Reflectance / **Rv**
Solar Transmittance / **Ts**
Solar Reflectance / **Rs**
Solar Absorption / **As**
G Value / **G tot**

Gtot refernece glasing types (EN 14501)

A: Clear single glazing
B: Clear double glazing
C: Double glazing with coating
D: Reflective double glazing with coating

Certification:

ecospecifier global

Ecospecifier Global Certified

OEKO-TEX® CONFIDENCE IN TEXTILES STANDARD 100

OEKO-TEX Standard 100

trevira CS

TREVIRA CS Inherently Flame Retardant

Light-fastness:	5-6 (ISO 105 B02)
Care Instructions:	Handle fabric with care and wear clean gloves. Lightly dust regularly with clean feather duster. A hand-held vacuum with low suction may also be used. When vacuuming, avoid pulling or stretching the fabric. Leave the blind down until completely dry.
Warranty:	5 year warranty as complete roller shade systems for internal use. For more information regarding warranties and extended warranties, please contact Climate Ready Fabrics.
Sustainability:	● PVC-free ● 100% recyclable

Colour Range:

Face fabric side showing tonal backing

| White B111 | Beige B112 | Grey B113 | Bronze B114 | Black B115 |

Colours are to be used for reference purposes only.
For an accurate colour sample, please contact Climate Ready Fabrics for a fabric swatch sample.