

Autofire E60—Auto Closing Fire Window


1 hour (-/60/-) fire rated DtS solution NCC Clause C3.4

January 2014



1300 665 471

www.smokecontrol.com.au



Smoke Control's Full Life Cycle Service ensures that at any stage of the project – from design through to commissioning – the only company responsible is Smoke Control

100% QUALITY



The Autofire auto closing fire rated window system is fully approved for fire ratings up -/60/-. Designed and manufactured in Australia.

The Autofire auto closing fire rated window system is a DtS solution as per the requirements of NCC Clause C3.4.

Single glass panels can span 1.2m H x 1.1m W, max 1.44m² area. Multiple operable's / fixed windows can be combined for larger openings.

So why the Stopleveline E60 system?

- Slim unobtrusive design
- Sizes made to measure
- Various options to meet energy efficient design solutions
- Privacy films can be applied
- Maintain building ventilation requirements
- High quality product
- 1 year conditional warranty

100% Customer Service



Smoke Control offers obligation free technical support throughout your design and documentation stage. We are also happy to provide obligation free pricing so that you can accurately prepare your budgets

We have also prepared a complete kit for your documentation requirements. Simply download from our website a complete set of specifications and drawings. If you would like our drawings in DWG format, simply give our technical department a call or email your request.

We will endeavour to respond the same day !

info@smokecontrol.com.au

TECHNICAL SUPPORT by qualified engineers and draftspeople

MASTER SPECIFICATIONS

Download

DESIGN DETAILS

Download



100% Flexibility



Unobtrusive in design, the Autofire auto closing fire rated window system is designed to be an aesthetic way to protect your windows close to boundaries.

In the event of a fire, the fusible system incorporated into the window design will melt, closing the window and protecting the property from fire.

Made to measure, there are also a multitude of glazing options to meet all your U-Value, SHGC etc requirements, from double glazing to Low-e glass or films.

The Autofire auto closing fire rated window system has been full scale fire tested in strict accordance with AS1530.4.

Glass is a grade A toughened Safety glass in accordance with AS1288.

Stainless steel framing can be provided for buildings within 5km of the ocean.

Framing can be powder coated any colour in the Dulux Duralloy range to match clients tastes and building façade. Other powercoat colours and systems are available on request.

Full certification issued with Installation.