

## BENEFITS OF SISALATION® REFLECTIVE FOIL

**Insulation:** All products in the range are tested in accordance with AS4200.1 and proven to provide significant lifelong insulation benefits.

**Quality:** Every product in the range is manufactured in Australia under an ISO 9001 Certified Quality Management System.

Sisalation® Reflective Foil					
Application	Duty	Product	Roll size m x mm	m <sup>2</sup> per roll	Product code
Tiled Roof	Extra Heavy	Sisalation® Fall Arrest Tile Roof Sarking ExHD	30 x 1500	45	952300
	Heavy	Sisalation® Tiled Roof Sarking HD	30 x 1500	45	952296
Metal Roof	Heavy	Sisalation® Metal Roof Sarking HD	60 x 1350	81	952260
	Medium	Sisalation® Metal Roof Sarking MD	60 x 1350	81	951260
Wall Wrap	Extra Heavy	Sisalation Wall Wrap® ExHD	30 x 1350	40.5	255130
			60 x 1350	81	255160
		Sisalation Wall Wrap® ExHD Breather	30 x 1350	40.5	255136
	Medium		60 x 1350	81	255162
		Sisalation Wall Wrap® MD	30 x 1350	40.5	255088
			60 x 1350	81	255092
Multi Purpose	Extra Heavy	Sisalation® Residential Multi Purpose ExHD	30 x 1350	40.5	952330
			30 x 1500	45	952331
			60 x 1350	81	952360
	Light	Sisalation® Residential Multi Purpose LD	60 x 1350	81	950260
	Facing Foil	Heavy	Sisalation® Facing Foil HD	60 x 1200	72
300 x 1200				360	952148
Sisalation® Facing Foil HD Perforated			600 1500	900	952204
			60 x 1350	81	952182
			300 x 1200	360	952151
Sisalation® Black Facing Foil Perforated HD		60 x 1350	81	952276	
		300 x 1350	405	952272	
Medium		Sisalation® White Metal Roof MD	60 x 1350	81	251460
			Sisalation® White Metal Roof MD Perforated	60 x 1350	81
		Light	Sisalation® Facing Foil LD	500 x 1350	675
1000 x 1350	1350			950230	
Residential Shed Foil		Sisalation® Residential Shed Foil LD	60 x 1350	81	952099

†† Can only be used in Residential Class 1 Metal Roof Applications.

## InsulMist® Reflective Insulation

Product	Material R-value	Nominal thickness mm	Roll size m x mm	m <sup>2</sup> Per Roll
InsulMist® 650AG Reflective Insulation	R0.20	6.5	22.25 x 1350	30
InsulMist® 650BR Breather AG Reflective Insulation	R0.20	6.5	22.25 x 1350	30
InsulMist® 800AG Reflective Insulation	R0.25	8	22.25 x 1350	30

## InsulBubble® Reflective Insulation

Product	Nominal Thickness mm	Roll Size m x mm	m <sup>2</sup> per roll
InsulBubble® 100 Reflective Insulation	4.5	22.25 x 1350	30
InsulBubble® 200 Reflective Insulation	4.5	22.25 x 1350	30

## Tyvek® HomeWrap

Product	Roll Size m x mm	m <sup>2</sup> per roll
Tyvek® HomeWrap	30 x 2743	82
	30 x 3048	91

### NEED HELP?

CALL OUR NATIONAL CUSTOMER SERVICE TEAM:

**1300 654 444**

Additional assistance on Total R-values can also be found in the ICANZ Insulation Handbook at [www.icanz.org.au](http://www.icanz.org.au)

**Fletcher  
Insulation**

**Fletcher Insulation**  
600 Woodstock Ave  
Rooty Hill NSW 2766

P 1300 654 444  
F 02 9675 2618  
E [info@insulation.com.au](mailto:info@insulation.com.au)

© Fletcher Insulation 2014. Fletcher Insulation reserves the right to change product specifications without prior notification. Information in this publication and otherwise supplied to users as to the subject product is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of products, no warranty is given or is to be implied with respect to either such information or the product itself, in particular the suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application. InsulBubble® is a registered trademark of Sealed Air Corporation. DuPont™, StraightFlash™, FlexWrap™, Tyvek® are trademarks or registered trademarks of E. I. du Pont de Nemours and Company. All other ™ and ® are trademarks or registered trademarks of Fletcher Insulation Pty Limited ABN 72 001 175 355. BR06 Revision 2 Issue Date 12.02.2014 / FI\_0288\_000214

The future of **Insulation**

# Sarking and wall wrap for homes



**Fletcher  
Insulation**

*We safely deliver extraordinary value to our customers*

### DUPONT™ FLASHING SYSTEMS

The DUPONT™ Flashing System provides comprehensive protection from water leaks and is designed to help direct water to the building exterior instead of trapping it inside the wall system. DUPONT™ FlexWrap™ is wrapped into the rough opening before the window is installed making one-step seamless protection possible. DUPONT™ StraightFlash™ is also available as a flashing material for windows and doors and provides a reliable moisture seal.

### TILED ROOF

- Specifically developed for installation under tiled roofs.
- Sisalation® Fall Arrest Tile Roof Sarking ExHD reflective foil has been independently tested and certified as a Fall Arrest Sarking.
- Suitable for installation in areas prone to high or seasonal winds.
- Installation\*: Should be installed in accordance with AS/NZS 4200.2 'Installation requirements for pliable building membranes'. A minimum airspace of 40mm is required adjacent to the reflective foil face to provide optimum insulation performance. All products being installed into a tiled roof application must be installed under the battens

\*See product datasheet for more details.

### METAL ROOF

- Developed for metal roof applications.
- Sisalation® Metal Roof Sarking HD reflective foil is a high performance, heavy weight product recommended for use in high wind areas.
- Sisalation® Residential Multi Purpose ExHD reflective foil is a versatile, extra heavy duty and economical residential roof sarking.
- Installation\*: Should be installed in accordance with AS/NZS 4200.2 "Installation requirements for pliable building membranes". A minimum airspace of 40mm is required adjacent to the reflective foil face. All products being installed into a metal roof application must be installed under the battens.

\*See product datasheet for more details.

### TYVEK® HOMEWRAP

DUPONT™ Tyvek® HomeWrap is suitable for homes with external cladding material. It will help protect the home against wind and rain that can penetrate through the exterior cladding. The unique woven structure blocks excess water from entering into the walls. The breathable structure also allows vapour to pass through to help promote drying in the wall system.



### INSULBUBBLE® REFLECTIVE INSULATION

InsulBubble® reflective insulation can be used as a roof sarking and wall wrap, it is easy to install and provides a better aesthetic finish to the underside of a home garage or shed with no ceiling.

### INSULMIST® REFLECTIVE INSULATION

InsulMist® reflective insulation achieves the thermal break requirement set by the Building Code of Australia, when used on homes with steel framework. InsulMist® reflective insulation also acts as a vapour barrier reducing the passage of moisture and dust particles into the roof and wall cavities.

### THERMATAPE® INSULATION

Thermatape® insulation works by creating a thermal break between the steel frame and the outer cladding material in steel framed homes. The high density foam prevents direct contact between the steel frame and the cladding at the fixing point, thereby, ensuring that the overall thermal performance of the insulation system is not adversely affected by thermal bridging.

### SISALATION WALL WRAP®

- Sisalation Wall Wrap® products provide the ultimate protection against the elements.
- Wall wraps stop moisture from transferring from the external to the internal walls and allows building work to continue inside the home even in inclement weather.
- Wall wraps provide a barrier for wind and dust.
- Installation\*: wall wraps should be installed in accordance with AS/NZS 4200.2 'Installation requirements for pliable building membranes'. It should be installed with a 150mm overlap between runs. External cladding should be installed without delay.

\*See product datasheet for more details.