




Altro Cantata™

adhesive-free flooring



Sunrise | AFP282008
WR393 / A1M393 / LRV 19



Bluebell | AFP282004
WR398 / A1M398 / LRV 26



Willow Tree | AFP282007
WR399 / A1M399 / LRV 41




Adhesive-free flooring -
swatch above shows
underside emboss of
Altro Cantata.

Reusable and recyclable
post-use.



Mocha | AFP282003
WR389 / A1M389 / LRV 40




Frosted Glass | AFP282005
WR388 / A1M388 / LRV 52




Crème Caramel | AFP282006
WR385 / A1M385 / LRV 50




Black Sand | AFP282010
WR485 / A1M485 / LRV 7



True Grit | AFP282001
WR391 / A1M82 / LRV 17



Graphite | AFP282002
WR390 / A1M390 / LRV 30



Hazelnut | AFP282009
WR418 / A1M239 / LRV 18



Elephant Grey | AFC281003
WR436 / A1M487 / LRV 17



Seal Grey | AFC281002
WR435 / A1M390 / LRV 26




Bluefin | AFC281001
WR438 / A1M486 / LRV 26



Treviso | AFT284003
WR483 / A1M483 / LRV 44



Rome | AFT284001
WR481 / A1M83 / LRV 16



Venice | AFT284004
WR484 / A1M484 / LRV 40



Milan | AFT284002
WR482 / A1M482 / LRV 15



Typical applications

Reception, corridor, treatment, teaching, waiting and seating areas in: hospitals, care homes, kindergartens, schools, universities, cafés, restaurants.

Technical information

	Fire behaviour tested in acc. with Classified in acc. with	EN ISO 9239-1 EN ISO 11925-2 EN 13501-1	≥ 4.5 kW/m ² Pass C _f -s1
	Slip resistance	EN 13893 DIN 51130 / BGR 181	≥ 0.30 / DS R10 For enhanced safety, see our ranges that offer sustained slip resistance for life.
	Sound insulation	EN ISO 10140	ca. 14 dB
	Flooring type	EN 651	Heterogenous floor
	Thickness	EN ISO 24346	2.4 mm
	Wear layer thickness	EN ISO 24340	0.7 mm
	Roll dimensions	EN ISO 24341	2 m x 20 m = 40 m ²
	Weight	EN ISO 23997	2.4 kg/m ²
	Residual indentation	EN ISO 24343-1	≤ 0.20 mm
	Classification for use	EN ISO 10874	34, 42
	Flexibility	EN ISO 24344	Pass
	Light fastness	EN ISO 105-BO2	≥ 6
	Castor chair abrasion	EN 425	Yes, type W
	Wear resistance	EN 660-2	Group T
	Chemical resistance	EN ISO 26987	Good
	Under floor heating	EN 12524	Suitable
	Electrical behaviours	EN 1815	≤ 2 kV, antistatic
	VOC emissions	Indoor Air Comfort Gold CDPH 1350 / Floorscore	Approved Approved



20 | debolon dessauer bodenbeläge GmbH & Co. KG,
Ebertallee 209, D-06846 Dessau-Roßlau | EN 651 |
DoP-No. RN-A034 | Reaction to fire: Cfl-s1 | Slip resistance: DS |
Formaldehyde: E1 | Electrical behaviour: EN 1815 < 2 kV |
EN 14041:2004/AC:2006 | 1658 |
Resilient floor covering to be used within a building



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

Altro Limited a company certified by SGS to ISO 9001 and ISO 14001.



Sustainability



*A+ BRE generic green guide rating for resilient flooring, full details available at www.thegreenguide.org.uk

Installation and maintenance

Please refer to Altro installation and maintenance instructions. Failure to follow these instructions can affect product performance. Technical information on installation and staining can be found at www.altro.com

 Altro, Designed for possibilities. Made for people. Altro Cantata and Altro Easyclean technology are trademarks of Altro Limited.

United Kingdom

+44 (0) 1462 707 700

enquiries@altro.com

Australia

+61 3 9764 5666

info@asf.com.au