



FES110 Series

ELECTRIC DEADLOCK STRIKE - HIGH SECURITY



The FES110 Series electric deadlock strike's release mechanism has been designed to provide door access control while maximising security to a door assembly, fitted with square bolt deadlocks.

The FES110 monitors both door lock tongue and internal locking of the strike. The device is multi-voltage, accepting 12VDC - 30VDC and has a 2 year warranty.

Features

- Stainless steel faceplate and keeper
- Holding strength of up to 500kg
- 2 year warranty
- Multi-voltage 12VDC-30VDC (has to be specified)(has to be specified)
- Monitoring Lock Status Sensor (LSS) and Door Status Sensor (DSS) monitoring
- PTO and PTR version available

Warranties

Mechanical	2 years
Electronic	2 years

Technical specifications

Part No.	FES110-PTL	FES110-PTO
Function	Power To Lock (PTL)	Power To Open (PTO)
Holding Strength	Up to 500kg	
Voltage/Current	12-30 VDC (Multi-voltage) 12 V 600mA dropping to 220mA 24V 350mA dropping to 12mA	
Approvals	Up to 2-hour fire rating (contact Allegion for more details)	
Monitoring	Lock Status Sensor (LSS) and Door Status Sensor (DSS)	
Dimensions	L= 306 x W= 32 x H= 58mm	

Product dimensions

