

UNA PORTE

VERSATILE SOLUTION FOR DDA COMPLIANCE UP TO 2000MM



proudly distributed by



UNA PORTE

ADVANTAGES & TECHNICAL DATA

- ✓ for indoor and outdoor use
- ✓ soft start/soft stop via a frequency-controlled drive system
- ✓ optimum ratio of space requirement to usable platform area
- ✓ no pit required due to ramp
- ✓ simple retrofitting

Compliant with NCC E3.6 and AS1735.15

CONTROL & OPERATION

- ↑ push-button operation on the platform / remote controlled buttons for landing call stations
- ↑ full graphic color display
- ↑ integrated fault memory
- ↑ Dual control panels with braille

POWER SUPPLY

- ↑ 220-240V, 1 phase, 10A

FLOOR

- ↑ Anodized aluminium checker plate

OPTIONS

- ↑ automatic door operators
- ↑ LED RGB lighting
- ↑ electrical emergency lowering
- ↑ SMS remote query of operating states



FAST ASSEMBLY

TRAVEL HEIGHT

- ↑ from 500mm to 2000mm

STOPS

- ↑ 2 stops

VELOCITY

- ↑ 0,15 m/s

LOAD CAPACITY

- ↑ 375 kg

COLOR

- ↑ open platform standard RAL 9022
- ↑ lifting column anodised aluminium

PLATFORM SIZE

- ↑ 1400 x 1100 mm (LxB)

REQUIRED SPACE

- ↑ 1675 x 1290 mm (LxB) with closed swing door

DOOR

- ↑ 960 mm passage width

TYPE OF DRIVE

- ↑ guide chain system with electric drive 0.75 kW
- ↑ safety gear with integrated speed limiter



Direct Lifts Australia
1300 240 298
info@directlifts.com.au
www.directlifts.com.au