

Neoflex™ 700 Series
REPTile


Neoflex™
RESILIENT FLOORING

REPHOUSE
www.rephouse.com



Transform any floor to your taste.

Neoflex™ 700 Series REPTiles are dual-durometer rubber tiles, 1m x 1m in size, available from 8 - 30 mm thick. Available in any Neoflex 700 Series color, Neoflex™ 700 Series REPTiles are a terrific choice for cardio areas, freestyle areas or suspension training activities.



The surface finish is made of synthetic EPDM rubber with an "orange-peel" like finish for good grip and excellent durability. Logos, agility and functional zone markings can be in-laid in to the surface for maximum effectiveness and usability.



www.rephouse.com




Specifications.




Property	Standard	Result
Thickness		8 - 30 mm
Size		1000 mm x 1000 mm
Shore Hardness	ASTM D 2240	60°
Resilience	DIN 18032-2	40%
Tear Strength Top Layer	ASTM D 624	1.25 MPa
Tear Strength Base Layer	ASTM D 624	0.70 MPa
Taber Abrasion	ASTM C 504	0.66 gr
Remaining Indentation	DIN 53960	0.05 mm
Flammability	EN 13501-1	C _{fl} -s1
Coefficient of Friction	ASTM D 2047-97	Dry: 1.03 Wet: 0.97

All in one, easily installed format.

Neoflex™ 700 Series REPTiles are supplied in 1m x 1m tiles, that are easy to install.




without graphics




with graphics


Standard Colors.




701




701B



702




636




711



716



720




723



740




742




744



749




750




755




757




768




776




783



700-001




700-002




700-003




700-004




700-005




700-006




700-007



700-008



700-009



700-010

A Selection of Standard Colors

For real samples, contact us!