

VOGL -BUILD YOUR SPECIFICATION

Complete the table and use the details in your project specification.

PRODUCT	VOGL	SUPPLIER	DECOR SYSTEMS - PH: 1800 835 035	
PROFILE	(CHOOSE A PROFILE FROM THE LIST ABOVE)			
ACCESS PANELS	QUANTITY	(CHOOSE AN OPTION FROM THE LIST ABOVE)		
VOGL FRIEZE TAPE	QUANTITY	(CHOOSE AN OPTION FROM THE LIST ABOVE)		
67MM WIDE FURRING CHANNEL	4.8M X 67MM	3.6M X 67MM	6M X 67MM	QUANTITY
TCR CLIP	QUANTITY	DIRECT FIXING SADDLE	QUANTITY	
"A" CLIPS	QUANTITY			
FIRE CERTIFICATION	VOGL COMES WITH A GROUP 1 FIRE RATING. IN SOME CASE, IT CAN ACHIEVE A GROUP 1 CERTIFICATION WHEN A SPECIFIC COMBINATION OF SUBSTRATE AND FINISH IS USED. PLEASE DISCUSS THIS WITH YOUR DECOR SYSTEMS PROJECT CONSULTANT.			
NOTES	(ANY EXTRA INFORMATION YOU WOULD LIKE TO ADD?)			
<p>Close collaboration between Decor Systems, the project architect and the client has taken place to develop this specification. Vogl cannot be substituted unless agreed by Architect and Acoustic Engineer.</p> <p>Panels should be allowed to acclimatise on site for at least five days before installation. Decor Systems certificate # (Contact your Decor Systems project consultant for your individual project number) to be supplied upon completion.</p> <p>Panel installation to be as per manufacturer's instructions and AS/NZS 2785. - Installation to be done by an approved ceiling and partition contractor.</p> <p>Product guarantee to be 99 years as per Decor Systems guarantee. Please contact Decor Systems for your project specific completion number.</p>				