



Bottle Filler Solutions

Hydration and Wellbeing®



Fill and Go

Designed for student hydration and wellbeing so they can simply fill and go





This bottle filler range has been developed with a **'swap and go'** retrofit design philosophy.

Simply remove the existing bubbler and replace with your new Enware bottle filler!

Fill and Go

Hydration and Wellbeing

Hello 2021, you're finally here and there's good news on the horizon as we head out of lockdown.

We've not been able to say a proper goodbye to COVID just yet and we've all learned a few things when it comes to the spread of infection and disease. We all still need to be diligent especially when it comes to minimising the risk of cross contamination.

During COVID the importance of student hydration and wellbeing never went away and it's

still a top priority. Enware's rapid R & D response to this need has been the development of a range of bottle fillers.

Almost every article you read about hydration, there is a common theme, by the time you're feeling thirsty – you're probably dehydrated. That's why it's important to refill and refresh drink bottles with water, regularly throughout the day. We know that educating and encouraging good hydration habits means that **students need access to drinking water.**

Enware's range of bottle fillers is a great alternative solution to bubblers. An easy and convenient way for students to fill their water bottles routinely throughout the day whilst reducing the 'mouth to water' cross contamination risk.










Focused on solutions designed to promote student hydration and wellbeing... now and into the future.





Browse through our product selection matrix to help guide you.

Swap and Go

| | PART NUMBER | TROUGH/MOUNTING TYPE | ACTIVATION | INLET SIZE | FLOW RATE |
|---|---|----------------------|--|--------------------|--------------------------------------|
|  | BUBBFRWE-R Activation Right Side | Wallsend | Push Button (Right Hand Side) Suitable for mounting on left end of trough | 1/2" BSP (15mm) | 5 L/min |
|  | BUBBFRWE-L Activation Left Side | Wallsend | Push Button (Left Hand Side) Suitable for mounting on right end of trough | 1/2" BSP (15mm) | 5 L/min |
|  | BUBBF224-WE-C Type 63 Activation Right Side Filler at Front | Wallsend | Cam Action | 1/2" BSP (15mm) | 5 L/min (Adjustable 2-7 L/min) |
|  | BUBBF224-WE-LVR Type 63 Activation Right Side Filler at Front | Wallsend | Lever Action | 1/2" BSP (15mm) | 5 L/min (Adjustable 2-7 L/min) |
|  | BUBBFRWEL-CR Activation Right Side Filler at Left | Wallsend with Lid | Cam Action (Right Hand Side) | 1/2" BSP (15mm) | 5 L/min |
|  | BUBBFRWEL-CL Activation Left Side Filler at Right | Wallsend with Lid | Cam Action (Left Hand Side) | 1/2" BSP (15mm) | 5 L/min |
|  | BUBBFRWEL-LL Activation Left Side Filler at Right | Wallsend with Lid | Lever (Left Hand Side) | 1/2" BSP (15mm) | 5 L/min |
|  | BUBBFRWEL-LR Activation Right Side Filler at Left | Wallsend with Lid | Lever (Right Hand Side) | 1/2" BSP (15mm) | 5 L/min |
|  | BUBBFRWEL-PBL Activation Left Side Filler at Right | Wallsend with Lid | Push Button (Left Hand Side) | 1/2" BSP (15mm) | 5 L/min |



Swap and Go

| | PART NUMBER | TROUGH/MOUNTING TYPE | ACTIVATION | INLET SIZE | FLOW RATE |
|--|---|--|----------------------------------|--------------------|--------------------------------------|
|  | BUBBFRWEL-PBR Activation Right Side Filler at Left | Wallsend with Lid | Push Button (Right Hand Side) | 1/2" BSP (15mm) | 5 L/min |
|  | BUBBFRW-PB Activation at Front | Wall Mount | Push Button | 1/2" BSP (15mm) | 5 L/min |
|  | BUBBF219-C Type 100 Activation at Front Filler at Left or Right | Wall Mount | Cam Action | 1/2" BSP (15mm) | 5 L/min (Adjustable 2-7 L/min) |
|  | BUBBF219-LVR Type 100 Activation at Front Filler at Left or Right | Wall Mount | Lever | 1/2" BSP (15mm) | 5 L/min (Adjustable 2-7 L/min) |
|  | BUBBFW-PB95 Activation at Front Filler Underneath | Wall Mount | Push Button | 1/2" BSP (15mm) | 5 L/min |
|  | BUBBFRH-PB Activation at Front | Hob Mount Replacement for Enware DFSA120 and DFSA121 Chillers | Push Button | 1/2" BSP (15mm) | 5 L/min |
|  | BUB302B Activation at Top Filler at Front | Hob Mount | Push Button | 1/2" BSP (15mm) | 5 L/min |
|  | BUBBFGFH-C150 312mm Tall Gooseneck Spout Fixed Activation right side, filler at front | Hob Mount | Cam Action | 1/2" BSP (15mm) | 8 L/min |
|  | BUBBFGSH-C150 350mm Tall Gooseneck Spout Fixed Activation right side, filler at front | Hob Mount | Cam Action | 1/2" BSP (15mm) | 8 L/min |
|  | BUB268B Activation at Front Filler Underneath | Wall Mount | Push Button | 1/2" BSP (15mm) | 5 L/min |

Fill and Go.. Hands Free!

- Battery operated (6V)
or Mains Powered (12V)
- Low power consumption
- Adjustable sensitivity for difficult
light conditions
- Suited to indoor applications
- 5.5lpm laminar flow
- 2-5 year battery life
- Low battery warning indicator



Electra Sensor

ENM6320 - Mains Powered

ENM6350 - Battery Operated



You don't have to go it alone, your local Enware representative is available to help you.

ENWARE

1300 369 273 (AUS)

info@enware.com.au

www.enware.com.au