

# CFT540 LED (350mA)

105-0082

1/2

**we-ef**



## Description

IP66. Class I. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. RFC™ Reflection Free Contour main lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation. Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. LED board can be easily removed for upgrading. CAD- optimised OLC® optics for superior illumination and glare control. Maximum spacing for streetlighting applications depends on wattage and light distribution: 5.5 to 9 times the mounting height. Available from 1st quarter 2015.

<b>Beam Type</b>	rectangular [R]
<b>Lamp Type</b>	LED-36/36W/830 - 3000K
<b>Gear Type</b>	EC
<b>Nominal Luminous Flux (lm)</b>	
LED Lumens	126 lm
LEDs	36
Total Lumens	4536 lm
Tj	85 °C
<b>Rated Luminous Flux (lm)</b>	
LED Lumens	117.7 lm
Total Lumens	4236.6 lm
Ta	25 °C
<b>Rated Input Power</b>	42 W

# CFT540 LED (350mA)

105-0082

2/2

