




Designed for possibilities.
Made for people.

Welcome to Altro
Altro Floors Catalogue





Contents

Altro specialised slip-resistant flooring	4
Altro Pisces™	6
Altro Pisces data sheet	8
Altro Aquarius™	10
Altro Aquarius data sheet	12
Altro Stronghold™ 30 / K30	14
Altro Stronghold 30 / K30 data sheet	16
Altro Classic™ 25 / X25	18
Altro Classic 25 / X25 data sheet	20
Altro XpressLay™ Adhesive-free safety flooring	22
Altro XpressLay data sheet	26
Altro Walkway™ 20 / VM20	28
Altro Walkway 20 / VM20 data sheet	32
Altro designer slip-resistant flooring	28
Altro Orchestra™	30
Altro Orchestra data sheet	34
Altro Operetta™	36
Altro Operetta data sheet	40
Altro Serenade™	42
Altro Serenade data sheet	44
Altro Wood™ Safety	46
Altro Wood Safety data sheet	50
Altro Wood™ Safety Comfort	52
Altro Wood Safety Comfort data sheet	54
Altro Cantata™	62
Altro Cantata data sheet	64



Altro Specialised Slip-resistant flooring

Altro have developed a series of ranges that are catered to those specialised areas that need extra protection underfoot. We cover the following high-risk areas:



For barefoot/shoe - Altro Aquarius and Altro Pisces

For wet areas where people could be barefoot or wearing any type of shoe, Altro's revolutionary Altro Aquarius is the ideal solution. It can be used in wet and dry locations including bathrooms, shower and changing areas, found in healthcare, leisure and social housing environments.

For 'home away from home' environments, looks really do matter. Altro Pisces is perfect for those providing accommodation, safety remains a top priority, especially in wet environments where the likelihood of a slip is high.



For kitchens / catering - Altro Stronghold 30/K30

The wet and greasy conditions of commercial kitchens prone to frequent spillages are catered for by a 3mm safety floor which boasts Altro's highest rating for slip resistance, Altro Stronghold 30/K30.



For a heavy duty solution - Altro Classic 25/X25

Our 2.5mm safety flooring provides outstanding durability and sustained slip resistance, and are the ideal choice for extreme heavy duty areas where extra protection is needed. Their excellent resistance to mechanical or physical damage makes them firm favourites in demanding environments like education, industry and healthcare.




For a sustainable solution - Altro XpressLay adhesive-free

Unlike traditional, glue-down flooring, which typically requires the adhesive to cure overnight, Altro XpressLay can be walked on and welded the same day it is installed. Altro XpressLay saves you money and installation time. It offers unrivalled sustainability credentials and all while looking great with its large palette of forty hues.



A medium wear safety flooring for general purpose - Altro Walkway 20/VM20

Altro Walkway is our hugely popular, hard-wearing 2mm safety flooring which provides lifelong slip and abrasion resistance. The range has 42 colours – featuring bright and subtle, sparkle-free designs, and decorative chipped options which give you enhanced design flexibility.





Altro Pisces™



Typical applications:

Bathrooms. Showers. Wet environments in social care; home adaptations, social housing. Student accommodation. Swimming pool surrounds. Saunas. Spas. Changing rooms*.

For 'home from home' environments, looks really do matter. For those providing accommodation, safety remains a top priority, especially in wet environments where the likelihood of a slip is high. Achieving Class B to DIN51097 for barefoot use, plus a Pendulum Test Value (PTV) of ≥ 50 (Slider 96), a soft-look finish and 16 attractive shades, Altro Pisces brings together the best of both worlds.

Altro Pisces is the first safety flooring developed with AltroBead Technology™; tiny beads are blended and evenly distributed into the flooring. The result is the consistent, soft appearance that you would want from domestic interiors, with the lifetime sustained slip-resistance you expect from Altro.

Altro Pisces performs whether wet or dry, in shoes or barefoot.



! We strongly recommend carrying out a risk assessment in any area in which the installation of safety flooring is considered, focusing on the potential risk posed by contaminants from spillages. See www.altro.com/safety for more information.

! Looks great with:

- Altro Whiterock White
- Altro Whiterock Satins
- Altro Whiterock Chameleon
- Altro Wood Safety

! Contributes to reducing the environmental impact of your specification:

- A+ BRE Generic Green Guide Rating for Safety Flooring, full details available at www.thegreenguide.org.uk



i For a co-ordinated appearance, colour matched **Weldrods (WR)** and **Mastics (A1M)** are available. You'll find their product codes under the relevant swatches.
LRV = Light Reflectance Value



















QUICK SHIP Stocked colours for quick delivery. Other colours are indent only and have a lead time of 8-12 weeks. For large quantities please call to confirm stock holding.


Dimensions 2m x 20m
Format ROLL
Thickness 2mm



! **Samples**
If colour choice is critical, please request a sample of the material.
+61 3 9764 5666
info@asf.com.au

Altro Pisces™ Data Sheet

Flooring Type		EN 13845/ EN 13553	Safety flooring
Classification for use		EN 685	34 & 43
Slip resistance		PTV EN 13845 EN 13893 DIN 51130	≥ 50 (Slider 96) ESf & ESb DS R11 Class B
Thickness		EN 428	2 mm
Wear Layer		EN 429	2 mm
Flexibility		EN 435	Pass
Weight		EN 430	2.6 kg/m ²
Roll dimensions		EN 426	2.0m x 20.00m - 40m ²
Light fastness		EN 20105-B02	≥6
Sound insulation		ISO 140-8	5 dB (subject to validation)
Wear resistance		EN 13845	≤10% particles lost over 50000 Cycles
Indentation		EN 433	≤ 0.10mm
Fire performance		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl-s1 ≥8kW/m ² Pass
Chemical resistance		EN 423	Good
Caster chair abrasion		EN 425	Pass
Under floor heating		EN 12667	Suitable
Electrical behaviours		EN 1815	≤ 2kV Antistatic
VOC emissions		Section 01350	Pass



All information is correct at the time of print and is subject to change without prior notice. Visit us online for more information and updates. This product has never contained phthalate plasticisers. www.altro.com



Altro Aquarius™

Typical applications:

Bathrooms. Showers. Changing rooms.
Swimming pool surrounds. Saunas.



You asked – we delivered. Inspired by customer feedback, Altro Aquarius was developed for lasting performance in wet and dry, shoes or barefoot. Achieving a pendulum test value of TRRL ≥ 50 and Class B to DIN51097 for barefoot use, Altro Aquarius provides optimum lifetime sustained slip-resistance in wet and dry environments. It's a 2mm safety floor that has been extensively tested on a variety of shoe types to ensure top performance in a host of environments – bathrooms, changing areas, hospital wards. Anywhere you can expect a wet and dry floor environment. It's also easy to clean, with Altro Easyclean Maxis PUR technology, meaning it's at the forefront of safety floor cleaning.

No longer do you have to choose between studded or standard safety flooring. With Altro Aquarius you can have it all. Good looks and comfort, without compromising on safety.


! We strongly recommend carrying out a risk assessment in any area in which the installation of safety flooring is considered, focusing on the potential risk posed by contaminants from spillages.
See www.altro.com/safety for more information.

! Looks great with:

- Altro Whiterock Satins
- Altro Whiterock Chameleon
- Altro Walkway 20

! Contributes to reducing the environmental impact of your specification:

- A+ BRE Generic Green Guide Rating for Safety Flooring, full details available at www.thegreenguide.org.uk



i For a co-ordinated appearance, colour matched **Weldrods (WR)** and **Mastics (A1M)** are available. You'll find their product codes under the relevant swatches.
LRV = Light Reflectance Value























QUICK SHIP Stocked colours for quick delivery. Other colours are in stock only and have a lead time of 8-12 weeks. For large quantities please call to confirm stock holding.

Dimensions	2m x 20m
Format	ROLL
Thickness	2mm

! **Samples**
If colour choice is critical, please request a sample of the material.
+61 3 9764 5666
info@asf.com.au



Altro Aquarius™ Data Sheet

Flooring Type	 	EN 13845/ EN 13553	Safety flooring
Classification for use	 	EN 685	34 & 43
Slip resistance	 	TRRL EN 13845 EN 13893 DIN 51130	≥ 36 ESf DS R10
Thickness		EN 428	2 mm
Wear Layer		EN 429	2 mm
Flexibility		EN 435	Pass
Weight		EN 430	2.4 kg/m ²
Roll dimensions	 	EN 426	2.0m x 20.00m - 40m ²
Light fastness		EN 20105-B02	≥6
Sound insulation		ISO 140-8	5 dB (subject to validation)
Wear resistance		EN 13845	≤10% particles lost over 50000 Cycles
Indentation		EN 433	≤ 0.10mm
Fire performance		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl-s1 ≥8kW/m ² Pass
Chemical resistance		EN 423	Good
Caster chair abrasion		EN 425	Pass
Under floor heating		EN 12667	Suitable
Electrical behaviours		EN 1815	≤ 2kV Antistatic
VOC emissions		prEN 15052 Section 01350 AgBB/DiBf	Low/Pass/Approved

** Caution Ketone/Aromatic Solvents. Please contact Altro for further technical advice regarding staining and chemical resistance. This product has never contained phthalate plasticisers.

All information is correct at the time of print and is subject to change without prior notice. Visit us online for more information and updates.

[≡ Back to contents](#)





Altro Stronghold™ 30/K30



Typical applications:

Kitchens. Canteens. Food preparation and service areas.
Areas where grease, oils or fats are present.

Water underfoot is treacherous enough – add grease, oils and fats, and you've got a dangerous environment. So, for commercial kitchens, canteens, food preparation and service areas, it's essential to select flooring that will help catering staff do their job safely.

Altro Stronghold 30 achieves Altro's highest rating for slip resistance (TRRL≥55, R12) and is designed to minimise risk in wet and greasy conditions for the lifetime of the flooring. As well as helping to keep staff safe from slips, it also helps reduce their fatigue, thanks to its 3mm thickness which provides noise reduction and comfort underfoot.

Altro Stronghold 30 is frequently specified with Altro Whiterock hygienic wall cladding to create safe and hygienic environments in commercial and industrial kitchens.


! We strongly recommend carrying out a risk assessment in any area in which the installation of safety flooring is considered, focusing on the potential risk posed by contaminants from spillages.
See www.altro.com/safety for more information.

! Looks great with:

- Altro Whiterock White
- Altro Whiterock Satins
- Altro Classic 25

! Contributes to reducing the environmental impact of your specification:

- A+ BRE Generic Green Guide Rating for Safety Flooring, full details available at www.thegreenguide.org.uk



i For a co-ordinated appearance, colour matched **Weldrods (WR)** and **Mastics (A1M)** are available. You'll find their product codes under the relevant swatches.
LRV = Light Reflectance Value



















QUICK SHIP Stocked colours for quick delivery. Other colours are indent only and have a lead time of 8-12 weeks. For large quantities please call to confirm stock holding.

Dimensions	2m x 15m
Format	ROLL
Thickness	3mm



! **Samples**
If colour choice is critical, please request a sample of the material.
+61 3 9764 5666
info@asf.com.au

Altro Stronghold 30/K30™ Data Sheet

Flooring Type		EN 13845/ EN 13553	Safety flooring
Classification for use		EN 685	34 & 43
Slip resistance		TRRL EN 13845 EN 13893 DIN 51130	≥ 55 Class 3 / Clase 3 / Klasse 3 (CTE) ESf DS R12
Thickness		EN 428	3 mm
Wear Layer		EN 429	3 mm
Flexibility		EN 435	Pass
Weight		EN 430	3.9 kg/m ²
Roll dimensions		EN 426	2 m x 15 m = 30 m ²
Light fastness		EN 20105-B02	≥6
Sound insulation		ISO 140-8	10 dB
Wear resistance		EN 13845	≤10% particles lost over 50000 Cycles
Indentation		EN 433	≤ 0.10mm
Fire performance		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl-s1≥8kW/m ² pass
Chemical resistance		EN 423	Good
Caster chair abrasion		EN 425	Pass
Under floor heating		EN 12667	Suitable
Electrical behaviours		EN 1815	≤ 2kV Antistatic
VOC emissions		prEN 15052 Section 01350 AgBB/DiBf	Low/Pass/Approved

** Caution Ketone/Aromatic Solvents. Please contact Altro for further technical advice regarding staining and chemical resistance.

This product has never contained phthalate plasticisers.

All information is correct at the time of print and is subject to change without prior notice. Visit us online for more information and updates.

[≡ Back to contents](#)





Altro Classic™ 25



Typical applications:

Locations where substances like chalk, paint, clay or dirt are present, such as craft, design and technology (CDT) / art rooms and circulation areas.

Classic by name, classic by nature. Altro Classic 25 was the first ever safety flooring; it's been tried and trusted for over 60 years, and its traditional, industrial look is still popular today.

Altro Classic 25 provides lasting slip resistance, durability and abrasion resistance, making it ideal for use in heavy traffic areas – particularly with wheeled traffic. It's also good for areas where occasional moisture and dust can increase the risk of slipping as it has a TRRL rating ≥ 45 and an R11 slip rating.

Available in practical, dirt-hiding shades, with the addition of new colours for even greater choice, Altro Classic 25 is easy to clean and maintain.

For specialist locations such as kitchens, canteens and food preparation areas, where grease, oils or fats may be present, we recommend Altro Stronghold 30. For bathrooms and wet rooms we recommend Altro Aquarius.

! We strongly recommend carrying out a risk assessment in any area in which the installation of safety flooring is considered, focusing on the potential risk posed by contaminants from spillages. See www.altro.com/safety for more information.

Looks great with:


- Altro Whiterock White
- Altro Whiterock Satins
- Altro Stronghold 30

🌍 Contributes to reducing the environmental impact of your specification:

- A+ BRE Generic Green Guide Rating for Safety Flooring, full details available at www.thegreenguide.org.uk




Anvil
X2594R11 LRV: 11
WR101 / A1M72




Mushroom
X2542R11 LRV: 32
WR24 / A1M27




Walnut
X2586R11 LRV: 10
WR62 / A1M62




Quarry Red
X2560R11 LRV: 13
WR42 / A1M42




Pewter Grey
X2539R11 LRV: 26
WR81 / A1M81




Whisper
X2548R11 LRV: 24
WR354 / A1M84




Graphite
X2546R11 LRV: 21
WR86 / A1M86



Legend
X2544R11 LRV: 10
WR231 / A1M73




Blue
X2541R11 LRV: 20
WR71 / A1M71




Aster
X2549R11 LRV: 17
WR286 / A1M286



Blackberry
X2547R11 LRV: 7
WR100 / A1M100



Truffle
X2545R11 LRV: 17
WR153 / A1M239



i For a co-ordinated appearance, colour matched **Weldrods (WR)** and **Mastics (A1M)** are available. You'll find their product codes under the relevant swatches.
LRV = Light Reflectance Value



















Stocked colours for quick delivery. Other colours are in stock only and have a lead time of 8-12 weeks. For large quantities please call to confirm stock holding.

Dimensions 2m x 20m
Format ROLL
Thickness 2.5mm

Samples
If colour choice is critical, please request a sample of the material.

+61 3 9764 5666
info@asf.com.au

Altro Classic 25/X25™ Data Sheet


Flooring Type		EN 13845/ EN 13553	Safety flooring
Classification for use		EN 685	34 & 43
Slip resistance		TRRL EN 13845 EN 13893 DIN 51130	≥ 45 ESf DS R11
Thickness		EN 428	2.5 mm
Wear Layer		EN 429	2.5 mm
Flexibility		EN 435	Pass
Weight		EN 430	3.2 kg/m ²
Roll dimensions		EN 426	2 m x 20 m = 40m ²
Light fastness		EN 20105-B02	≥6
Sound insulation		ISO 140-8	5 dB
Wear resistance		EN 13845	≤10% particles lost over 50000 Cycles
Indentation		EN 433	≤ 0.10mm
Fire performance		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl-s1≥8kW/m ² pass
Chemical resistance		EN 423	Good
Caster chair abrasion		EN 425	Pass
Under floor heating		EN 12667	Suitable
Electrical behaviours		EN 1815	≤ 2kV Antistatic
VOC emissions		prEN 15052 Section 01350 AgBB/DiBt	Low/Pass

** Caution Ketone/Aromatic Solvents. Please contact Altro for further technical advice regarding staining and chemical resistance.

This product has never contained phthalate plasticisers.

All information is correct at the time of print and is subject to change without prior notice. Visit us online for more information and updates.

[≡ Back to contents](#)





Altro XpressLay™ adhesive-free safety floor

Typical applications:

General purpose for areas where the ability to easily remove and recycle post installation plays an important part in your requirements for sustainable flooring finishes.



The world's first ever, adhesive-free safety floor that can save you money on materials, time on installation and offers you unrivalled sustainability credentials.

Revolutionary Altro XpressLay is a step change in the evolution of safety flooring. It's installed using a tape system instead of adhesive, so can be installed without a surface DPM. It can be easily removed post-installation, re-used elsewhere and then at the end of its life be recycled.

The range boasts 42 colours and matches with Altro Walkway™ 20 enabling you to combine the use of both ranges to suit the application.

For specialist locations such as kitchens, canteens and food preparation areas, where grease, oils or fats may be present, we recommend Altro Stronghold 30. For bathrooms and wet rooms we recommend Altro Aquarius.

! We strongly recommend carrying out a risk assessment in any area in which the installation of safety flooring is considered, focusing on the potential risk posed by contaminants from spillages. See www.altro.com/safety for more information.

Matches:


- Altro Walkway 20

Looks great with:

- Altro Whiterock
- Altro Aquarius

🌍 Contributes to reducing the environmental impact of your specification:

- A+ BRE Generic Green Guide Rating for Safety Flooring, full details available at www.thegreenguide.org.uk




i For a co-ordinated appearance, colour matched **Weldrods (WR)** and **Mastics (A1M)** are available. You'll find their product codes under the relevant swatches.
LRV = Light Reflectance Value

QUICK SHIP Stocked colours for quick delivery. Other colours are in stock only and have a lead time of 8-12 weeks. For large quantities please call to confirm stock holding.


Dimensions 2m x 20m
Format ROLL
Thickness 2.2mm




Samples
If colour choice is critical, please request a sample of the material.
+61 3 9764 5666
info@asf.com.au




Bone
XL22215 LRV: 37
WR20 / A1M20




Sand
XLI2251 LRV: 40
WR20 / A1M20



Savannah
XLI2250 LRV: 19
WR153 / A1M239



Waterfall
XL22912 LRV: 31
WR155 / A1M135




Runway
XL2206P LRV: 9
WR72 / A1M72




Pavement
XLI2207P LRV: 14
WR83 / A1M83




Signal
XLI2216P LRV: 13
WR300 / A1M42




Swan
XLI2212P LRV: 75
WR291 / A1M01




Tango
XL2231 LRV: 14
WR42 / A1M42




Cherry
XL22920 LRV: 10
WR148 / A1M148




Silk
XLI2203P LRV: 10
WR310 / A1M35




Minster
XL2218P LRV: 40
WR289 / A1M265




Pitch
XL2220P LRV: 5
WR277 / A1M100




Forge
XL2215P LRV: 9
WR248 / A1M238




Temple
XL2209P LRV: 27
WR261 / A1M81




Streetlight
XLI2205P LRV: 45
WR287 / A1M79




Rock
XLI2204P LRV: 23
WR84 / A1M84



Fresco
XLI2217P LRV: 31
WR309 / A1M309




Stream
XL2201P LRV: 22
WR288 / A1M71




Arena
XL2219P LRV: 41
WR297 / A1M20




Monument
XLI2208P LRV: 23
WR305 / A1M239




Gallery
XL2211P LRV: 10
WR62 / A1M62



Mallard
XLI2213P LRV: 13
WR302 / A1M302




Roof Garden
XL2200P LRV: 23
WR262 / A1M154



Underside of the product - no adhesive, ideal for new concrete floors with up to 97% relative humidity



Royal College of Art



Gecko
XLI2202P LRV: 18
WR308 / A1M308

! We strongly recommend carrying out a risk assessment in any area in which the installation of safety flooring is considered, focusing on the potential risk posed by contaminants from spillages. See www.altro.com/safety for more information.

Matches:
• **Altro Walkway 20**
Looks great with:
• **Altro Whiterock**
• **Altro Aquarius**

globe Contributes to reducing the environmental impact of your specification:
• A+ BRE Generic Green Guide Rating for Safety Flooring, full details available at www.thegreenguide.org.uk



i For a co-ordinated appearance, colour matched **Weldrods (WR)** and **Mastics (A1M)** are available. You'll find their product codes under the relevant swatches.
LRV = Light Reflectance Value



















QUICK SHIP Stocked colours for quick delivery. Other colours are in stock only and have a lead time of 8-12 weeks. For large quantities please call to confirm stock holding.

Dimensions 2m x 20m
Format ROLL
Thickness 2.2mm

Samples
If colour choice is critical, please request a sample of the material.
+61 3 9764 5666
info@asf.com.au



Altro XpressLay™ Data Sheet

Flooring Type		EN 13845/ EN 13553	Safety flooring
Classification for use		EN 685	34 & 43
Slip resistance		TRRL EN 13845 EN 13893 DIN 51130	≥ 36 ESf DS R10
Thickness		EN 428	2.2 mm
Wear Layer		EN 429	0.8 mm
Flexibility		EN 435	Pass
Weight		EN 430	2.6 kg/m ²
Roll dimensions		EN 426	2 m x 20 m = 40m ²
Light fastness		EN 20105-B02	≥6
Sound insulation		ISO 140-8	7 dB
Wear resistance		EN 13845	≤10% particles lost over 50000 Cycles
Indentation		EN 433	≤ 0.10mm
Fire performance		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl-s1≥8kW/m ² pass
Chemical resistance		EN 423	Good
Caster chair abrasion		EN 425	Pass
Under floor heating		EN 12667	Suitable
Electrical behaviours		EN 1815	≤ 2kV Antistatic
VOC emissions		prEN 15052 Section 01350	Low/Pass

** Caution Ketone/Aromatic Solvents. Please contact Altro for further technical advice regarding staining and chemical resistance.

This product has never contained phthalate plasticisers.

All information is correct at the time of print and is subject to change without prior notice. Visit us online for more information and updates.

[≡ Back to contents](#)





Altro Walkway™ 20/VM20




Typical applications:
General purpose.

Altro Walkway 20/VM20 is our hugely popular, hard-wearing 2mm safety flooring which provides lifelong slip and abrasion resistance.


The range has 42 colours and shares its colour range with Altro XpressLay™. This enables you to combine use of both ranges when you need traditionally adhered and adhesive-free safety flooring in adjacent areas.

Altro Walkway 20/VM20 is easy to cove and weld. It achieves ≥ 36 on the pendulum test giving sustained slip resistance throughout the lifetime of the product. It also includes PUR cleanability, superior chemical and stain resistance.


For specialist locations such as kitchens, canteens and food preparation areas, where grease, oils or fats may be present, we recommend Altro Stronghold 30. For bathrooms and wet rooms we recommend Altro Aquarius.




Black
VM20892 LRV: 6
WR100 / A1M100



Fog*
VM20153 LRV: 27
WR81 / A1M81




Lupin
VMI2059 LRV: 17
WR286 / A1M286




Coal
VMI2058 LRV: 6
WR100 / A1M100




Midnight
VM20421 LRV: 11
WR72 / A1M72




Blue
VM20412 LRV: 22
WR71 / A1M71




River
VMI2057 LRV: 22
WR71 / A1M71




Nightfall
VMI2056 LRV: 10
WR72 / A1M72




Dolphin
VM2010 LRV: 21
WR86 / A1M86




Cloud
VM2014 LRV: 41
WR79 / A1M191




Blizzard
VMI2055 LRV: 44
WR79 / A1M191




Whale
VMI2054 LRV: 20
WR86 / A1M86




Skyline
VM20332 LRV: 24
WR52 / A1M52




Biscuit
VM20907 LRV: 30
WR146 / A1M20



Winter
VMI2053 LRV: 61
WR105 / A1M01



Tarragon
VMI2052 LRV: 26
WR52 / A1M52



Tundra
VM20910 LRV: 17
WR153 / A1M239



! We strongly recommend carrying out a risk assessment in any area in which the installation of safety flooring is considered, focusing on the potential risk posed by contaminants from spillages. See www.altro.com/safety for more information.

Matches:

- Altro XpressLay

Looks great with:

- Altro Whiterock
- Altro Aquarius
- Altro XpressLay

globe Contributes to reducing the environmental impact of your specification:

- A+ BRE Generic Green Guide Rating for Safety Flooring, full details available at www.thegreenguide.org.uk




i For a co-ordinated appearance, colour matched **Weldrods (WR)** and **Mastics (A1M)** are available. You'll find their product codes under the relevant swatches.
LRV = Light Reflectance Value




Stocked colours for quick delivery. Other colours are indent only and have a lead time of 8-12 weeks. For large quantities please call to confirm stock holding.

Dimensions 2m x 20m
Format ROLL
Thickness 2mm


Samples
If colour choice is critical, please request a sample of the material.
+61 3 9764 5666
info@asf.com.au




Bone
VM20215 LRV: 37
WR20 / A1M20




Sand
VMI2051 LRV: 40
WR20 / A1M20



Savannah
VMI2050 LRV: 19
WR153 / A1M239




Waterfall
VM20912 LRV: 31
WR155 / A1M135




Runway
VM2006P LRV: 9
WR72 / A1M72




Pavement
VMI2007P LRV: 14
WR83 / A1M83




Signal
VMI2016P LRV: 13
WR300 / A1M42




Swan
VMI2012P LRV: 75
WR291 / A1M01




Tango
VM2031 LRV: 14
WR42 / A1M42



Cherry
VM20920 LRV: 10
WR148 / A1M148




Silk
VMI2003P LRV: 10
WR310 / A1M35




Minster
VM2018P LRV: 40
WR289 / A1M265




Pitch
VM2020P LRV: 5
WR277 / A1M100




Forge
VM2015P LRV: 9
WR248 / A1M238




Temple
VM2009P LRV: 27
WR261 / A1M81




Streetlight
VMI2005P LRV: 45
WR287 / A1M79




Rock
VMI2004P LRV: 23
WR84 / A1M84




Fresco
VMI2017P LRV: 31
WR309 / A1M309




Stream
VM2001P LRV: 22
WR288 / A1M71



Arena
VM2019P LRV: 41
WR297 / A1M20




Monument
VMI2008P LRV: 23
WR305 / A1M239




Gallery
VM2011P LRV: 10
WR62 / A1M62



Mallard
VMI2013P LRV: 13
WR302 / A1M302



Roof Garden
VM2000P LRV: 23
WR262 / A1M154



Gecko
VMI2002P LRV: 18
WR308 / A1M308



! We strongly recommend carrying out a risk assessment in any area in which the installation of safety flooring is considered, focusing on the potential risk posed by contaminants from spillages. See www.altro.com/safety for more information.

Matches:
• **Altro XpressLay**
Looks great with:
• **Altro Whiterock**
• **Altro Aquarius**
• **Altro XpressLay**

globe Contributes to reducing the environmental impact of your specification:
• A+ BRE Generic Green Guide Rating for Safety Flooring, full details available at www.thegreenguide.org.uk



i For a co-ordinated appearance, colour matched **Weldrods (WR)** and **Mastics (A1M)** are available. You'll find their product codes under the relevant swatches.
LRV = Light Reflectance Value

























Stocked colours for quick delivery. Other colours are indent only and have a lead time of 8-12 weeks. For large quantities please call to confirm stock holding.

Dimensions 2m x 20m
Format ROLL
Thickness 2mm

Samples
If colour choice is critical, please request a sample of the material.

+61 3 9764 5666
info@asf.com.au

Altro Walkway 20/VM20™ Data Sheet

Flooring Type	 	EN 13845/ EN 13553	Safety flooring
Classification for use	 	EN 685	34 & 43
Slip resistance	 	TRRL EN 13845 EN 13893 DIN 51130	≥ 36 ESf DS R10
Thickness		EN 428	2 mm
Wear Layer		EN 429	2 mm
Flexibility		EN 435	Pass
Weight		EN 430	2.4 kg/m ²
Roll dimensions	 	EN 426	2 m x 20 m = 40m ²
Light fastness		EN 20105-B02	≥6
Sound insulation		ISO 140-8	5 dB
Wear resistance		EN 13845	≤10% particles lost over 50000 Cycles
Indentation		EN 433	≤ 0.10mm
Fire performance		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl-s1≥8kW/m ² pass
Chemical resistance		EN 423	Good
Caster chair abrasion		EN 425	Pass
Under floor heating		EN 12667	Suitable
Electrical behaviours		EN 1815	≤ 2kV Antistatic ≤ 109Ω (VM20SD)
VOC emissions		prEN 15052 Section 01350 AgBB/DiBf	Low/Pass/Approved





Altro Designer Slip-resistant flooring

Altro have developed a series of ranges that are catered to those front of house areas that require a designer look:



For that designer look - Altro Orchestra, Altro Operetta and Altro Serenade

One product doesn't fit all. Altro have three complementary products to meet the needs of different areas. Colourful, easy to clean and compatible with each other, they provide the harmonious look you want while giving the performance you need. Altro Orchestra provides 15dB sound reduction and comfort underfoot, Altro Operetta is a robust floor for high traffic areas and Altro Serenade has 19dB sound reduction to reduce the transfer of noise between rooms and create a calming atmosphere.



For a natural wood look - Altro Wood Safety

When you want to create a homely, comforting and familiar look but you don't want to compromise on safety, Altro Wood Safety is ideal. The range offers 16 wood-look designs, including classic, contemporary classic and on-trend – so you can vary the mood from cool and classy to warm and nurturing.



For a sustainable solution that feels like home - Altro Cantata

Altro Cantata is a blend of all the benefits of Altro XpressLay technology and uses the aesthetic design feature of Altro Pisces.





Altro Orchestra™

Typical applications:

School, kindergarten and university corridors and classrooms., Student accommodation, Hospital and care home corridors and patient / resident rooms., Retail, Home adaptations / social housing

For areas where comfort and sound reduction are important, 2.85mm Altro Orchestra has been engineered to create the ideal environment to learn and live. Low residual indentation facilitates the flexible use of equipment and furniture, including hospital beds. At the same time, the integrated impact sound insulation system cuts impact sound by up to 15dB.

It offers comfort underfoot making life easier on the feet of students and patients but particularly hard-working staff who spend countless hours on the move.

With a palette of 40 colours and designs varying from calming neutrals reflecting tones of nature, to vibrant shades, Altro Orchestra allows you to create the right atmosphere every time

! We strongly recommend carrying out a risk assessment in any area in which the installation of safety flooring is considered, focusing on the potential risk posed by contaminants from spillages.
See www.altro.com/safety for more information.

Matches:

- **Operetta**
- **Serenade**
















Looks great with:

- **Altro Whiterock**

globe icon Contributes to reducing the environmental impact of your specification:

- A+ BRE Generic Green Guide Rating for Safety Flooring, full details available at www.thegreenguide.org.uk



 Chant CH2814 LRV: 26 WR435 / A1M200	 Fusion CH2813 LRV: 49 WR434 / A1M200	 Urban CH2816 LRV: 50 WR437 / A1M200	 Swing CH2819 LRV: 49 WR440 / A1M200
	 Punk CH2822 LRV: 43 WR443 / A1M200	 Soul CH2817 LRV: 29 WR438 / A1M200	 Rap CH2820 LRV: 30 WR441 / A1M200
 Jungle CH2823 LRV: 24 WR444 / A1M200	 Club CH2815 LRV: 17 WR436 / A1M200	 Metal CH2818 LRV: 16 WR439 / A1M200	 Gospel CH2821 LRV: 17 WR442 / A1M200
 Reggae CH2801 LRV: 48 WR422 / A1M200	 Romantic CH2804 LRV: 51 WR425 / A1M200	 Classical CH2807 LRV: 50 WR428 / A1M200	 Ragtime CH2810 LRV: 53 WR431 / A1M200



i For a co-ordinated appearance, colour matched **Weldrods (WR)** and **Mastics (A1M)** are available. You'll find their product codes under the relevant swatches.
LRV = Light Reflectance Value

QUICK SHIP Stocked colours for quick delivery. Other colours are indent only and have a lead time of 8-12 weeks. For large quantities please call to confirm stock holding.


Dimensions	2m x 20m
Format	ROLL
Thickness	2.85mm



Samples
If colour choice is critical, please request a sample of the material.
+61 3 9764 5666
info@asf.com.au



House
CH2811 LRV: 26
WR432 / A1M200



Country
CH2808 LRV: 26
WR429 / A1M200




Latin
CH2803 LRV: 32
WR424 / A1M200



Pop
CH2805 LRV: 32
WR426 / A1M200




Violin
CH2834 LRV: 31
WR455 / A1M200




Chimes
CH2836 LRV: 52
WR457 / A1M200




Oboe
CH2835 LRV: 34
WR456 / A1M200



Bongo
CH2840 LRV: 27
WR461 / A1M200




Folk
CH2812 LRV: 15
WR443 / A1M200




Motown
CH2809 LRV: 10
WR430 / A1M200




Salsa
CH2802 LRV: 20
WR423 / A1M200




Drum
CH2837 LRV: 18
WR458 / A1M200




Flute
CH2833 LRV: 22
WR454 / A1M200




Trombone
CH2839 LRV: 39
WR460 / A1M200




Flamenco
CH2806 LRV: 12
WR427 / A1M200




Harp
CH2830 LRV: 28
WR451 / A1M200




Clarinet
CH2832 LRV: 34
WR453 / A1M200




Banjo
CH2826 LRV: 38
WR447 / A1M200




Bassoon
CH2831 LRV: 17
WR452 / A1M200




Guitar
CH2828 LRV: 29
WR449 / A1M200




Trumpet
CH2825 LRV: 37
WR446 / A1M200



Glockenspiel
CH2827 LRV: 23
WR448 / A1M200
























Cello
CH2829 LRV: 24
WR450 / A1M200



Piano
CH2838 LRV: 19
WR459 / A1M200



Altro Orchestra™ Data Sheet

Flooring Type	 	EN 651	Resilient Floor
Classification for use	 	EN ISO 10874	34 & 42
Slip resistance	 	EN 13893 DIN 51130	DS R10
Thickness		EN ISO 24346	2.85mm
Wear Layer		EN ISO 24340	0.7mm
Flexibility		EN ISO 24344	Pass
Weight		EN ISO 23997	2.66kg/m ²
Roll dimensions	 	EN ISO 24341	2.0m x 20.00m - 40m ²
Light fastness		EN ISO 105-BO2	≥6
Sound insulation		ISO 140-8	ca. 15dB
Wear resistance		EN 660-2	Group T
Indentation		EN ISO 24343	≤ 0.20mm
Fire performance		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Cf-s1≥ 4.5kW/m ² pass
Chemical resistance		EN ISO 26987	Good
Caster chair abrasion		EN 425	Pass
Under floor heating		EN 12667	Suitable
Electrical behaviours		EN 1815	≤ 2kV Antistatic
VOC emissions		Section 01350 / Floorscore	Pass

All information is correct at the time of print and is subject to change without prior notice. Visit us online for more information and updates. This product has never contained phthalate plasticisers.





Altro Operetta™

Typical applications:

Hospital / care home corridors and patient rooms, Retail, Schools, universities – general circulation areas, corridors

Altro Operetta is a robust floor perfect for medium to high traffic areas. It is easy to clean and maintain. It has 25 attractive, natural and contemporary colours and finishes to fit in your interior design scheme. It matches and coordinates with Altro Orchestra and Altro Serenade to create a complete look throughout.

Combine with our extensive range of Altro wall cladding: Altro Whiterock for areas requiring a hygienic surface and Altro Fortis wall protection for busy areas that need extra protection.

! We strongly recommend carrying out a risk assessment in any area in which the installation of safety flooring is considered, focusing on the potential risk posed by contaminants from spillages.
See www.altro.com/safety for more information.

Matches:


- Operetta
- Serenade

Looks great with:

- Altro Whiterock

globe Contributes to reducing the environmental impact of your specification:

- A+ BRE Generic Green Guide Rating for Safety Flooring, full details available at www.thegreenguide.org.uk



i For a co-ordinated appearance, colour matched **Weldrods (WR)** and **Mastics (A1M)** are available. You'll find their product codes under the relevant swatches.
LRV = Light Reflectance Value

QUICK SHIP Stocked colours for quick delivery. Other colours are in stock only and have a lead time of 8-12 weeks. For large quantities please call to confirm stock holding.

Dimensions 2m x 20m
Format ROLL
Thickness 2mm



Samples
If colour choice is critical, please request a sample of the material.
+61 3 9764 5666
info@asf.com.au




Waltz
OP2106 LRV: 12
WR427 / A1M200




Crescendo
OP2102 LRV: 20
WR423 / A1M200



Overture
OP2123 LRV: 24
WR444 / A1M200




Bass
OP2121 LRV: 17
WR442 / A1M200




Contralto
OP2120 LRV: 30
WR441 / A1M200




Quaver
OP2101 LRV: 48
WR422 / A1M200




Clef
OP2125 LRV: 37
WR446 / A1M200




Canon
OP2129 LRV: 24
WR450 / A1M200




Key
OP2131 LRV: 17
WR452 / A1M200




Madrigal
OP2134 LRV: 31
WR455 / A1M200




Glee
OP2136 LRV: 52
WR457 / A1M200




Acapella
OP2135 LRV: 34
WR456 / A1M200




Tenor
OP2138 LRV: 19
WR459 / A1M200

























Baroque
OP2133 LRV: 22
WR454 / A1M200



Soprano
OP2137 LRV: 18
WR458 / A1M200




Altro Operetta™ Data Sheet

Flooring Type	 	EN 10582	Resilient Floor
Classification for use	 	EN ISO 10874	34 & 43
Slip resistance	 	EN 13893 DIN 51130	DS R10
Thickness		EN ISO 24346	2mm
Wear Layer		EN ISO 24340	0.7mm
Flexibility		EN ISO 24344	Pass
Weight		EN ISO 23997	2.66kg/m ²
Roll dimensions	 	EN ISO 24341	2.0m x 20.00m - 40m ²
Light fastness		EN ISO 105-BO2	≥6
Sound insulation		ISO 140-8	ca. 4dB
Wear resistance		EN 660-2	Group T
Indentation		EN ISO 24343	≤ 0.10mm
Fire performance		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl-s1 ≥ 8kW/m ² pass
Chemical resistance		EN ISO 26987	Good
Caster chair abrasion		EN 425	Pass
Under floor heating		EN 12667	Suitable
Electrical behaviours		EN 1815	≤ 2kV Antistatic
VOC emissions		Section 01350 / Floorscore	Pass

All information is correct at the time of print and is subject to change without prior notice. Visit us online for more information and updates. This product has never contained phthalate plasticisers.

[≡ Back to contents](#)





Altro Serenade™

Typical applications:

Kindergarten playrooms, Hotel rooms, Offices, Care homes, Anywhere where the passage of sound must be prevented between storeys

Silence is golden. Whether softening the sounds of little feet or maximising privacy at work or leisure, acoustic Altro Serenade is more than up to the task. At 3.9mm thick and with 19dB impact sound insulation, not only does it reduce noise, it provides a high level of comfort underfoot, making it a great solution for well-used spaces. With 15 colour and design options, it matches and coordinates with Altro Orchestra and Altro Operetta. Combine with our extensive range of Altro wall cladding, Altro Whiterock, for areas requiring a hygienic surface.

! We strongly recommend carrying out a risk assessment in any area in which the installation of safety flooring is considered, focusing on the potential risk posed by contaminants from spillages. See www.altro.com/safety for more information.

Matches:


- Operetta
- Orchestra

Looks great with:

- Altro Whiterock

globe Contributes to reducing the environmental impact of your specification:

- A+ BRE Generic Green Guide Rating for Safety Flooring, full details available at www.thegreenguide.org.uk



i For a co-ordinated appearance, colour matched **Weldrods (WR)** and **Mastics (A1M)** are available. You'll find their product codes under the relevant swatches.
LRV = Light Reflectance Value












QUICK SHIP Stocked colours for quick delivery. Other colours are indent only and have a lead time of 8-12 weeks. For large quantities please call to confirm stock holding.


Dimensions	2m x 20m
Format	ROLL
Thickness	3.9mm



Samples
If colour choice is critical, please request a sample of the material.
+61 3 9764 5666
info@asf.com.au

Altro Serenade™ Data Sheet

Flooring Type		EN 651	Resilient Floor
Classification for use		EN ISO 10874	34 & 42
Slip resistance		EN 13893 DIN 51130	DS R10
Thickness		EN ISO 24346	3.9mm
Wear Layer		EN ISO 24340	0.7mm
Flexibility		EN ISO 24344	Pass
Weight		EN ISO 23997	2.9kg/m ²
Roll dimensions		EN ISO 24341	2.0m x 20.00m - 40m ²
Light fastness		EN ISO 105-BO2	≥6
Sound insulation		ISO 140-8	ca. 19dB
Wear resistance		EN 660-2	Group T
Indentation		EN ISO 24343	≤ 0.20mm
Fire performance		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Cf-s1≥ 4.5kW/m ² pass
Chemical resistance		EN ISO 26987	Good
Caster chair abrasion		EN 425	Pass
Under floor heating		EN 12667	Suitable
Electrical behaviours		EN 1815	≤ 2kV Antistatic
VOC emissions		Section 01350 / Floorscore	Pass



All information is correct at the time of print and is subject to change without prior notice. Visit us online for more information and updates. This product has never contained phthalate plasticisers.



Altro Wood™ Safety



Typical applications:

Public spaces which are mainly subject to foot traffic, such as entrance areas, care home corridors, school corridors. Student accommodation.

When you want to create a homely, comforting and familiar look but you don't want to compromise on safety, Altro Wood Safety is ideal. The range offers 16 wood-look designs, including classic, contemporary classic and on-trend – so you can vary the mood from cool and classy to warm and nurturing.

Altro Wood Safety works well with contemporary décor such as metal and glass areas, mood lighting, vibrant colours and monotone themes. It's a great choice if you need to avoid any colour clashes.

The flooring features Altro Easyclean Maxis PUR Technology for long term cleanability and easier maintenance.

For specialist locations such as kitchens, canteens and food preparation areas, where grease, oils or fats may be present, we recommend Altro Stronghold 30. For bathrooms and wet rooms we recommend Altro Aquarius.

! We strongly recommend carrying out a risk assessment in any area in which the installation of safety flooring is considered, focusing on the potential risk posed by contaminants from spillages. See www.altro.com/safety for more information.

Looks great with:

- Altro Whiterock White
- Altro Whiterock Satins
- Altro Whiterock Chameleon
- Altro Aquarius

🌍 Contributes to reducing the environmental impact of your specification:

- A+ BRE Generic Green Guide Rating for Safety Flooring, full details available at www.thegreenguide.org.uk



Bleached Oak
WSA2001 LRV: 52
WR335 / A1M335



Autumn Maple
WSA2005 LRV: 24
WR339 / A1M339



Farmhouse Oak
WSA2004 LRV: 38
WR338 / A1M27



Oak Traditions
WSA2013 LRV: 25
WR353 / A1M225



Vintage Cherry
WSA2002 LRV: 22
WR336 / A1M239



Urban Cherry
WSA2003 LRV: 17
WR337 / A1M337



Rustic Oak
WSA2006 LRV: 37
WR340 / A1M340



Washed Oak
WSA2015 LRV: 38
WR347 / A1M200



Ranch Oak
WSA2021 LRV: 51
WR335 / A1M335



Worn Oak
WSA2023 LRV: 19
WR322 / A1M239



Manor Oak
WSA2016 LRV: 7
WR348 / A1M200



i For a co-ordinated appearance, colour matched **Weldrods (WR)** and **Mastics (A1M)** are available. You'll find their product codes under the relevant swatches.
LRV = Light Reflectance Value

Stocked colours for quick delivery. Other colours are in stock only and have a lead time of 8-12 weeks. For large quantities please call to confirm stock holding.

Dimensions 2m x 20m
Format ROLL
Thickness 2mm



Samples
If colour choice is critical, please request a sample of the material.
 +61 3 9764 5666
 info@asf.com.au



Mountain Oak
WSA2022 LRV: 22
WR339 / A1M339



Stately Oak
WSA2025 LRV: 10
WR468 / A1M62



Spring Maple
WSA2018 LRV: 27
WR352 / A1M352



Walnut Noir
WSA2011 LRV: 6
WR345 / A1M62



Antique Walnut
WSA2007 LRV: 15
WR341 / A1M160



Deep Bamboo
WSA2019 LRV: 21
WR342 / A1M224




Noble Oak
WSA2024 LRV: 17
WR467 / A1M467





















Light Beech
WSA2017 LRV: 43
WR462 / A1M462



Washed Bamboo
WSA2020 LRV: 42
WR463 / A1M392




Altro Wood™ Safety Data Sheet

Flooring Type		EN 13553	Safety flooring EN 13845
Classification for use		EN ISO 10874	
Slip resistance		TRRL EN 13845 EN 13893 DIN 51130	≥ 36 ESf DS R10
Thickness		EN ISO 24346	2 mm
Wear Layer		EN ISO 24340	0.7 mm
Flexibility		EN 435	Pass
Weight		EN ISO 23977	2.66 kg/m ²
Roll dimensions		EN ISO 24341	2 m x 20 m = 40m ²
Light fastness		EN 20105-B02	≥6
Sound insulation		ISO 140-8	ca. 4dB
Wear resistance		EN13845	≤10% particles lost over 50000 Cycles
Indentation		EN ISO 24343-1	≤ 0.10mm
Fire performance		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl-s1≥8kW/m ² pass
Chemical resistance		EN 423	Good
Caster chair abrasion		EN 425	Pass
Under floor heating		EN 12667	Suitable
Electrical behaviours		EN 1815	≤ 2kV Antistatic
VOC emissions		AgBB/DiBt	Approved

All information is correct at the time of print and is subject to change without prior notice. Visit us online for more information and updates.
This product has never contained phthalate plasticisers.
www.altro.com, www.altroscandess.se, www.altro.de

[≡ Back to contents](#)





Altro Wood™ Safety Comfort

Typical applications:

Public spaces which are mainly subject to foot traffic, such as Corridors and classrooms in schools, kindergartens, universities. Student accommodation. Hospital / care home corridors and patient rooms. Retail. Home adaptations / social housing.

Altro Wood Safety Comfort offers aesthetics combined with comfort. It's an ideal choice for areas that need to look good while helping to give comfort underfoot. This 2.85mm thick option offers 14dB sound reduction, which is great for noisy environments such as hospitals and kindergartens.

It is also suitable for wheeled traffic and low residual indentation facilitates the flexible use of equipment and furniture, including hospital beds.

With matching design and colour options across this range and Altro Wood Safety you can achieve a consistent look in different areas. Select from the ranges for the right technical performance required for the area.

The flooring features Altro Easyclean Maxis PUR Technology for long term cleanability and easier maintenance.

For specialist locations such as kitchens, canteens and food preparation areas, where grease, oils or fats may be present, we recommend Altro Stronghold 30. For bathrooms and wet rooms we recommend Altro Aquarius.

! We strongly recommend carrying out a risk assessment in any area in which the installation of safety flooring is considered, focusing on the potential risk posed by contaminants from spillages. See www.altro.com/safety for more information.

Looks great with:

- Altro Whiterock White
- Altro Whiterock Satins
- Altro Whiterock Chameleon
- Altro Aquarius

globe icon Contributes to reducing the environmental impact of your specification:


- A+ BRE Generic Green Guide Rating for Safety Flooring, full details available at www.thegreenguide.org.uk



			
	Regent Oak WSASC2825 LRV: 10 WR468 / A1M62	Classic Walnut WSASC2807 LRV: 15 WR341 / A1M160	Veteran Oak WSASC2822 LRV: 22 WR339 / A1M339 
			
	Warm Maple WSASC2805 LRV: 24 WR339 / A1M339	Soft Oak WSASC2804 LRV: 38 WR338 / A1M27 	Field Oak WSASC2806 LRV: 37 WR340 / A1M340
			
Light Bamboo WSASC2820 LRV: 42 WR463 / A1M392 	Royal Oak WSASC2823 LRV: 19 WR322 / A1M239 	Reclaimed Oak WSASC2821 LRV: 51 WR335 / A1M335 	
			
Antique Cherry WSASC2802 LRV: 22 WR239 / A1M239 	Aged Oak WSASC2815 LRV: 38 WR347 / A1M347		

CE
EN14041
Manufactured by:
Altro Ltd, Works Road
Letchworth Garden City
SG6 1NW
United Kingdom

i For a co-ordinated appearance, colour matched **Weldrods (WR)** and **Mastics (A1M)** are available. You'll find their product codes under the relevant swatches.
LRV = Light Reflectance Value



















 Stocked colours for quick delivery. Other colours are in stock only and have a lead time of 8-12 weeks. For large quantities please call to confirm stock holding.

Dimensions 2m x 20m
Format ROLL
Thickness 2.85mm



Samples
If colour choice is critical, please request a sample of the material.
+61 3 9764 5666
info@asf.com.au

Altro Wood™ Safety Comfort Data Sheet

Flooring Type		EN 13845 / EN 651	Safety flooring
Classification for use		EN ISO 10874	34 & 42
Slip resistance		PTV EN 13845 EN 13893 DIN 51130	≥ 36 ESf DS R10
Thickness		EN ISO 24346	2.85mm
Wear Layer		EN ISO 24340	0.7 mm
Flexibility		EN ISO 24344	Pass
Weight		EN ISO 23997	2.66 kg/m ²
Roll dimensions		EN ISO 24341	2 m x 20 m = 40m ²
Light fastness		EN 20105-B02	≥6
Sound insulation		ISO 140-8	ca. 14dB
Wear resistance		EN 660-2	≤10% particles lost over 50000 Cycles
Indentation		EN ISO 24343	≤ 0.20mm
Fire performance		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Cf-s1≥ 4.5kW/m ² pass
Chemical resistance		EN ISO 26987	Good
Caster chair abrasion		EN 425	Pass
Under floor heating		EN 12667	Suitable
Electrical behaviours		EN 1815	≤ 2kV Antistatic
VOC emissions		IAC Gold	Pass



All information is correct at the time of print and is subject to change without prior notice. Visit us online for more information and updates. This product has never contained phthalate plasticisers.



Altro Cantata™

Typical applications:

Corridors in hospitals, residential care homes and education buildings. Patient rooms in hospitals. General circulation areas in retail, kindergartens, schools and universities.

Altro Cantata is a compact 2.2mm floor. Available in 16 soft-look shades ranging from subtle natural tones to vivid colours, it sets the tone for corridors and general areas in a whole range of environments. As well as creating stunning surroundings, Altro Cantata is installed without using an adhesive making installation time, and the disruption that goes with it, minimal.

Altro Cantata, which has a smooth finish, uses our award-winning adhesive-free installation method. Being adhesive-free Altro Cantata gives you, and those who walk on it, a whole symphony of benefits, from reduced downtime to 100% recyclability.

Altro Cantata is a durable floor that can tolerate medium to heavy-duty traffic, meaning that it performs in busy spaces as you would expect and want it to. It is also easy to clean, ensuring that its striking shades look as good as on the day of installation, long-term.

Altro Cantata harmonises perfectly with other Altro floors, plus Altro Whiterock™ hygienic wall cladding and the Altro Fortis™ wall, door and corner protection system, meaning we can help you create the look and feel you want, throughout.


! We strongly recommend carrying out a risk assessment in any area in which the installation of safety flooring is considered, focusing on the potential risk posed by contaminants from spillages. See www.altro.com/safety for more information.

Looks great with:

- Altro Whiterock
- Altro Aquarius
- Altro XpressLay

globe Contributes to reducing the environmental impact of your specification:

- A+ BRE Generic Green Guide Rating for Safety Flooring, full details available at www.thegreenguide.org.uk



i For a co-ordinated appearance, colour matched **Weldrods (WR)** and **Mastics (A1M)** are available. You'll find their product codes under the relevant swatches.
LRV = Light Reflectance Value



















QUICK SHIP Stocked colours for quick delivery. Other colours are indent only and have a lead time of 8-12 weeks. For large quantities please call to confirm stock holding.

Dimensions 2m x 20m
Format ROLL
Thickness 2.2mm




Samples
If colour choice is critical, please request a sample of the material.
+61 3 9764 5666
info@asf.com.au

Altro Cantata™ Data Sheet

Flooring Type		EN 13845	Resilient Floor
Classification for use		EN ISO 10874	34 & 43
Slip resistance		EN 13893 DIN 51130	DS R10
Thickness		EN ISO 24346	2.2 mm
Wear Layer		EN ISO 24340	0.8 mm
Flexibility		EN ISO 24344	Pass
Weight		EN ISO 23997	2.6kg/m ²
Roll dimensions		EN ISO 24341	2.0m x 20.00m - 40m ²
Light fastness		EN ISO 105-BO2	≥6
Sound insulation		ISO 140-8	5 dB
Wear resistance		EN 13845	≤10% particles lost over 50000 Cycles
Indentation		EN ISO 24343	≤ 0.10mm
Fire performance		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl-s1≥8kW/m ² pass
Chemical resistance		EN 423	Good
Caster chair abrasion		EN 425	Pass
Under floor heating		EN 12524	Suitable
Electrical behaviours		EN 1815	≤ 2kV Antistatic
VOC emissions		Section 01350 / Floorscore	Pass

** Caution Ketone/Aromatic Solvents. Please contact Altro for further technical advice regarding staining and chemical resistance. This product has never contained phthalate plasticisers. All information is correct at the time of print and is subject to change without prior notice. Visit us online for more information and updates.

[≡ Back to contents](#)





Samples

If colour choice is critical, please request a sample of the material

 1800 673 441 (toll free)

 info@asf.com.au



 1800 673 441 (toll free)  info@asf.com.au



Altro, the future is safer with altro, Altro Aquarius, Altro Suprema, Altro Walkway 20, Altro Classic 25, Altro Stronghold 30, Altro Wood Safety, Altro Everlay, Altro Whiterock, Altro Whiterock Chameleon, Altro Whiterock Digiclad, Altro Whiterock Splashbacks, Altro Whiterock Satins, Altro Whiterock Flexijoint, AltroProof, Altroprime, AltroClean 44, AltroFix, Altro Easyclean Maxis Technology, Altro Easyclean Technology, Altro Easyclean Original, Altro Easyclean Maxis PUR and SampleExpress are trademarks of Altro Limited.

Content correct at time of going to print. Altro reserves the right to change any detail. © Copyright Altro 2017

asf.com.au