

How to specify Whelan Thermal Tap

1. To have solid state temperature control, designed to contain water within 1°C of boiling point at all times when in operation.
2. To have 350 Kpa pressure limiting valve supplied as standard.
3. To have no connection to drain - no tundish.
4. To have 1/4 turn solid brass tap with anti-flood tap body designed to prevent damage to bench top due to flooding.
5. To have optional lever handle fitted for disable aid.
6. To have optional extended tap body of up to maximum of 150mm (from bottom of spout to base of tap).
7. To have optional twin filter manifold supplied (if required) to improve water quality.
8. To have optional integral 24 hour 7 day programmable timer to save energy.
9. To have choice of 6 different sizes of unit with different capacity of boiling water to suit your need.
10. To be installed in accordance with the manufacturer's instruction.

Selection Chart Whelan Thermal tap

To select the correct size unit for your needs simply determine the maximum number of cups of boiling water are required at any one time, then choose the corresponding model from the chart below.

MODEL NO.	No. OF CUPS SERVED	CUP/Hr RECOVERY	TOTAL KW	PHASE	VOLTAGE	HEIGHT mm	WIDTH mm	DEPTH mm
TT 6	6	80	1.8	1	1/240	370	195	200
TT 6T★	6	80	1.8	1	1/240	380	235	235
TT 10	10	110	2.4	1	1/240	380	195	235
TT 10T★	10	110	2.4	1	1/240	380	235	235
TT 20	20	110	2.4	1	1/240	440	195	235
TT 20T★	20	110	2.4	1	1/240	480	235	235
TT 30	30	110	2.4	1	1/240	535	195	235
TT 30T★	30	110	2.4	1	1/240	535	235	235
TT 40	40	110	2.4	1	1/240	455	330	345
TT 40T★	40	110	2.4	1	1/240	455	330	345
TT 60	60	110	2.4	1	1/240	535	330	345
TT 60T★	60	110	2.4	1	1/240	535	330	345

Water Chiller for Original Twin Tap

MODEL NO.	PHASE	GAS	HEIGHT mm	WIDTH mm	DEPTH mm
UWC/1	1/240	R. 134A Env. Friendly	295	400	200
UWC/2	1/240	R. 134A Env. Friendly	278	408	295

Specifications are subject to change without notice. T★ = Unit fitted with programmable timer 1 Litre = 5 x 200 ml cups

WARRANTY:

12 months from date of installation. Filter cartridge is excluded from this warranty as cartridge life is depended on water quality and consumption rate.

Typical Installation

