

EXPONA **Simplay**

DESIGN VINYL



Natural Rustic Oak 2517



White Rustic Pine **2513**



Grey Ash **2512**

EXPOVA

Simplay

DESIGN VINYL

Grey and white shades provide a modern, sleek and contemporary look





Natural Rustic Pine **2514**

Natural and earthy tones complement a wide range of spaces and furnishings



Light Classic Oak **2520**



Medium Classic Oak **2521**



Brown Rustic Oak **2515**



Brown Mystique Wood **2519**

EXPOVA

Simplay

DESIGN VINYL

Rustic and mystique woods provide texture and depth to any room



Grey Mystique Wood **2518**



EXPOVA

Simplay

DESIGN VINYL

Concrete has a raw material feel that is understated yet inviting and very on-trend



Warm Grey Concrete **2568**



Dark Grey Concrete **2569**



Light Classic Oak **2520** 185mm x 1505mm



Natural Ash **2511** 177mm x 1219mm



Natural Rustic Oak **2517** 177mm x 1219mm



Medium Classic Oak **2521** 185mm x 1505mm



Brown Rustic Oak **2515** 177mm x 1219mm



Brown Mystique Wood **2519** 185mm x 1505mm



White Rustic Pine **2513** 177mm x 1219mm



Natural Rustic Pine **2514** 177mm x 1219mm



Grey Ash **2512** 177mm x 1219mm




Grey Mystique Wood **2518** 185mm x 1505mm



Dark Grey Finline **2510** 177mm x 1219mm



Light Grey Concrete **2567**
600mm x 600mm



Warm Grey Concrete **2568**
600mm x 600mm



Dark Grey Concrete **2569**
600mm x 600mm

All planks and tiles have bevelled edges








Reproductions in printing and photography are for guidance only. For colour and product selection, an original sample is recommended.

“EASIER TO INSTALL”

- The quickest laying product in the market
- Easy replacement of individual elements
- Surface covering below remains intact
- Reduced subfloor preparation
- Product reusability
- No click systems

- ① PUR surface treatment
- ② Clear wear layer
- ③ Decoration layer
- ④ Stabilisation layer
- ⑤ Glass fibre dimension stabilisation layer
- ⑥ Load-bearing layer
- ⑦ Special backing structure



TECHNICAL DATA	Characteristics	Standards	EXPONA SimpLay
<p>SimpLay DESIGN VINYL</p>      	Type of floorcovering	EN 649 EN ISO 10582	heterogeneous, PVC
	Surface treatment		
	Total weight	EN 430 EN ISO 23997	8000 g/m ²
	Performance classification	EN 685 EN ISO 10874	23 34 43
	Gauge	EN 428 EN ISO 24346	5.0mm
	Wear layer thickness	EN 429 EN ISO 24340	0.7mm
	Packaging plank size	EN 427 EN ISO 24342	10 @ 177.8 x 1219.2mm = 2.17m ² 8 @ 185.0 x 1505.0mm = 2.23m ²
	Packaging tile size	EN 427 EN ISO 24342	6 @ 600.0 x 600.0mm = 2.16m ²
	Abrasion group	EN 660-2 EN ISO 10582	T Typ I
	Residual indentation	EN 433 EN ISO 24343-1	pass
	Colour fastness to artificial light	EN ISO 105-B02	level ≥ 6 method A
	Behaviour to fire	EN 13501-1	B _{fl} - s1
	Slip resistance	DIN 51130 EN 13893	R10 DS
	Chemical resistance	EN 423 EN ISO 26987	*
Castor chair suitability	EN 425 ISO 4918	yes type W EN 12 529	
Underfloor heating suitability	EN 1264-2	suitable max. 27° C	
Sound reduction	EN 140-8 EN ISO 10140-3	9 dB	
AgBB VOC test		below quantifiable levels	

* Resistant depending on concentration and time of exposure, in case of increased impact of oils, grease, acids, alkalis and other aggressive chemicals - please contact Polyflor.

Subject to changes for reasons of technical further development.

CUSTOMER GUARANTEE

All products purchased from the range are guaranteed for 15 Years Residential and 10 Years Commercial against normal wear and tear in the recommended environment provided they have been fitted correctly and maintained in accordance with the manufacturer's instructions. In order to make a claim, customers must apply in writing indicating where their flooring was purchased and provide satisfactory proof of purchase. This guarantee only applies in the event of the visible wearing out of the decorative pattern on the surface within the 15 Years Residential or 10 Years Commercial guarantee period from the time of purchase and provided the flooring has been subject to normal usage in the recommended environment. It does not cover general misuse and we suggest that adequate UV protection be taken against products being installed in direct sunlight as fading may occur. It is the manufacturer's recommendation that felt or teflon pads are used for protection under chairs and other furniture which will help to prevent scratching and marring of your floor's finish. When moving any heavy objects please place a plywood panel over your vinyl floor. In the event of the manufacturers of Expona SimpLay accepting that a claim is valid under this guarantee, they will either repair the flooring or supply replacement flooring free of charge. In the unlikely event of the flooring no longer being in stock, flooring of equivalent quality will be provided.

expona Simplay

DESIGN VINYL



Natural Ash 2511



Polyflor Australia Pty Ltd

ABN 68 007 134 518

59-65 Wedgewood Road
Hallam VIC 3803
Australia

P: 1800 777 425

F: 03 9215 4444

E: sales@polyflor.com.au

www.polyflor.com.au

Polyflor New Zealand

100 Plunket Avenue
Manukau Auckland 2104
New Zealand

P: 0800 765 935

F: 0800 846 737

E: sales@polyflor.co.nz

www.polyflor.co.nz

