

Aluminium Friction Stays



Doric
New Zealand

Application

The Doric FS Series friction stay has been designed to suit most residential awning applications on aluminium, timber and uPVC windows.

Features

- Extruded aluminium profiles
- Spin riveted connection on all joints
- Factory set friction to eliminate adjustment on site
- Geometrically accurate to ensure smooth positive operation
- Powder coated to increase protection from corrosion



Model	Size	Stack Height (+ 1mm)	Max. Sash Height	Max. Sash Weight	Opening
FS0001	236mm	13mm	750mm	6 kg	45 deg
FS0002	330mm	13mm	1000mm	9 kg	35 deg
FS0003	515mm	13mm	1300mm	12kg	27 deg
FS0004	440mm	13mm	1200mm	43kg	20 deg
FS0004	440mm	13mm	1500mm	20kg	20 deg
FS0004	440mm	13mm	1800mm	15kg	20 deg

Model	A	B	C	D	E	F	G	H	I	J	K
FS0001	110	65	29	-	30	235	172	-	-	55.5	54
FS0002	198	158	79	-	30	330	266	-	133	65	54
FS0003	310	258	172	86	30	512	450	-	296	148	54
FS0004	228	212	160	52	8	440	390	-	240	90	40

Note: Letters apply to dimension diagram below (mm).

