





TUDOR



To view colour swatches for each state refer to www.monier.com.au

A look suited to both traditional steep pitches and contemporary architecture, Tudor gives classic style a fresh look with its clean, defined lines and geometric design.



TILES USAGE WITH WASTAGE (+/-2%)
Approx. 11.0 tiles per sqm.

TILE COVERAGE (±2%)
Approx. 9.90 tiles per sqm.

DIMENSIONS (±2%)
Length 420mm
Width 329mm

MASS (±2%)
Per tile 4.50kg
Per m² 44.0kg

HEAD LAP ADJUSTMENT (MM)
80 – 110

FEATURE
Square

COLOUR APPLICATION
Colour On

RECOMMENDED BONDING
Straight bond

ROOF PITCH
Minimum Pitch with Sarking: 15°
Minimum Pitch without Sarking: 20°



Please consult the Design Guide at Monier.com.au for installation requirements applicable to your project.

Please refer to AS2049 for acceptable tolerance to these measurements stated above.



CONCRETE ACCESSORIES

ACCESSORY	LENGTH (MM)	WIDTH (MM)	HEIGHT (MM)	ANGLE (DEGREE)	WEIGHT (KG)
Parbarge 	420	248	126	84	4.9
Starter 	420	250	80	120	2.8
3-Way Apex (butt & overlapping) 	391.7	413.3	135	135	3.8
Ridge 	420	250	80	120	3.4
Ridge Saddle 	205	250	175	120	3.3
Gable Finial — Scroll 	245	240	280	120	5.1
Apex Finial — Scroll 	385	420	320	120	6
Spoon- Starter 	410	395	125	120	6