

**Panasonic**

# ELEVATE YOUR BATHROOM EXPERIENCE

WITH PANASONIC'S SMART THERMO VENTILATOR FV-30BY1



Upgrade your bathroom with the Panasonic Thermo Ventilator FV-30BY1 – where comfort meets innovation

# INNOVATIVE AND RELIABLE

## HEATER PROTECTIVE LOUVER

Safety is enhanced with the use of highly flame-retardant plastic.

## CERTIFIED WATERPROOF TEST

The main body of The Heater passes IPX2 Water Resistance Test. Reliable and safe to use.

## TEMPERATURE-CONTROL MATERIAL

With the use of PTC material, the Heater's temperature can be controlled at below 237°C.

## THERMAL CUT-OFF

Power supply will cut off automatically when temperature of The Heater exceeds the threshold.

## PRODUCT SPECIFICATION



Model		FV-30BY1		FV-30BG3	
Voltage [V]		230	240	230	240
Frequency [Hz]		50		50	
PTC Heater		✓		✓	
Adjustable Air Direction		-		✓	
Filter		Dust filter		Anti-bacteria filter	
Water-resistant Remote Control		✓		✓	
Shut-off Timer		✓		✓	
Rated Current [A]		7.0	6.7	7.2	6.9
Ventilation Air Volume [m³/h]		150	155	170	180
Power Consumption [W] (at 23°C)		1600	1620	1670	
Power Consumption [W] (at 40°C)		1470	1490	1500	
Noise [dB(A)]	Heat	45	45	46	46
	Vent	45	46	38	39
Weight [kg]		3.7		5.2	
Product Dimension [mm] (Louver excluded)		260 x 280 x 150		270 x 290 x 180	
Cut out Size [mm]		264 x 284		300 x 300	

- Power consumption and rated current are obtained in the factory default state, and the test ambient temperature is 40°C.
- Air volume, electric specification and noise value are measured when static Pressure is 0 Pa.
- Noise value is the weighted sound pressure grade A, which is the central value measured by this company, its tolerance range is from +3 to -7. The method to measure is as follows: in an anechoic chamber, measure noise value first 1m away from the left, right and beneath of the sample, then get the averaged value.

# Panasonic

aircon.panasonic.com.au

\*Actual colours may vary slightly from shown.  
\*Specifications are subject to change without prior notice.