


DECORLUX & DECORSLOT MATERIAL SAFETY DATA SHEET



SECTION ONE: IDENTIFICATION OF MATERIAL AND SUPPLIER

PRODUCT NAME: DecorLux and DecorSlot
RECOMMENDED USE: Prefinishing of wall and ceiling panels
SUPPLIER NAME: Decor Systems Australia
ADDRESS: 6 Millennium Court, Silverwater
 NSW 2128, Australia
PHONE: +612 9748 1800
FAX: +612 9648 1800
EMAIL: info@decorsystems.com.au
WEBSITE: www.decorsystems.com.au

SECTION TWO: HAZARD IDENTIFICATION

Hazard Classification: Classified as hazardous according to NOHSC criteria. Not classified as a dangerous good by the criteria of the ADG Code.

SECTION THREE: COMPOSITION/ INFORMATION ON INGREDIENTS

SUBSTANCES:

INGREDIENT	FORMULA	CONC.	CAS NUMBER
Silicia, Crystalline and quartz	Si-Q2	20-30%	14808-60-7
Calcium Silicate		<60%	1344-95-2
Water	H2O	<15%	7732-18-5
Cellulose		<15%	9004-34-6

SECTION FOUR: FIRST AID MEASURES

INGESTION: For advice, contact a Poisons Information Center on 13 11 26 (Australia wide) or a doctor. Ingestion is considered unlikely due to product form.

EYES: Flush with copious amounts water holding eyelids open. Take care not to rinse contaminated water into the non-affected eye. If symptoms persist, seek medical attention.

SKIN: Gently flush affected areas with water. If irritation develops, seek medical attention.

INHALATION: Remove from exposed area. If symptoms develop, seek medical attention.

ADVICE TO DOCTOR: Treat symptomatically.

SECTION FIVE: FIRE FIGHTING MEASURES

FLAMMABILITY: Nonflammable. No fire or explosion hazard exists.

FIRE AND EXPLOSION: Nonflammable. No fire or explosion hazard exists.



CONTACT
 1800 835 035
 info@decorsystems.com.au

WEBSITE
 decorsystems.com.au

© DECOR SYSTEMS 2021

EXTINGUISHING: NONFLAMMABLE.

HAZCHEM CODE: NONE ALLOCATED.

SECTION SIX: ACCIDENTAL RELEASE MEASURE

SPILLAGE: Collect and reuse where possible.

SECTION SEVEN: EXPOSURE CONTROLS/ PERSONAL PROTECTION

EXPOSURE STANDARDS	NOHSC [1003 (1005)] AUSTRALIA/OSH NEW ZEALAND (MAY 1995)
Silica, crystalline-Quartz (14808-60-7)	ES-TWA: 0.1 mg/m ³ (Silica Quartz, respirable, NOHSC) ES-TWA: 0.1 mg/m ³ (QLD); 0.15 mg/m ³ (NSW)
Calcium Silicate (1344-95-2)	ES-TWA: 10 mg.m ³ WES: 10 mg/m ³
Cellulose (9004-34-6)	ES-TWA: 10 mg/m ³ (inspirable dust) WES: 10 mg/m ³

PERSONAL PROTECTIVE EQUIPMENT: No personal protective equipment is normally required. If cutting or sanding with potential for dust generation, wear cotton gloves, dust-proof goggles, leather boots and a Class P1 (Particulate) Respirator.

SECTION EIGHT: HANDLING AND STORAGE

HANDLING: Use safe work practices to avoid skin or eye contact and inhalation. Observe good personal hygiene. Prohibit eating, drinking and smoking in contaminated areas. Wash hands before eating. Remove contaminated clothing and protective equipment before entering eating areas.

STORAGE: Store in a cool dry well-ventilated area away from oxidising areas, acids, and foodstuffs. Ensure product is adequately labeled, protected from physical damage and sealed when not in use.

SECTION NINE: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Tinted or primed finish grey flat sheets

ODOUR: Slight odour

PH: Not available

VAPOUR PRESSURE: Not available

VAPOUR DENSITY: Not available

BOILING POINT: Not available

MELTING POINT: Not available



CONTACT
1800 835 035
info@decorsystems.com.au

WEBSITE
decorsystems.com.au

© DECOR SYSTEMS 2021

EVAPORATION RATE: Not available

SOLUBILITY IN WATER: Not available

SPECIFIC GRAVITY: 1.3–1.7

% VOLATILES: Not available

FLAMMABILITY: Non Flammable

FLASH POINT: Not relevant

UPPER EXPLOSION LIMIT: Not relevant

LOWER EXPLOSION LIMIT: Not relevant

AUTO IGNITION TEMPERATURE: Not available

SECTION TEN: STABILITY AND REACTIVITY

REACTIVITY: Incompatible with oxidising agents (eg peroxide) and acids (eg hydrochloric acid).

DECOMPOSITION PRODUCTS: May evolve toxic gases if heated to decomposition

SECTION ELEVEN: TOXICOLOGICAL INFORMATION

TOXICOLOGY DATA:

Cellulose (9004-34-6)

LC50 (inhalation): > 5800 mg/m³/4 hours (rat)

LD50 (skin): > 2000 mg/kg (rabbit)

LD50 (ingestion): > 5000 mg/kg (rat)

HEALTH HAZARD SUMMARY: Low toxicity – irritant. Under normal conditions of use this product is not anticipated to present a hazard unless product is drilled, cut or sanded with the generation of irritating/slightly corrosive dust. Use safe work practices to avoid dust generation and inhalation. Chronic exposure to crystalline silica may cause lung fibrosis (silicosis) and it is classified as carcinogenic to humans (IARC Group 1)

INHALATION: Not applicable. An inhalation hazard is not anticipated unless this material is cut, drilled or sanded with dust generation, which may result in mucous irritation of the upper respiratory tract with over exposure. Crystalline silica is classified as carcinogenic to humans (IARC Group 1).

INGESTION: Not applicable. Due to product form, ingestion is considered highly unlikely.

SKIN: Not applicable. If dust is generated, prolonged exposure may result in irritation, itching, redness, rash and possible dermatitis.

EYE: Irritant. Exposure to dust may result in irritation, pain, redness, and conjunctivitis.



CONTACT
1800 835 035
info@decorsystems.com.au

WEBSITE
decorsystems.com.au

© DECOR SYSTEMS 2021

**SECTION TWELVE:
ECOLOGICAL
INFORMATION**

ENVIRONMENT: Limited ecotoxicity data was available for this product at the time this report was prepared. Ensure appropriate measures are taken to prevent this product from entering the environment.

**SECTION THIRTEEN:
DISPOSAL
CONSIDERATIONS**

WASTE DISPOSAL: Reuse where possible. No special precautions are required for this product.

LEGISLATION: Dispose of in accordance with relevant local legislation.

**SECTION
FOURTEEN:
TRANSPORT
INFORMATION:**

Not classified as Dangerous Goods, according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

**SECTION FIFTEEN:
REGULATORY
INFORMATION**

Poisons Schedule: None allocated

**SECTION
SIXTEEN: OTHER
INFORMATION**

Respirators: In general, the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or sir supplied respirators should be considered where prolonged or repeated use is necessary.

ABBREVIATIONS:

Mg/m³: milligrams per cubic metre

Ppm: parts per million

TWA/ES: Time Weighted Average or Exposure Standard

pH: relates to hydrogen ion concentration – this value will relate to a scale of 0–14, where 0 is highly acidic, and 14 is highly alkaline.

CAS#: Chemical Abstract Service Number – used to uniquely identify chemical compounds.

M: moles per litre, a unit of concentration.

IARC: International Agency for Research on Cancer

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained in this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentrations and the availability of engineering controls should be considered before final selection of personal protective equipment is made. Information provided by Risk Management Technologies is summarized for ease of use. Additional technical information is available upon request.

GET IN TOUCH

CONTACT
1800 835 035
info@decorsystems.com.au

DECORSYSTEMS.COM.AU

