

WINDOWS AND DOORS





Artisan Architectural

Artisan Architectural is Capral Aluminium's Architectural product range.

Featuring slim lines, various sill and panel configurations, and available in a range of popular colours, Artisan is a suitable option for the high demands of commercial and domestic applications.

Artisan looks good in either a traditional or contemporary décor, making it the ideal choice for homeowners, builders, designers and architects alike.

Supplied from Capral's LocAl® Green Lower Carbon Aluminium with CO²e of 8t CO2e/1tAl. Significantly lower carbon emissions than global averages for primary aluminium, from ASI Certified Smelter.







ARTISAN ARCHITECTURAL 991 DOUBLE HUNG WINDOW

The Artisan Architectural 991 is a premium double hung window combining ease of use, high performance and a classic style into a bold 100mm frame. It incorporates a sash release system allowing easy cleaning from the inside – making it perfect for elevated applications.

Quality hardware and a sleak square cut frame make this the perfect choice, both now and for years to come. It is fully compatible and cohesive with our range of Artisan Architectural windows for a consistnet artchitectural aesthetic.

FEATURES AND BENEFITS

MAXIMUM PERFORMANCE

Serviceability Pressure

- Premium quality 100mm single and double glazed architectural framing systems
- Large capacity single and double glazing options
- Integrated insect and security screening options
- Exclusively designed components to improve the system's performance and function

WINDOW ENERGY RATINGS

- Provision for High, Low and Side Lights
- AGS 419/429 Flushline compatible for seamless integration

2200Pa

• Compatible with the full range of Artisan Architectural window suites



GLAZING CAPACITY	
Single Glazed	4-10mm
Double Glazed	10-18mm

WINEDOWN LINE	NOT NATINGS				
Window ID	Glazing	Uw	SHGC	Tvw	Air Inf
CAP-547-001	10.38Clr	6.4	0.52	0.58	0.12
CAP-547-002	10.38ComPlsClr	5.1	0.46	0.54	0.12
CAP-547-003	lOEnTech	5.2	0.47	0.54	0.12
CAP-547-007	6.38Clrlam	6.5	0.55	0.59	0.12
CAP-547-008	6EnTech	5.2	0.49	0.55	0.12
CAP-547-009	4Clr	6.6	0.61	0.61	0.12
CAP-548-001	4Clr-10-4Clr	4.6	0.54	0.55	0.12
CAP-548-002	4Clr-10Ar-4Clr	4.5	0.54	0.55	0.12
CAP-548-003	4Gy-10-4Cl r	4.6	0.40	0.34	0.12
CAP-548-004	4EnTech-10Ar-4C	3.9	0.45	0.51	0.12

ARTISAN ARCHITECTURAL 992 AWNING & CASEMENT WINDOW

Whether opening from the top or the side, the Artisan Architectural 992 Awning & Casement Window is configurable to meet your needs. Smooth operation, a clean 100mm or 150mm outer frame, and custom hardware options make this a premium package.

This modern window is fully compatible and visually cohesive with the other windows in our Artisan Architectural range, ensuring a clean look and a premium feel.

FEATURES AND BENEFITS

- Accepts double glazing up to 26mm alongside standard single glazing options
- Custom designed hardware options
- Awning configurations incorporate an integrated hook hinge at the head for strength
- Optional Caprice side latches to ensure security and performance on large sashes
- Integrated insect and security screening options for a modern, tidy aesthetic
- AGS 419, 426 & 629 Flushline compatible for seamless integration
- Compatible with the full range of Artisan Architectural window suites

MAXIMUM PERFORMANCE

Serviceability Pressure	3000Pa
Ultimate Pressure	4500Pa
Water Penetration	900Pa

FRAME DIMENSIONS

/ 150mm
į

MAXIMUM RECOMMENDED SIZE

Height	2700mm
Width	2700mm
Max Area	3.24m²*
Weight	106kg

GLAZING CAPACITY

Single Glazed	4-8mm
Thick Glazed	8-14mm
Double Glazed	12-26mm

^{*} Relies on the use of a twin chain winder

WINDOW ENERGY RATINGS

Window ID	Glazing	Uw	SHGC	Tvw	Air Inf
CAP-551-001	10.38Clrlam	6.7	0.46	0.47	0.08
CAP-551-002	loet	5.7	0.41	0.44	0.08
CAP-551-003	10.38ComPlsClr	5.7	0.41	0.44	0.08
CAP-551-007	6.38Clrlam	6.8	0.48	0.48	0.08
CAP-551-008	6Clr	6.8	0.51	0.49	0.08
CAP-551-009	6ET	5.8	0.44	0.45	0.08
CAP-551-010	5Clr	6.9	0.51	0.49	0.08
CAP-552-001	6.38Clr-12-6Clr	5.0	0.41	0.42	0.08
CAP-552-002	6.38Clr-12Ar-6CI	4.9	0.41	0.42	0.08
CAP-552-003	6Clr-12-6Clr	5.0	0.43	0.42	0.08
CAP-552-004	6ET-12Ar-6Clr	4.5	0.38	0.39	0.08
CAP-552-005	4Clr-10-4Clr	5.1	0.46	0.44	0.08







ARTISAN ARCHITECTURAL 994 TOP HUNG SLIDING DOOR

The Artisan Architectural 994 Top Hung Sliding Door is designed to succeed in both residential and commercial development projects. It is available as a one, two, three or four track door in recessed, corner, and cavity configurations.

The Artisan Architectural 994 Top Hung Sliding Door's top rolling hardware enhances its smooth operation. The system is compatible with Caprice and Caprio mortice and surface-mounted hardware.

FEATURES AND BENEFITS

- Suited to almost any commercial or architectural application
- Top rolling capability improves operating force
- Single, double, triple and quad track configurations available
- Fully compatible with Aquago linear grate solution
- Flat thresholds and track infills provide a flat sill option
- Infill thresholds and linear grate covers which allow timber or tile inserts
- Low profile non-water-rated sill can be used for internal applications
- Corner and cavity configurations are available
- Top rolling hardware is easily adjusted and concealed with pelmet beads
- Compatible with Caprio and Caprice mortice and surface-mounted hardware

MAXIMUM PERFORMANCE

Serviceability Pressure	1500Pa
Ultimate Pressure	3000Pa
Water Penetration	300Pa

FRAME DIMENSIONS

Depth	100mm/150mm
Height	44mm/50mm/80mm

MAXIMUM RECOMMENDED SIZE

Panel Height	3000mm
Panel Width	2500mm
Panel Weight	250kg

GLAZING CAPACITY

Single Glazed	4-10mm
Thick Glazed	10-15mm
Double Glazed	19-26mm

WINDOW ENERGY RATINGS

Window ID	Glazing	UW	SHGC	IVW	AIr Int
CAP-056-001	6Clr	6.3	0.63	0.66	0.37
CAP-056-002	6Gy	6.3	0.45	0.33	0.37
CAP-056-023	10.38CPClr	4.6	0.50	0.60	0.37
CAP-056-024	10.38CPGy	4.6	0.38	0.29	0.37
CAP-057-001	6Clr/12/6Clr	3.9	0.55	0.59	0.37
CAP-057-003	6SpGy/12/6Clr	3.9	0.18	0.06	0.37
CAP-057-009	6Clr/12Ar/6Clr	3.8	0.55	0.59	0.37
CAP-057-010	6EG/12Ar/6Clr	3.8	0.31	0.35	0.37



ARTISAN ARCHITECTURAL 995 FOLDING SERVERY WINDOW

The Artisan Architectural Folding Servery Window is a premium bi-fold option with a simple and smooth top-rolling action for easy access and simple operation. It's available in either single or double-glazed configurations with durable stainless steel hardware.

The sill-less design is perfect for use as a servery window, allowing clear views and convenient access. Open it fully to maximise airflow and access for entertaining or have just one panel open to let in a cool breeze — it's your choice!

FEATURES AND BENEFITS

- Single and double glazed options (up to 31mm)
- Top rolling system for smooth operation
- Sill-less design suits servery window
- Fully adjustable, including both horizontal and vertical
- Accepts double glazing providing excellent energy efficiency
- Complementary hardware from the Caprice range
- Euro spigot connectors save factory fabrication time
- Incorporates Stainless Steel hinges, rollers and flush-bolts
- Available in open in and open out configurations

MAXIMUM PERFORMANCE

Serviceability Pressure	2400Pa
Ultimate Pressure	5600Pa
Water Penetration	N/A

FRAME DIMENSIONS

Depth	101.6mm

MAXIMUM RECOMMENDED SIZE

Sash Height	2100mm
Sash Width	900mm
Sash Weight	80kg

GLAZING CAPACITY

Single Glazed	4-12mm
Thick Glazed	14-18mm
Double Glazed	19-31mm







ARTISAN ARCHITECTURAL 996 FOLDING DOOR

The Artisan Architectural Folding Door boasts smooth top rolling panels, enabling unobstructed access when open and ensures protection from the elements when closed. These doors are very adaptable making them an optimal choice when creating versatile living areas,

Highly configurable and with a wide array of hardware options, this folding door provides flexibility in design, including the option for sill and sill-less configurations.

FEATURES AND BENEFITS

- Top rolling hardware for ease of operation
- Water rated and non-water rated sills
- Compatible with the Aquago Linear Grate Sill
- Multiple rail and midrail heights available
- Euro and commercial corner cleat assembly methods
- Large range of open-in and open-out configurations

101.6mm

 Dedicated lock and cover stiles suit a large variety of hardware including Capral's Caprice and Caprio range



MAXIMUM PERFORMANCE

Serviceability Pressure	3000Pa
Jltimate Pressure	8000Pa
Water Penetration - Static	450Pa

FRAME DIMENSIONS

MAXIMUM RECOMMENDED SIZE		
Panel Height	3000mm	
Panel Width	1000mm	
Panel Weight	100kg	

GLAZING CAPACITY

Single Glazed	4-12mm
Thick Glazed	14-18mm
Double Glazed	19-31mm

WINDOW ENERGY RATINGS

Window ID Glazing	Uw	SHGC	Tvw	Air Inf
CAP-042-001 6Clr	6.0	0.56	0.57	0.33
CAP-042-002 6SpGy	6.0	0.25	0.06	0.33
CAP-042-003 6.38ClrLam	6.0	0.54	0.57	0.33
CAP-042-008 10.38CPClr	4.6	0.33	0.36	0.33
CAP-042-009 10.38CPNtl	4.6	0.33	0.36	0.33
CAP-042-010 11.52ClrLam	5.7	0.47	0.52	0.33
CAP-043-001 6Clr/12/6Clr - ALU	4.2	0.47	0.49	0.33
CAP-043-002 6Gy/12/6Clr - ALU	4.2	0.31	0.24	0.33
CAP-043-003 6EA/12/6Clr - ALU	3.7	0.41	0.46	0.33
CAP-043-004 6Clr/12Ar/6Clr - ALU	4.1	0.47	0.49	0.33
CAP-043-005 6Gy/12Ar/6Clr - ALU	4.1	0.30	0.24	0.33
CAP-043-006 6EA/12Ar/6Clr - ALU	3.5	0.41	0.46	0.33

ARTISAN ARCHITECTURAL 996 QUIK FOLDING DOOR

The Artisan Architectural Quik Folding Door has smooth top rolling panels and allows for convenient use of floor space - open wide for uninhibited access when entertaining or close for protection from the elements. An ideal choice when you are looking to create flexible living areas.

Artisan Architectural Folding Doors suit a wide range of hardware and are configurable with sill and sill-less options to suit your climate and lifestyle.

FEATURES AND BENEFITS

- Top rolling hardware for ease of operation
- Water rated and non-water rated sills
- Compatible with the Aquago Linear Grate Sill
- Quick fit stainless steel hardware
- Multiple rail and midrail heights available
- Euro and commercial corner cleat assembly methods
- Large range of open-in and open-out configurations
- Fast Fix Hinge screw on hardware for ease of install
- Dedicated lock and cover stiles suit a large variety of hardware including Capral's Caprice and Caprio range

MAXIMUM PERFORMANCE

Serviceability Pressure	3000Pa
Ultimate Pressure	5300Pa
Water Penetration - Static	450Pa

FRAME DIMENSIONS

Depth	101.6mm
-------	---------

MAXIMUM RECOMMENDED SIZE

Panel Height	2700mm*
Panel Width	900mm
Panel Weight	80kg

GLAZING CAPACITY

Single Glazed	4-12mm
Thick Glazed	14-18mm
Double Glazed	19-31mm

* With adjustable jamb hinge

WINDOW ENERGY RATINGS

Window ID	Glazing	Uw	SHGC	Tvw	Air Inf
CAP-562-001	6Clr/12/6Clr	4.1	0.49	0.52	0.13
CAP-562-002	6Clr/12Ar/6Clr	4	0.49	0.52	0.13
CAP-562-003	6Gy/12/6Clr	4.1	0.32	0.24	0.13
CAP-562-004	6EnTech/12Ar/6Clr	3.4	0.43	0.48	0.13
CAP-562-005	LightBridgeClrS0 6/12/6	3.3	0.4	0.51	0.13
CAP-562-006	LightBridgeGryS0 6/12/6	3.3	0.24	0.24	0.13
CAP-563-001	8Clr	5.9	0.53	0.56	0.12
CAP-563-002	638CPlsGy	4.6	0.34	0.25	0.08
CAP-563-003	638CPlsNtl	4.6	0.35	0.38	0.08
CAP-563-004	638CPlsClr	4.6	0.47	0.53	0.08
CAP-563-005	638ClrLam	5.9	0.53	0.57	0.12
CAP-563-006	6Clr	6	0.56	0.57	0.12







ARTISAN ARCHITECTURAL 997 HINGED DOOR

The Artisan Architectural 997 Hinged Door has a classic look and feel with all the modern trimmings. it integrates with the AGS 619 & 629 Flushline framing systems for consistent appearance across any space.

The Artisan Architectural Hinged Door's frame is double rebated to allow for the seamless integration of an Amplimesh Security Door or standard fly door.

The door can be double glazed to maximise thermal comfort and performance.

FEATURES AND BENEFITS

- Industry standard 46mm panel thickness
- Fully integratable with the AGS 619 & 629 Flushline framing systems
- Double rebated frame to seamlessly incorporate Amplimesh security door or standard fly door.
- Open-in single & french door configurations
- Fully compatible with the Caprio & Caprice hardware ranges
- Large range of rail heights and stile widths available
- Supports Euro cleat or commercial spigot assembly methods
- The AGS Commercial 619 or 629 framing systems allow for sidelight and highlight applications
- Water-rated and low profile non-water-rated sills are available
- Bushfire rated to BAL-40

MAXIMUM PERFORMANCE

Serviceability Pressure	4500Pa
Ultimate Pressure	10000Pa
Water Penetration - Static	300Pa

FRAME DIMENSIONS

MAXIMUM RECOMMENDED SIZE			
Panel Height	3000mm*		
Panel Width	1200mm*		
Panel Weight	100kg*		

GLAZING CAPACITY

Single Glazed	4-12mm
Thick Glazed	14-18mm
Double Glazed	19-31mm

ACOUSTICS (MAX)*

Acoustics	38 (-1; -3)

^{*} Based on Urban Plus 397 results

WINDOW ENERGY RATINGS

Glazing

Window ID

**********	0.02.11.6	0	01100		,
CAP-565-002	6.38CPGy	4.6	0.33	0.24	0.62
CAP-565-003	6.38CPNtl	4.6	0.34	0.37	0.62
CAP-565-004	6.38CPClr	4.6	0.45	0.52	0.62
CAP-565-005	6.38ClrLam	5.9	0.51	0.55	0.62
CAP-565-006	6Clr	5.9	0.53	0.55	0.62
CAP-565-007	6ET	4.6	0.45	0.51	0.62
CAP-564-002	6Clr/12Ar/6Clr	4.1	0.45	0.48	0.62
CAP-564-003	6Gy/12/6Clr	4.1	0.30	0.23	0.62
CAP-564-004	6ET/12Ar/6Clr	3.6	0.39	0.44	0.62
CAP-564-005	LB Clr 6/12/6	3.4	0.36	0.47	0.62
CAP-564-006	LB Gy 6/12/6	3.4	0.22	0.22	0.62

Uw SHGC Tvw Air Inf



ARTISAN ARCHITECTURAL 998 TILT & TURN WINDOW

The Artisan Architectural 998 Tilt & Turn is a multi-functional window and is compatible with the AGS Flushline range of commercial framing products. The tilt option opens the window inwards at the top, allowing it to be left open for ventilation whilst being safe from children climbing out and intruders entering. Once the key is inserted, a turn of the handle opens the window from the side, giving you the ability to direct airflow, clean windows safely from the inside and providing a quick escape in case of emergencies.

The Artisan Architectural Tilt & Turn Window is an ideal solution to common problems in residential and commercial applications such as multi-storey apartments and hotel complexes. The multi-point locking system also provides excellent structural and water performance making it suitable for use in high wind cyclonic areas.

FEATURES AND BENEFITS

- Single and double glazed options (up to 26mm)
- Standard and high performance configurations using sub frame system
- European designed components and hardware
- Multiple and adjustable locking points ensure structural integrity of the product is maintained even in high wind cyclonic areas
- Operable with a single handle with turn function restricted using a key override
- Inward opening allows for ease of cleaning
- An optional plant on screening adaptor
- Cyclonic debris impact resistance up to 15m/s

100mm

MAXIMUM PERFORMANCE

Serviceability Pressure	3000Pa
Ultimate Pressure	8000Pa
Water Penetration - Static	700Pa

FRAME DIMENSIONS

MAXIMUM RECOM	MENDED SIZE
Sash Height	2100mm
Sash Width	1300mm
Sash Weight	80kg

GLAZING CAPACITY

Single Glazed		4-12mm		
	Thick Glazed	14-18mm		
	Double Glazed	23-26mm		

ACOUSTICS (MAX)

Acoustics	38 (-1; -3)
71000001100	00(1, 0)

WINDOW ENERGY RATINGS

Window ID	Glazing	Uw	SHGC	Tvw	Air Inf
CAP-118-001	4Clr	6.7	0.43	0.39	0.12
CAP-118-002	6SpGy	6.7	0.21	0.04	0.12
CAP-118-003	6TS21Az	6.4	0.18	0.07	0.12
CAP-118-004	6.38CPNtl	5.9	0.28	0.26	0.12
CAP-119-001	5Clr/10Ar/5Clr	5.3	0.37	0.35	0.12
CAP-119-002	6ET/12/6Clr	5.0	0.32	0.32	0.12
CAP-119-003	6ET/12Ar/6Clr	4.9	0.32	0.32	0.12
CAP-119-004	10.76LamClr/12/4Clr	5.3	0.33	0.34	0.12
CAP-119-005	LB Clr5/12/5	4.8	0.31	0.34	0.12
CAP-119-006	LB Gy5/12/5	4.8	0.21	0.18	0.12







ARTISAN ARCHITECTURAL 999 AUTOMATED STRUT WINDOW

The Artisan Architectural 999 Automated Strut window is ideal in servery applications, allowing for large openings that conveniently stay out of the way when fully open at a 90 degree angle.

Operating hardware is concealed for a clean look and feel, and the window is available with or without a sill.

Integration to the Capral AGS 619 and 629 Flushline framing systems allows you flexibility in design while maintaining a uniform appearance.

FEATURES AND BENEFITS

- Opening and closing functionality is fully automated
- Integratable with the AGS Series 619 and 629 Flushline framing system
- Features a mitred sash with no hiding spots for spiders
- Available with a water-rated threshold or non-water-rated silless design
- Operating hardware is concealed within the custom pelmet

800Pa

Integrated self-latching mechanism

2400Pa Ultimate Pressure 597Pa Water Penetration FRAME DIMENSIONS Depth 150mm

MAXIMUM PERFORMANCE

Serviceability Pressure

	MAXIMUM RECOMME	NDED SIZE
	Sash Height	1700mm
	Sash Width	2100mm
	Sash Weight	65kg

GLAZING CAPACITY	
Single Glazed	4-12mm
Thick Glazed	14-18mm
Double Glazed	19-31mm

AP-555-008 6Clr 6.5 0.44 0.51 0.24 AP-555-001 1038ClrLam 6.4 0.46 0.48 0.24 AP-555-002 10ET 5.4 0.41 0.44 0.24 AP-555-003 1038ComPlsClr 5.4 0.40 0.44 0.24 AP-555-004 638ComPlsGy 5.5 0.32 0.22 0.24 AP-555-006 638ComPlsClr 5.6 0.43 0.46 0.24 AP-556-001 638Clr-12-6Clr 4.8 0.41 0.43 0.14 AP-556-002 638Clr-12Ar-6Cl 4.7 0.41 0.43 0.08 AP-556-003 6Clr-12-6Clr 4.8 0.43 0.43 0.09 AP-556-004 6ET-12Ar-6Clr 4.3 0.38 0.43 0.08						
AP-555-002 10ET 5.4 0.41 0.44 0.24 AP-555-003 1038ComPlsClr 5.4 0.40 0.44 0.24 AP-555-004 638ComPlsGy 5.5 0.32 0.22 0.24 AP-555-006 638ComPlsClr 5.6 0.43 0.46 0.24 AP-556-001 638Clr-12-6Clr 4.8 0.41 0.43 0.14 AP-556-002 638Clr-12Ar-6Cl 4.7 0.41 0.43 0.08 AP-556-003 6Clr-12-6Clr 4.8 0.43 0.43 0.09	AP-555-008	6Clr	6.5	0.44	0.51	0.24
AP-555-003 1038ComPlsClr 5.4 0.40 0.44 0.24 AP-555-004 638ComPlsGy 5.5 0.32 0.22 0.24 AP-555-006 638ComPlsClr 5.6 0.43 0.46 0.24 AP-556-001 638Clr-12-6Clr 4.8 0.41 0.43 0.14 AP-556-002 638Clr-12Ar-6Cl 4.7 0.41 0.43 0.08 AP-556-003 6Clr-12-6Clr 4.8 0.43 0.43 0.09	AP-555-001	1038ClrLam	6.4	0.46	0.48	0.24
AP-555-004 638ComPlsGy 5.5 0.32 0.22 0.24 AP-555-006 638ComPlsClr 5.6 0.43 0.46 0.24 AP-556-001 638Clr-12-6Clr 4.8 0.41 0.43 0.14 AP-556-002 638Clr-12Ar-6Cl 4.7 0.41 0.43 0.08 AP-556-003 6Clr-12-6Clr 4.8 0.43 0.49	AP-555-002	10ET	5.4	0.41	0.44	0.24
AP-555-006 638ComPlsClr 5.6 0.43 0.46 0.24 AP-556-001 638Clr-12-6Clr 4.8 0.41 0.43 0.14 AP-556-002 638Clr-12Ar-6Cl 4.7 0.41 0.43 0.08 AP-556-003 6Clr-12-6Clr 4.8 0.43 0.43 0.09	AP-555-003	1038ComPlsClr	5.4	0.40	0.44	0.24
AP-556-001 638Clr-12-6Clr 4.8 0.41 0.43 0.14 AP-556-002 638Clr-12Ar-6Cl 4.7 0.41 0.43 0.08 AP-556-003 6Clr-12-6Clr 4.8 0.43 0.43 0.09	AP-555-004	638ComPlsGy	5.5	0.32	0.22	0.24
AP-556-002 638Clr-12Ar-6Cl 4.7 0.41 0.43 0.08 AP-556-003 6Clr-12-6Clr 4.8 0.43 0.43 0.09	AP-555-006	638ComPlsClr	5.6	0.43	0.46	0.24
AP-556-003 6Clr-12-6Clr 4.8 0.43 0.43 0.09	AP-556-001	638Clr-12-6Clr	4.8	0.41	0.43	0.14
	AP-556-002	638Clr-12Ar-6Cl	4.7	0.41	0.43	0.08
AP-556-004 6ET-12Ar-6Clr 4.3 0.38 0.43 0.08	AP-556-003	6Clr-12-6Clr	4.8	0.43	0.43	0.09
	AP-556-004	6ET-12Ar-6Clr	4.3	0.38	0.43	0.08

WINDOW ENERGY RATINGS

CAP-556-005 4Clr-10-4Clr

CAP-556-006 4Clr-10Ar-4Clr

Glazing

Window ID

View full list of Residential and Commercial WERS rating at capral.com.au

Uw SHGC Tvw Air Inf

4.9 0.47 0.45 0.08

4.8 0.47 0.45 0.08



CAPRAL HARDWARE Designed to complement the Capral Futureline, Urban Plus, Urban and Artisan range of windows and doors, Caprio and Caprice by Capral are a contemporary range of hardware for windows and doors. The ranges are ideal for residential applications and deliver a stylish, consistent and cost-effective solution for windows and doors throughout a home.



CAPRIO HARDWARE RANGE

Caprio by Capral is a stylish, sleek range of contemporary hardware for windows and doors. This unique range is available in flat black, satin nickle and stainless-steel delivering a timeless and premium finish suitable for a variety of applications and environments. The Caprio range ensures exceptional durability without compromising on style.

Hinged Door Lever Set



D'pull Handle



Bi-Fold Actuator



Flush Pull



Magnetic Lever Furniture



Mortice Lock





CAPRICE HARDWARE RANGE

Designed to complement the Capral Futureline, Urban, Urban Plus and Artisan range of windows and doors, Caprice by Capral is a contemporary range of window and door hardware. Available in durable powder coat finishes, the range is ideal for residential applications delivering a consistent, stylish, cost-effective solution for all windows and doors throughout a home.

Single Point Sliding Door Lock



Flush Mortice Sliding Door Lock



Twin Point Sliding Door Lock



D'Pull Handle



Flush Pull Handle



Hinged Door Handles



Bi-Fold Hardware



Single Chain Winder



Sliding Window Mortice Lock



Dual Winder




Surface Mounted Sliding Window Lock



High Performance Dual Chain Winder









The Urban series is a standard range of energy efficient window and doors designed to inspire your living space.

Uncompromising in design, our Urban products are engineered with superior mechanisms and components for effortless, trouble-free operation.

All Urban windows and doors are designed to contribute to increased energy performance in your home.



The Urban Plus Designer Residential range is a collection of high-performance, energy efficient window and door systems designed to inspire your living space.

Uncompromising in design, the Urban Plus Designer Residential range is engineered with superior mechanisms and components for effortless, trouble free operation.







The AGS Commercial range is designed to achieve the ultimate combination of architectural style and performance. Each door and window is engineered to withstand Australia's harsh conditions, even the extremes. In fact, they're recognised as some of the best performing windows and doors on the market. All tested for heavy use commercial and residential applications.



The Futureline thermally broken range of windows and doors is designed to deliver improved thermal performance for commercial and residential projects.

Designed to meet the demands of ever-increasing energy efficiency requirements, the Futureline range is versatile and stylish, delivering robust structural performance whilst achieving excellent energy efficiency outcomes.

