

DECORLUX® BUILD YOUR SPECIFICATION

Complete the table and use the details in your project specification.

PRODUCT	DECORLUX	SUPPLIER	DECOR SYSTEMS - PH: 1800 835 035
PROFILE	(CHOOSE A PROFILE FROM THE LIST ABOVE)		
FINISH	(CHOOSE A FINISH FROM THE LIST ABOVE)		
FINISH VARIATION	(E.G. SMARTLOOK COLOUR)		
SUBSTRATE	6MM FIBRE CEMENT	9MM FIBRE CEMENT	
FIXING METHOD	(CHOOSE A FIXING METHOD FROM THE LIST ABOVE)		
DECORINSUL	YES	NO	
FIRE CERTIFICATION	DECORLUX® COMES WITH A GROUP 1 FIRE RATING AND IS DEEMED NON-COMBUSTIBLE.		
NOTES	(ANY EXTRA INFORMATION YOU WOULD LIKE TO ADD?)		
<p>This product requires an air gap and DecorInsul behind the panels for the best acoustic performance. Consult the acoustic test results, and opinion of project acoustic engineer for more details. If not available due to site constraints or budget, a 50mm gap with DecorInsul works in most cases.</p> <p>Close collaboration between Decor Systems, the project architect and the client has taken place to develop this specification. DecorLux® cannot be substituted unless agreed by Architect and Acoustic Engineer.</p> <p>Panels should be allowed to acclimatise on site for at least five days before installation. Decor Systems certificate # (Contact your Decor Systems project consultant for your individual project number) to be supplied upon completion.</p> <p>Panel installation to be as per manufacturer's instructions and AS/NZS 2785. - Installation to be done by an approved ceiling and partition contractor.</p> <p>Product guarantee to be 99 years as per Decor Systems guarantee. Please contact Decor Systems for your project specific completion number.</p>			