



Climate Ready
Fabrics

A TEXTURED SCREEN FABRIC

ReView

Metallised

- 100% virgin polyester
- UL Greenguard Gold Certified
- PVC Free



Roller Shades



Panel Glide Shades



Vertical Shades

Suitable for internal installation only.

Technical Data

Openness Factor:	3%
Fabric Width:	280 cm
Thickness:	0.44 mm
Weight:	250 g/m ²
Composition:	100% virgin polyester
Fire Retardancy:	Compliant to AS1530.2 and AS1530.3. Certificates available on request.

Fenestration Properties

Design	OF (%)	As (%)	Rs (%)	Ts (%)	Tuv (%)	Tv (%)
White 001	3	31	62	7	5	7
Beige 002	3	32	62	6	4	6
Grey 003	3	33	62	5	4	5
Dark Grey 004	3	34	62	4	4	4
Black 005	3	32	62	6	4	4

Openness Factor / OF
Ultraviolet Transmittance / Tuv
Light Transmittance / Tv
Solar Transmittance / Ts
Solar Reflectance / Rs
Solar Absorption / As

Data is current at time of printing. Please check website for most current information.

Certification:



UL GREENGUARD®
Gold Certified



OEKO-TEX
Standard 100

Care Instructions:






Handle fabric with care and wear clean gloves. Lightly dust regularly with clean feather duster. A hand-held vacuum with low suction may also be used. When vacuuming, avoid pulling or stretching the fabric. On metallised side, spot clean by gently blotting with a slightly damp cloth. Leave the blind down until completely dry.

Warranty:

5 year warranty as complete roller shade systems for internal use. For more information regarding warranties and extended warranties, please contact Climate Ready Fabrics.

Sustainability:

● PVC-free

Colour Range:**White 001****Beige 002****Grey 003****Dark Grey 004****Black 005**

Colours are to be used for reference purposes only.
For an accurate colour sample, please contact Climate Ready Fabrics for a fabric swatch sample.