

How it works

The Ozzi Kleen Sewage Treatment System treats up to 2,000 litres of wastewater everyday. Operating on a cyclic, fully aerobic basis, the wastewater treatment is highly effective and efficient, processing it into clear odourless irrigation water in a matter of hours.

The Ozzi Kleen Sewage Treatment System is the only one of its kind using activated sludge through cyclic aeration. Most modern town and industrial sewage treatment plants in Australia, and around the world, use this technology. The Ozzi Kleen Sewage Treatment System is the only domestic system that can offer you this.

Treatment Process

The activated sludge process starts treating all your household sewage, (i.e. toilets, bathrooms, kitchen, laundry etc), as soon as it enters the aeration compartment. A complete digestion of organic waste takes place in the oxygen enriched environment in the aeration tank using naturally occurring bacteria to produce treated water of a high quality. Treated water is decanted and stored within the tank in the effluent holding compartment available for reuse on gardens.

ADVANCED Model Available

The Advanced Model has an added function known as 'Nutrient Removal'. The quality of the treated water from the 'Advanced System' is to a higher standard, which makes it suitable for reuse in environmentally restricted applications. Ideal for: Highly Sensitive Catchment Areas, Canal Blocks, Small Size Blocks and Reducing Buffer Zones (check with local authorities).



Tank Diameter	1.95m
Tank Wall Height	1.90m
Tank Overall Height	2.70m
Tank Weight	400kg (approx)
Tank Thickness	up to 20mm



50+ Distributors Australia Wide

Your Local Ozzi Kleen Distributor



Suncoast Waste Water Management
Ph: +61 7 5459 4900 Fax: +61 7 5456 4677
59 Industrial Avenue, Kunda Park QLD 4556
Email: info@ozzikleen.com

Call Us NOW on
1800 450 767
or visit our website for more information
www.ozzikleen.com



OK
For

OZZI KLEEN®

Sewage Treatment System

Environmentally friendly wastewater recycling for your home



Typical Installation

www.ozzikleen.com

Ozzi Kleen Advantages

The Ozzi Kleen Sewage Treatment System allows you to keep using all your favourite non oil based household cleaners, disinfectants and bleaches (in normal use), processing them into harmless compounds. This enables you to go about your normal day-to-day activities with peace of mind.

The Ozzi Kleen Sewage Treatment Systems are built to last. The heavy-duty polyethylene tank is up to 20mm thick and is, weight for weight, 100 times stronger than concrete. As the Ozzi Kleen tank is roto-moulded and completely seamless, there is no risk of seepage, leaking or root intrusion. The tank is backed by a 15-year manufacturer's warranty.

“Ozzi Kleen is an easy care, clean and effective system, with a good watering system for our garden”

Proud Ozzi Kleen owners Mr & Mrs Balcombe, Tamworth NSW

Benefits to You

- Single lightweight tank
- Easy to install
- No septic odours – 100% aerobic non-septic system
- Lower running cost due to unique Ozzi Kleen cyclic aeration process
- Use your favourite bleaches and disinfectants
- Copes with most antibiotics
- No septic tank pump outs required
- Copes with shock loads
- Recycles nutrient rich water to reuse on gardens, lawns and trees
- The Only Non-Septic Fully Aerobic Cyclic Domestic Sewage Treatment System



Light weight tank. Easy to Install!

Trusted Name in Wastewater

Ozzi Kleen has been a trusted name in sewage treatment since the 1990s. As an Australian owned and operated manufacturer, Suncoast Waste Water Management developed and released the range of domestic Ozzi Kleen products into the market after decades of experience in commercial applications.

By installing an Ozzi Kleen Sewage Treatment System you can join the many thousands of households already enjoying the benefits of an endless supply of nutrient rich water to safely reuse on your property for watering gardens, lawns and trees.

Tank Diameter	1.95m
Tank Wall Height	1.90m
Tank Overall Height	2.70m
Tank Weight	400kg (approx)
Tank Thickness	up to 20mm

*Suitable for surface or sub-surface irrigation (check with local authorities)

*surface irrigation



*sub-surface irrigation

Artist Impression

