



Recommended Installation Height

From Floor to Top of Hand Dryer
= 1200 - 1350 mm
From Floor to Bottom of Hand Dryer
= 900 - 1050 mm

Disabled People's Washroom
From Floor to Bottom of Hand Dryer
= 1000 mm

Electrical Installation Options

Simple electrical connection by plug and lead as supplied, or can be direct wired by electrician.



Disabled compliant when installed in accordance with AS1428.

ECO JET DRYER JDECO-X [X = S (Silver), W (White), C (Chrome)]

TECHNICAL SPECIFICATIONS

Electrical

Input voltage: 230-240V AC, Single Phase 50Hz
Rated Power: 900W, 4.4 Amp
Motor Type: Vacuum, Brush Resistance Motor
Energy Consumption per use: 0.0032 kWh
Standby Power: 1 W

Construction

Powder coated Die Cast Aluminum Casing
Colour Finishes: White, Silver, Polished Chrome
Water Protection: IP22

Filtration

N/A

Operation

Infra Red Touch Free Operation
Hand Drying Time: Approx. 10 - 20 Seconds
Airflow: 320+ kph
Operating Noise: 70 dba

Weight

Unit Weight: 4.5kg

Warranty

3 year Parts, 1 Year Labour

Product Certification

Approved to IEC/EN60335-1 and IEC/EN60335-2-23

Compliant to EMC directive according to EN55014-1, EN55014-2, EN61000-3-2, EN61000-3-3