



www.altro.com

Designed for possibilities.
Made for people.

Altro Wood Safety collection





Altro Wood Safety



Washed Bamboo | WSA2020
WR463 / A1M392 / LRV 42

Design as shown



Farmhouse Oak | WSA2004
WR338 / A1M27 / LRV 38

1000 (550/450) x 100mm



Ranch Oak | WSA2021
WR335 / A1M335 / LRV 51

1000 x 125mm



Bleached Oak | WSA2001
WR335 / A1M335 / LRV 52

500 x 100mm



Light Beech | WSA2017
WR462 / A1M462 / LRV 43

333 x 62mm



Oak Traditions | WSA2013
WR353 / A1M225 / LRV 25

500 x 100mm



Rustic Oak | WSA2006
WR340 / A1M340 / LRV 37

500 x 100mm



Spring Maple | WSA2018
WR352 / A1M352 / LRV 27

1000 (550/450) x 100mm

Codes: WR = weld rod, A1M = mastic, LRV = light reflectance value
Light Reflectance Values measured in accordance with BS8493:2008.
Exact material match with samples cannot be guaranteed.



500 x 100mm

Washed Oak | WSA2015
WR347 / A1M347 / LRV 38



1000 (550/450) x 100mm

Vintage Cherry | WSA2002
WR336 / A1M239 / LRV 22



1000 x 125mm

Worn Oak | WSA2023
WR322 / A1M239 / LRV 19



500 x 100mm

Manor Oak | WSA2016
WR348 / A1M348 / LRV 7



1000 (550/450) x 100mm

Autumn Maple | WSA2005
WR339 / A1M339 / LRV 24



1000 x 125mm

Mountain Oak | WSA2022
WR339 / A1M339 / LRV 22



1000 (550/450) x 100mm

Urban Cherry | WSA2003
WR337 / A1M337 / LRV 17



1000 (550/450) x 100mm

Walnut Noir | WSA2011
WR345 / A1M62 / LRV 6



1000 x 166mm

Noble Oak | WSA2024
WR467 / A1M467 / LRV 17



Design as shown

Deep Bamboo | WSA2019
WR342 / A1M224 / LRV 21



1000 (550/450) x 100mm

Antique Walnut | WSA2007
WR341 / A1M160 / LRV 15



1000 x 166mm

Stately Oak | WSA2025
WR468 / A1M62 / LRV 10

Please note: The measurements stated next to each sample is the size of the plank(s) within the 2m x 20m sheet.
All information is correct at the time of print and is subject to change without prior notice.

Altro Wood Safety Comfort



1000 x 125mm

Reclaimed Oak | WSASC2821
WR335 / A1M335 / LRV 51



500 x 100mm

Soft Oak | WSASC2804
WR338 / A1M27 / LRV 38



Design as shown

Light Bamboo | WSASC2820
WR463 / A1M392 / LRV 42



500 x 100mm

Field Oak | WSASC2806
WR340 / A1M340 / LRV 37



1000 (550/450) x 100mm

Warm Maple | WSASC2805
WR339 / A1M339 / LRV 24



1000 (550/450) x 100mm

Deep Cherry | WSASC2803
WR337 / A1M337 / LRV 17



1000 x 125mm

Veteran Oak | WSASC2822
WR339 / A1M339 / LRV 22



1000 (550/450) x 100mm

Classic Walnut | WSASC2807
WR341 / A1M160 / LRV 15



500x100mm

Aged Oak | WSASC2815
WR347 / A1M347 / LRV 38



1000 (550/450) x 100mm

Antique Cherry | WSASC2802
WR336 / A1M239 / LRV 22



1000 x 125mm

Royal Oak | WSASC2823
WR322 / A1M239 / LRV 19



1000 x 166mm

Regent Oak | WSASC2825
WR468 / A1M62 / LRV 10



Altro Wood™ Safety

Flooring type	Slip resistance	Thickness	Wear layer	Weight	Roll dimensions	Fire performance	Sound Insulation
EN 13845	PTV EN 13845 EN 13893 DIN 51130	EN ISO 24346	EN ISO 24340	EN ISO 23997	EN ISO 24341	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	EN ISO 10140
Safety flooring	≥ 36 ESf DS R10	2mm	0.7mm	2.66kg/m ²	2m x 20m = 40m ²	Bfl s1	Approx 4dB

CE 13 | Debolon Dessauer Bodenbeläge GmbH & Co. KG, Ebertallee 209, 06846 Dessau-Roßlau |
 DIN EN 13845 | DoP-No. Altro Wood Safety-RN-A025 | Reaction to fire: Bfl s1 | Slip resistance: DS | Formaldehyde: E1 |
 Electrical behaviour: < 2 kV | DIN EN 14041:2008 | 1658 | Resilient floor covering to be used within a building

Altro Wood™ Safety Comfort

Flooring type	Slip resistance	Thickness	Wear layer	Weight	Roll dimensions	Fire performance	Sound Insulation
EN 651	PTV EN 651 EN 13893 DIN 51130	EN ISO 24346	EN ISO 24340	EN ISO 23997	EN ISO 24341	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	EN ISO 10140
Safety flooring	≥ 36 ESf DS R10	2.85mm	0.7mm	2.6kg/m ²	2m x 20m = 40m ²	Cfl s1	Approx 14dB

CE 17 | Debolon Dessauer Bodenbeläge GmbH & Co. KG, Ebertallee 209, 06846 Dessau-Roßlau |
 DIN EN 651 | Reaction to fire: Cfl s1 | Slip resistance: DS | Formaldehyde: E1 | Electrical behaviour: < 2 kV |
 DIN EN 14041:2008 | 1658 | Resilient floor covering to be used within a building

Sustainability



Indication of the level of emissions of volatile substances in the ambient air that are posing a toxic hazard on being inhaled, rated on a scale from A+ (very low emissions) to C (high emissions).

†A+ BRE generic green guide rating for resilient flooring, full details available at www.thegreenguide.org.uk

i Installation and Maintenance

Install according to installation instructions and codes of practice. Refer to cleaning card. Failure to install and maintain flooring according to installation instructions can affect performance and slip resistance. Protect from other trades. Oil residue, certain cleaning agents, asphalt and anti-oxidants in some rubber can cause traffic stain. Caution, Ketone / aromatic solvents. For further technical information please visit www.altro.com

Altro, Designed for possibilities. Made for people. Altro Wood Safety, Altro Wood Safety Comfort and Altro EasyClean technology are trademarks of Altro Limited.



Altro Limited a company certified by SGS to ISO 9001 and ISO 14001.

+44 (0) 1462 707 700

www.altro.com

enquiries@altro.com

+61 3 9764 5666

www.asf.com.au

info@asf.com.au