

SureSteel[®]

Directional Tactile Ground Surface Indicators.

PRODUCT DESCRIPTION:

A one piece directional tactile ground surface indicator manufactured from 316 Marine grade stainless steel to provide long lasting stable performance. Designed to provide way finding directional guidance for the vision impaired. As part of The Disability Discrimination Act (DDA) compliance, it is mandatory to provide Tactile Guidance (TGSI's) to stairs, ramps and many other varying conditions.

DIMENSIONS:

Designed to conform with the Australian Standards. SureSteel[®] directional Tactiles:

- have a major diameter of 35mm, a minor diameter of 25mm
- have a length of 290mm (Nominal)
- have a protrusion height of 5mm, the maximum to ensure longevity and optimum anti-slip.
- are available with and without a fixing spigot, diameter of 6mm x 18mm long, to ensure mechanical retention to all substrates including concrete, timber, bitumen and most other surfaces. Manufactured from one piece to ensure overall strength and durability.

PRODUCT RANGE:

SureSteel[®] directional Tactile ribs are available in 3 basic designs: Square rib, hair line rib and hair line rib with stepped side face.

FEATURES:

- R11 anti-slip rated in Accordance with the Australian Standards AS4586.
- Comes with an optional 18mm fixing Spigot which provides maximum fixing strength in all substrates. The SureSteel[®] fixing spigot is the longest in the industry.
- Manufactured from 316 Marine grade stainless steel to ensure long lasting maintenance free performance.
- Resistant to heavy traffic abuse and maintenance machinery.
- SureSteel[®] offers specifiers the option of retaining the aesthetics of the underlying substrate without compromising tactile performance.
- Highly polished, milled finish which is bright and attractive.

LUMINANCE CONTRAST:

In accordance with the Australian Standards a minimum luminance contrast of 45% must be provided between a monochromatic directional tactile indicator and the surrounding substrate. SureSteel[®] directional Tactile Indicators are available in 3 styles which allow specifiers to select the most appropriate luminance contrast for any given application and aesthetic requirement. Refer to the SureSteel[®] luminance chart for selection details.

COMPLIES WITH:

- AS/NZS 1428:4.2002 Design for access and mobility
- AS/NZS 4586:1999 Slip resistance classification for new pedestrian surface materials



Working hard to keep
the world on its feet

