





TRADITIONAL



To view colour swatches for each state refer to www.monier.com.au

Traditional in strength but modern in appearance, this classic profile creates a smooth surface and subtle wave that gives a flowing, undulating texture to the roof.



TILES USAGE WITH WASTAGE (+/-2%)
Approx. 11.0 tiles per sqm.

TILE COVERAGE (±2%)
Approx. 9.90 tiles per sqm.

DIMENSIONS (±2%)
Length 420mm (415mm in NSW)
Width 327mm

MASS (±2%)
Per tile 4.90kg
Per m² 48.5kg

HEAD LAP ADJUSTMENT (MM)
80 – 110

FEATURE
Low wave

COLOUR APPLICATION
Colour On

RECOMMENDED BONDING
Straight bond

ROOF PITCH
Minimum Pitch with Sarking: 15°
Minimum Pitch without Sarking: 20°



Please consult the Design Guide at Monier.com.au for installation requirements applicable to your project.

Please refer to AS2049 for acceptable tolerance to these measurements stated above.



CONCRETE ACCESSORIES

ACCESSORY	LENGTH (MM)	WIDTH (MM)	HEIGHT (MM)	ANGLE (DEGREE)	WEIGHT (KG)
Parbarge 	420	248	126	84	4.9
Starter 	420	250	80	120	2.8
3-Way Apex (butt & overlapping) 	391.7	413.3	135	135	3.8
Ridge 	420	250	80	120	3.4
Ridge Saddle 	205	250	175	120	3.3
Gable Finial — Scroll 	245	240	280	120	5.1
Apex Finial — Scroll 	385	420	320	120	6
Spoon- Starter 	410	395	125	120	6