

Selection Chart Whelan Dynamicboil SL Series

To select the correct size unit for your needs simply determine the maximum number of cups of boiling water are required at any one time, then choose the corresponding model from the chart below.

MODEL NO./LITRES	No. OF CUPS SERVED	CUP/Hr RECOVERY	TOTAL KW	PHASES/VOLTAGE	HEIGHT mm	WIDTH mm	DEPTH mm	OVERFLOW
SL.2.5	13	70	1.58	1/240	430	460	185	3/4" BSP
SL.5	25	70	1.58	1/240	500	460	185	3/4" BSP
SL.7.5	38	70	1.58	1/240	550	460	185	3/4" BSP
SL10	50	100	2.25	1/240	500	600	250	3/4" BSP
SL.15	75	100	2.25	1/240	550	600	250	3/4" BSP
		210	4.75	2/240				
SL.20	100	100	2.25	1/240	550	600	250	3/4" BSP
		210	4.75	2/240				
SL.25	125	100	2.25	1/240	650	600	250	3/4" BSP
		210	4.75	2/240				
SL.30	150	100	2.25	1/240	700	600	250	3/4" BSP
		230	4.8	2/240				
		340	7.2	3/240				
SL.50	250	100	2.35	1/240	900	600	250	3/4" BSP
		230	4.8	2/240				
		340	7.2	3/240				
SL.60	300	100	2.35	1/240	1000	600	250	3/4" BSP
		230	4.8	2/240				
		340	7.2	3/240				
BW 90	450	100	2.50	1/240	950	600	510	3/4" BSP
		230	4.8	2/240				
		340	7.2	3/240				
BW 136	680	230	4.8	2/240	950	740	635	3/4" BSP
		340	7.2	3/240				
BW 180	900	230	4.8	2/240	950	800	700	3/4" BSP
		340	7.2	3/240				
BW 225	1125	340	7.2	3/240	950	900	800	3/4" BSP
BW 450	2250	340	7.2	3/240	1200	1020	915	1 1/2" BSP

Specifications subject to change without notice. 1 litre equals 5 cups approximately

Notes