

EXCELLENT HEAT PROTECTION WITH 100% LIGHT AND UV RAYS BLOCKED

SCREEN NATURE

Blackout

- 100% of light and UV rays blocked
- PVC free
- · Excellent dimensional stability
- Durable



Suitable for internal installation using:	0						
	Roller Shades	Panel Glide Shades	Vertical Shades	Internal installation only.			
Openness Factor:	0%						
Fabric Width:	240 cm						
Thickness:	0.45 mm						
Weight:	425 g/m ²						
Composition:	PVC-free treated flocked glass fibre fabric						
Fire Retardancy:	Compliant	to AS1530.2	and AS1530.3.				

Fenestration Properties:

	ó	KIJ ^A	ζ ^λ	6 ₇	19	₽ _S	Þ.s	2000 2000 2000 2000 2000 2000 2000 200	is and a
	0	~	~	4	~	4	4	6.0	00
WHITE	0%	0%	0%	83%	0%	70%	30%	0.26	0.12
OYSTER	0%	0%	0%	83%	0%	70%	30%	0.26	0.12
LINEN	0%	0%	0%	84%	0%	70%	30%	0.26	0.12
SAND	0%	0%	0%	84%	0%	70%	30%	0.26	0.12
SILVER GREY	0%	0%	0%	83%	0%	70%	30%	0.26	0.12
SABLE	0%	0%	0%	82%	0%	70%	30%	0.26	0.12
BRONZE	0%	0%	0%	81%	0%	70%	30%	0.26	0.12
BLACK	0%	0%	0%	86%	0%	70%	30%	0.26	0.12

Ultraviolet Transmittance / Tuv
Light Transmittance / Tv
Light Reflectance / Rv
Solar Transmittance / Ts
Solar Reflectance / Rs
Solar Absorption / As
G Value / G tot

Openess Factor / OF

Certificates available on request.

G tot: Total solar factor, ratio of the energy transmitted through a window and solar protection device. Classification and reference glazing according to standard EN 14501

Data is current at time of printing. Please check website for most current information.

Antibacterial	ASTME E 2180 - More than 99% of bacteria destroyed)					
Light-fastness:	7/8 - ISO 105 B02					
Care Instructions:	Handle fabric with care and wear clean gloves. Lightly dust regularly with clean feather duster. A hand-held vacuum with low suction may also be used. When vacuuming, avoid pulling or stretching the fabric. On metallised side, spot clean by gently blotting with a slightly damp cloth. Leave the blind down until completely dry.					
Warranty:	5 year warranty as complete roller shade systems for internal use. For more information regarding warranties and extended warranties, please contact Climate Ready Fabrics.					
Sustainability:	 100% recyclable PVC-free 					

Colour Range:



Colours are to be used for reference purposes only. For an accurate colour sample, please contact Climate Ready Fabrics for a fabric swatch sample.

Specification information and other data are based on information available at the time of publication of this document and are subject to production tolerances and/or change without prior notice.



[©] Copyright January 2020 Climate Ready® Fabrics