



Range Overview

700XP & 900XP

Index

700XP

Gas Boiling Tops	6
Gas Ranges on Oven (4 burners)	6
Gas Ranges on Oven (6 Burners)	6
Gas Solid Tops	7
Gas Boiling Tops	7
Electric Boiling Tops with Round Plates	7
Electric Boiling Tops with Square Plates	8
Electric Ranges on Oven	8
Electric Solid Tops	8
Infrared Cooking Tops	9
Induction Cooking Tops	9
Induction Cooking Tops - HP	9
Gas Fryers with "V" shape Well	10
Gas Tube Fryers	10
Fryer Tops with "V" shape Well	10
Electric Fryer Tops with Tilting Heating Elements	11
Electric Fryers with "V" shape Well	11
Electric Fryers with Tilting Heating Elements	11
Electric Chip Scuttle Top	12
Pasta Cookers	12
Gas Fry Tops (half module)	12
Gas Fry Tops (full module)	13
Electric Fry Tops (half module)	13
Electric Fry Tops (full module)	14
Electric Fry Tops (full module)	14
Gas Grill Tops - HP	15
Electric Grill Tops - HP	15
Gas Grill Tops	15
Grills	16
Electric Grill Tops	16
Multifunctional Cookers	16
Electric Bain-Marie Tops	17
Tilting Braising Pans	17
Boiling Pans	18
Refrigerated Bases	18
Freezer Base	19
Ambient Worktops	19
Top with Water Column	19
Sink Unit	20
Open Bases	20

900 XP

Gas Boiling Tops	21
Gas Boiling Tops - HP	21
Gas Boiling Tops - HP	21
Gas Ranges on Convection Oven (4 burners)	22
Gas Ranges on Static Oven (4 Burners)	22
Gas Ranges on Static Oven (6 or 8 Burners)	22
Electric Boiling Tops with Square Plates	23
Electric Ranges with Square Plates on Oven	23
Gas Solid Tops	23
Gas Solid Tops and Burners	24
Hob Cooking Tops	24
Infrared Cooking Tops	24
Induction Cooking Tops	25
Gas Fryers with "V" shape Well	25
Gas Fryers with Electronic Control	25
Gas Fryer with Automatic Cooking Mode	26
Gas Tube Fryers	26
Electric Fryers with "V" shape Well	26
Electric Fryers with Tilting Heating Elements	27
Electric Fryers with Electronic Control	27
Electric Fryer with Automatic Cooking Mode	28
Electric Chip Scuttle Top	28
Pasta Cookers	29
Electric Rethermalizer	29
Gas Automatic Pasta Cookers	29
Electric Automatic Pasta Cookers	30
Steam Automatic Pasta Cookers	30
Gas Fry Tops (half module)	30
Gas Fry Tops (full module)	31
NitroChrome ³ Gas Fry Tops - HP	31
Electric Fry Tops (half module)	32
Electric Fry Tops (full module)	32
Electric Fry Tops (full module)	33
NitroChrome ³ Electric Fry Tops - HP	33
Gas Grill Tops - HP (Powergrill)	34
Electric Grill Tops - HP (Powergrill)	34
Grills Freestanding	34
Multifunctional Cookers	35
Bain-Marie Tops	35
Gas Tilting Braising Pans (80lt and 100 lt)	35
Electric Tilting Braising Pans (80lt and 100 lt)	36
Gas Boiling Pans (Cylindrical)	36
Electric Boiling Pans (Cylindrical)	37
Boiling Pans (Rectangular)	37
Ref-freezer Base	37
Refrigerated Base	38
Ambient Worktops	38
Top with Water Column	38
Sink Unit	38
Bases	39

Other non modular

Electric Fryers 600mm Deep

39

700XP Modular cooking

Gas Boiling Tops



	371000	371001	371004	371166	371167	371170
External dim. - mm						
width	400	800	1200	400	800	1200
depth	730	730	730	730	730	730
height	250	250	250	250	250	250
Gas power - kW	11	22	33	11	22	33
Burners - nr/kW	2x5,5	4x5,5	6x5,5	2x5,5	4x5,5	6x5,5
AGA certification				•	•	•

Gas Ranges on Oven (4 burners)



	371002	371003	371168	371169	371125
External dim. - mm					
width	800	800	800	800	800
depth	730	730	730	730	730
height	850	850	850	850	850
Gas power - kW	28	22	28	22	22
Electric power - kW		6		6	6
Burners - nr/kW	4x5,5	4x5,5	4x5,5	4x5,5	4x5,5
Gas static oven	•		•		
Electric static oven		•		•	•
AGA certification			•	•	
Electrical connection		400V 3N 50/60Hz		400V 3N 50/60Hz	230V 3 50/60Hz

Gas Ranges on Oven (6 Burners)



	371173	371005	371006	371171	371172
External dim. - mm					
width	900	1200	1200	1200	1200
depth	730	730	730	730	730
height	850	850	850	850	850
Gas power - kW	42	39	33	39	33
Electric power - kW			6		6
Burners - nr/kW	6x5,5	6x5,5	6x5,5	6x5,5	6x5,5
Gas static oven		•		•	
Gas stratified oven	•				
Electric static oven			•		•
Large oven with 2 doors	•				
Open cupboard		•	•	•	•
AGA certification				•	•
Electrical connection			400V 3N 50/60Hz		400V 3N 50/60Hz

700XP Modular cooking

Gas Solid Tops



	371007	371008
External dim. - mm		
width	800	800
depth	730	730
height	250	850
Gas power - kW	7	13
Gas static oven		•

Gas Boiling Tops



	371011	371012	371009	371010
External dim. - mm				
width	800	1200	800	1200
depth	730	730	730	730
height	250	250	850	850
Gas power - kW	14,6	25,6	20,6	24
Burners - nr/kW	2x5,5	2x5,5+2x5,5	2x5,5	2x5,5
Gas static oven			•	•
Open cupboard				•

Electric Boiling Tops with Round Plates



	371014	371015	371019	371126	371127
External dim. - mm					
width	400	800	1200	400	800
depth	730	730	730	730	730
height	250	250	250	250	250
Electric power - kW	5,2	10,4	15,6	5,2	10,4
Plates - nr/kW	2x2,6	4x2,6	6x2,6	2x2,6	4x2,6
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	230V 3 50/60Hz	230V 3 50/60Hz

700XP Modular cooking

Electric Boiling Tops with Square Plates



	371017	371130
External dim. - mm		
width	800	800
depth	730	730
height	250	250
Electric power - kW	10,4	10,4
Plates - nr/kW	4x2,6	4x2,6
Electrical connection	400V 3N 50/60Hz	230V 3 50/60Hz

Electric Ranges on Oven



	371016	371128	371018	371129
External dim. - mm				
width	800	800	800	800
depth	730	730	730	730
height	850	850	850	850
Electric power - kW	16,4	16,4	16,4	16,4
Plates - nr/kW	4x2,6	4x2,6	4x2,6	4x2,6
Electric static oven	•	•	•	•
Electrical connection	400V 3N 50/60Hz	230V 3 50/60Hz	400V 3N 50/60Hz	230V 3 50/60Hz
Round plates	•	•		
Square plates			•	•

Electric Solid Tops



	371027	371028
External dim. - mm		
width	400	800
depth	730	730
height	250	250
Electric power - kW	5	10
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz

700XP Modular cooking

Infrared Cooking Tops



	371024	371025	371026	371133	371134
External dim. - mm					
width	400	800	800	400	800
depth	730	730	730	730	730
height	250	250	850	250	250
Electric power - kW	4,4	8,8	14,8	4,4	8,8
Zones - nr/kW	2x2,2	4x2,2	4x2,2	2x2,2	4x2,2
Electric static oven			•		
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	230V 3 50/60Hz	230V 3 50/60Hz

Induction Cooking Tops



	371020	371021	371131	371132
External dim. - mm				
width	400	800	400	800
depth	730	730	730	730
height	250	250	250	250
Electric power - kW	7	14	7	14
Zones - nr/kW	2x3,5	4x3,5	2x3,5	4x3,5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	230V 3 50/60Hz	230V 3 50/60Hz

Induction Cooking Tops - HP



	371175	371176	371023	371282
External dim. - mm				
width	400	800	800	400
depth	730	730	730	730
height	250	250	250	250
Electric power - kW	10	20	10	5
Zones - nr/kW	2x5	4x5	2x5	1x5
Rear condiment holder			•	
Wok				•
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz

700XP Modular cooking

Gas Fryers with "V" shape Well



	371068	371070	371069	371071
External dim. - mm				
width	400	400	800	800
depth	730	730	730	730
height	850	850	850	850
Gas power - kW	7	14	14	28
Wells - nr/lt	1x7	1x15	2x7	2x15
Baskets - nr	1	1	2	2

Gas Tube Fryers



	371072
External dim. - mm	
width	800
depth	730
height	850
Gas power - kW	27,5
Wells - nr/lt	1x34
Baskets - nr	2

Fryer Tops with "V" shape Well



	371075	371076	371140	371141	371066	371067
External dim. - mm						
width	400	800	400	800	400	800
depth	730	730	730	730	730	730
height	250	250	250	250	250	250
Electric power - kW	5,4	10,8	5,4	10,8		
Gas power - kW					7	14
Wells - nr/lt	1x7	2x7	1x7	2x7	1x7	2x7
Baskets - nr	1	2	1	2	1	2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	230V 3 50/60Hz	230V 3 50/60Hz		

700XP Modular cooking

Electric Fryer Tops with Tilting Heating Elements



	371074	371079	371080	371139	371142	371143
External dim. - mm						
width	400	400	800	400	400	800
depth	730	730	730	730	730	730
height	250	250	250	250	250	250
Electric power - kW	9	8,7	17,4	9	8,7	17,4
Wells - nr/lt	2x5	1x12	2x12	2x5	1x12	2x12lt
Baskets - nr	2	1	2	2	1	2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	230V 3 50/60Hz	230V 3 50/60Hz	230V 3 50/60Hz

Electric Fryers with "V" shape Well



	371077	371081	371083	371078	371082
External dim. - mm					
width	400	400	400	800	800
depth	730	730	730	730	730
height	850	850	850	850	850
Electric power - kW	5,4	10	10	10,8	20
Wells - nr/lt	1x7	1x15	1x15	2x7	2x15
Baskets - nr	1	1	2	2	2
Automatic and programmable			•		
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz

Electric Fryers with Tilting Heating Elements



	371084	371085	371144
External dim. - mm			
width	400	800	800
depth	730	730	730
height	850	850	850
Electric power - kW	8,7	17,4	17,4
Wells - nr/lt	1x14	2x14	2x14
Baskets - nr	1	2	2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	230V 3 50/60Hz

700XP Modular cooking

Electric Chip Scuttle Top



	371086
External dim. - mm	
width	400
depth	730
height	250
Electric power - kW	1
Wells - nr	1
Electrical connection	230V 1N 50/60Hz

Pasta Cookers



	371090	371091	371098	371100	371099
External dim. - mm					
width	400	800	400	400	800
depth	730	730	730	730	730
height	850	850	850	850	850
Gas power - kW	11,5	23			
Electric power - kW			6	9	12
Wells - nr/lt	1x24,5	2x24,5	1x24,5	1x24,5	2x24,5
Automatic and programmable				•	
Electrical connection			400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz

Gas Fry Tops (half module)



	371320	371323	371037
External dim. - mm			
width	400	400	400
depth	730	730	730
height	250	250	250
Cooking surface (wxd) mm	330x540	330x540	330x540
Gas power - kW	7	7	7
Smooth plate	•		•
Ribbed plate		•	
Brushed chrome plate	•	•	
Polished chrome plate			•
Thermostatic control			•

700XP Modular cooking

Gas Fry Tops (full module)



	371330	371335	371038	371041
External dim. - mm				
width	800	800	800	800
depth	730	730	730	730
height	250	250	250	250
Cooking surface (wxd) mm	730x540	730x540	730x540	730x540
Gas power - kW	14	14	14	14
Smooth plate	•		•	
Smooth and ribbed plate		•		•
Brushed chrome plate	•	•		
Polished chrome plate			•	•
Thermostatic control			•	•

Electric Fry Tops (half module)



	371325	371332	371193	371328	371321
External dim. - mm					
width	400	400	400	400	400
depth	730	730	730	730	730
height	250	250	250	250	250
Cooking surface (wxd) mm	330x540	330x540	330x540	330x540	330x540
Electric power - kW	4,5	4,5	4,5	4,5	4,5
Smooth plate	•		•	•	•
Ribbed plate		•			
Brushed chrome plate	•	•		•	•
Polished chrome plate			•		
Horizontal plate				•	
Thermostatic control	•	•	•	•	•
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	230V 3 50/60Hz

700XP Modular cooking

Electric Fry Tops (full module)



	371340	371347	371194	371197	371344
External dim. - mm					
width	800	800	800	800	800
depth	730	730	730	730	730
height	250	250	250	250	250
Cooking surface (wxd) mm	730x540	730x540	730x540	730x540	730x540
Electric power - kW	8,4	8,4	8,4	8,4	8,4
Smooth plate	•		•		
Smooth and ribbed plate		•		•	
Completely ribbed plate					•
Brushed chrome plate	•	•			•
Polished chrome plate			•	•	
Thermostatic control	•	•	•	•	•
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz

Electric Fry Tops (full module)



	371322	371329	371201
External dim. - mm			
width	800	800	800
depth	730	730	730
height	250	250	250
Cooking surface (wxd) mm	730x540	730x540	730x540
Electric power - kW	7,8	7,8	7,8
Smooth plate	•		
Smooth and ribbed plate		•	•
Brushed chrome plate	•	•	
Polished chrome plate			•
Thermostatic control	•	•	•
Electrical connection	230V 3 50/60Hz	230V 3 50/60Hz	230V 3 50/60Hz

700XP Modular cooking

Gas Grill Tops - HP



	371042	371043
External dim. - mm		
width	400	800
depth	730	730
height	250	250
Cooking surface (wxd) mm	371x472	742x472
Gas Power - kW	7	14
Powergrill	•	•

Electric Grill Tops - HP



	371266	371267	371268	371302	371301	371300
External dim. - mm						
width	400	800	1200	400	800	1200
depth	730	730	730	730	730	730
height	250	250	250	250	250	250
Cooking surface (wxd) mm	345x400	705x400	1065x400	345x400	705x400	1065x400
Well capacity (lt)	4,5	8,8	12	4,5	8,8	12
Electric Power - kW	3,75	7,5	11,25	3,75	7,5	11,25
Electrical connection	415V 3N 50/60Hz	415V 3N 50/60Hz	415V 3N 50/60Hz	230V 3N 50/60Hz	230V 3N 50/60Hz	230V 3N 50/60Hz
Tilting heating elements	•	•	•	•	•	•

Gas Grill Tops



	371044	371045
External dim. - mm		
width	400	800
depth	730	730
height	250	250
Cooking surface (wxd) mm	321x478	641x478
Gas power - kW	7	14

700XP Modular cooking

Grills



	371237	371238	371241	371242
External dim. - mm				
width	400	800	400	800
depth	730	730	730	730
height	850	850	850	850
Cooking surface (wxd) mm	316x478	631x478	316x478	631x478
Gas power - kW	8	16		
Electric power - kW			6	12
Tilting heating elements			•	•
Electrical connection			400V 3N 50/60Hz	400V 3N 50/60Hz

Electric Grill Tops



	371239	371240
External dim. - mm		
width	400	800
depth	730	730
height	250	250
Cooking surface (wxd) mm	316x478	631x478
Electric power - kW	6	12
Tilting heating elements	•	•
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz

Multifunctional Cookers



	371105	371106	371109	371110
External dim. - mm				
width	400	800	400	800
depth	730	730	730	730
height	850	850	850	850
Power supply	Gas	Gas	Electric	Electric
Gas power - kW	7	14		
Electric power - kW			5	10
Well - lt	11	22	11	22
Compound cooking plate	•	•	•	•
Electrical connection			400V 3N 50/60Hz	400V 3N 50/60Hz

700XP Modular cooking

Electric Bain-Marie Tops



	371096	371097	371145
External dim. - mm			
width	400	800	800
depth	730	730	730
height	250	250	250
Electric power - kW	1,5	3	3
Well capacity	GN1/1	GN2/1	GN2/1
Electrical connection	230V 1N 50/60Hz	400V 3N 50/60Hz	230V 3 50/60Hz

Tilting Braising Pans



	371181	371183
External dim. - mm		
width	800	800
depth	730	730
height	850	850
Power supply	Gas	Electric
Gas power - kW	16	
Electric power - kW		9,5
Nominal well capacity - lt	60	60
Duomat bottom	•	•
Electrical connection		400V 3N 50/60Hz

700XP Modular cooking

Boiling Pans



	371271	371269	371270	371272	371273
External dim. - mm					
width	800	800	800	800	800
depth	730	730	730	730	730
height	850	850	850	850	850
Power supply	Gas	Gas	Gas	Electric	Electric
Gas power - kW	14	14	14		
Electric power - kW	0,1	0,1	0,1	9,4	9,4
Well - lt	60	60	60	60	60
Direct heating	•				
Indirect heating		•	•	•	•
Automatic jacket refilling			•		•
Automatic jacket depressurization			•		•
Electrical connection	230V 1N 50 Hz	230V 1N 50 Hz	230V 1N 50 Hz	400V 3N 50/60Hz	400V 3N 50/60Hz

Refrigerated Bases



	371290	371291	371292	371293	371295	371296
External dim. - mm						
width	1200	1200	1600	1600	1200	1600
depth	700	700	700	700	700	700
height	600	600	600	600	600	600
Drawers - nr	2		3		4	6
Doors - nr		2		3		
Temperature - °C	+10 / -2	+10 / -2	+10 / -2	+10 / -2	+10 / -2	+10 / -2
Refrigerant type	R290	R290	R290	R290	R290	R290
Electrical connection	230V 1N 50Hz	230V 1N 50Hz	230V 1N 50Hz	230V 1N 50Hz	230V 1N 50Hz	230V 1N 50Hz
Automatic evaporation	•	•	•	•	•	•

700XP Modular cooking

Freezer Base



	371294
External dim. - mm	
width	1200
depth	700
height	600
Drawers - nr	2
Doors - nr	
Temperature - °C	-15 / -20
Refrigerant type	R290
Electrical connection	230V 1N 50Hz
Automatic evaporation	•

Ambient Worktops



	371115	371116	371117	371118	371119
External dim. - mm					
width	200	400	400	800	800
depth	730	730	730	730	730
height	250	250	250	250	250
Drawer			•		•

Top with Water Column



	206377
External dim. - mm	
width	200
depth	730
height	250
Digital flow meter	•
Electric power - kW	0,2
Electrical connection	230V 1N 50Hz

700XP Modular cooking



Sink Unit

	371214
External dim. - mm	
width	400
depth	730
height	250

Open Bases



	371210	371211	371112	371113	371114
External dim. - mm					
width	200	200	400	800	1200
depth	550	550	550	550	550
height	600	600	600	600	600
Open			•	•	•
Closed	•				
Drawer for bottles		•			

900XP Modular cooking

Gas Boiling Tops



	391000	391002	391011	391193
External dim. - mm				
width	400	800	1200	800
depth	930	930	930	930
height	250	250	250	250
Gas power - kW	12	28	44	24
Burners - nr/kW	2x6	1x10+3x6	2x10+4x6	1x7,5+3x5,5
Town gas				•

Gas Boiling Tops - HP



	391001	391003	391012	391192	391194	391196
External dim. - mm						
width	400	800	1200	400	800	1200
depth	930	930	930	930	930	930
height	250	250	250	250	250	250
Gas power - kW	20	40	60	15	30	45
Burners - nr/kW	2x10	4x10	6x10	2x7,5	4x7,5	6x7,5
Town gas				•	•	•
HP models	•	•	•	•	•	•

Gas Boiling Tops - HP



	391024
External dim. - mm	
width	800
depth	930
height	250
Gas power - kW	30
Burners - nr/kW	1x5+1x10 +1x15
HP models	•
Concentric burners	•

900XP Modular cooking



Gas Ranges on Convection Oven (4 burners)

	391007	391008	391009
External dim. - mm			
width	800	800	800
depth	930	930	930
height	850	850	850
Gas power - kW	34,5	38,5	50,5
Electric power - kW	0,25	0,25	0,25
Burners - nr/kW	4x6	1x10+3x6	4x10
Gas convection oven	•	•	•
Electrical connection	230V 1N 50Hz	230V 1N 50Hz	230V 1N 50Hz

Gas Ranges on Static Oven (4 Burners)



	391004	391005	391006	391010	391195	391164
External dim. - mm						
width	800	800	800	800	800	800
depth	930	930	930	930	930	930
height	850	850	850	850	850	850
Gas power - kW	32,5	36,5	48,5	28	28	28
Electric power - kW				6	6	6
Burners - nr/kW	4x6	1x10+3x6	4x10	1x10+3x6	1x7,5+3x5,5	1x10+3x6
Gas static oven	•	•	•			
Electric static oven				•	•	•
Town gas					•	
Electrical connection				400V 3N 50/60Hz	400V 3N 50/60Hz	230V 3 50/60Hz

Gas Ranges on Static Oven (6 or 8 Burners)



	391013	391014	391015	391016	391017
External dim. - mm					
width	1200	1200	1200	1200	1600
depth	930	930	930	930	930
height	850	850	850	850	850
Gas power - kW	52,5	68,5	56	72	73
Burners - nr/kW	2x10+4x6	6x10	2x10+4x6	6x10	2x10+6x6
Gas static oven	•	•			
Large oven			•	•	
Open cupboard	•	•			

900XP Modular cooking

Electric Boiling Tops with Square Plates



	391039	391040	391165	391166
External dim. - mm				
width	400	800	400	800
depth	930	930	930	930
height	250	250	250	250
Electric power - kW	8	16	8	16
Plates - nr/kW	2x4	4x4	2x4	4x4
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	230V 3 50/60Hz	230V 3 50/60Hz

Electric Ranges with Square Plates on Oven



	391041	391167
External dim. - mm		
width	800	800
depth	930	930
height	850	850
Electric power - kW	22	22
Plates - nr	4x4	4x4
Electric static oven	•	•
Electrical connection	400V 3N 50/60Hz	230V 3 50/60Hz

Gas Solid Tops



	391018	391019	391214
External dim. - mm			
width	800	800	800
depth	930	930	930
height	250	850	850
Gas power - kW	10,5	19	21
Electric power - kW			0,25
Gas static oven		•	
Gas convection oven			•
Electrical connection			230V 1N 50Hz

900XP Modular cooking

Gas Solid Tops and Burners



	391020	391021	391215
External dim. - mm			
width	800	1200	1200
depth	930	930	930
height	850	850	850
Gas power - kW	30	35	37
Electric power - kW			0,25
Burners - nr/kW	1x10+1x6	1x10+1x6	1x10+1x6
Gas static oven	•	•	
Gas convection oven			•
Open cupboard		•	•
Electrical connection			230V 1N 50Hz

Hob Cooking Tops



	391022	391023	391046	391047
External dim. - mm				
width	400	800	400	800
depth	930	930	930	930
height	250	250	250	250
Gas power - kW	8	16		
Electric power - kW			7	10
Cooking zones - nr	1	2	2	2
Electrical connection			400V 3N 50/60Hz	380-400V 3N 50/60Hz

Infrared Cooking Tops



	391044	391045	391170
External dim. - mm			
width	400	400	800
depth	930	930	930
height	250	250	250
Electric power - kW	6,8	13,6	13,6
Zones - nr/kW	2x3,4	4x3,4	4x3,4
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	230V 3 50/60Hz

900XP Modular cooking

Induction Cooking Tops



	391277	391278	391168	391169	391353
External dim. - mm					
width	400	800	400	800	400
depth	930	930	930	930	930
height	250	250	250	250	250
Electric power - kW	10	20	10	20	5
Zones - nr/kW	2x5	4x5	2x5	4x5	
Wok					•
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	230V 3 50/60Hz	230V 3 50/60Hz	400V 3N 50/60Hz

Gas Fryers with "V" shape Well



	391077	391331	391078	391332
External dim. - mm				
width	400	400	800	800
depth	930	930	930	930
height	850	850	850	850
Gas power - kW	14	20	28	42
Wells - nr/lt	1x15	1x23	2x15	2x23
Baskets - nr	1	2	2	4

Gas Fryers with Electronic Control



	391333	391334	391335	391375	391376	391377
External dim. - mm						
width	400	400	400	400	400	400
depth	930	930	930	930	930	930
height	1200	1200	1200	1200	1200	1200
Gas power - kW	26	26	26	26	26	26
Electric power - kW	0,1	0,1	0,1	0,1	0,1	0,1
Wells - nr/lt	1x23	1x23	1x23	1x23	1x23	1x23
Baskets - nr	2	2	2	2	2	2
Programmable	•	•	•	•	•	•
Mechanized oil filtering		•	•		•	•
Prearranged for Advanced filtering system		•	•		•	•
Automatic lifting system			•			•
Electrical connection	220/240V 1N 50Hz	220/240V 1N 50Hz	220/240V 1N 50Hz	220V 1N 60Hz	220V 1N 60Hz	220V 1N 60Hz

900XP Modular cooking

Gas Fryer with Automatic Cooking Mode



	391343	391379
External dim. - mm		
width	400	400
depth	930	930
height	1200	1200
Gas power - kW	25	25
Electric power - kW	0,1	0,1
Wells - nr/lit	1x23	1x23
Baskets - nr	2	2
Programmable	•	•
Mechanized oil filtering	•	•
Prearranged for Advanced filtering system	•	•
Automatic lifting system	•	•
Automatic cooking programs	5	5
Electrical connection	220/240V 1N 50Hz	220V 1N 60Hz



Gas Tube Fryers

	391084
External dim. - mm	
width	800
depth	930
height	1200
Gas power - kW	19
Wells - nr/lit	1x23
Baskets - nr	2

Electric Fryers with "V" shape Well



	391087	391088	391337	391338	391384	391385
External dim. - mm						
width	400	800	400	800	400	800
depth	930	930	930	930	930	930
height	850	850	850	850	850	850
Electric power - kW	10	20	18	36	17,2	34,4
Wells - nr/lit	1x15	2x15	1x23	2x23	1x23	2x23
Baskets - nr	1	2	2	4	2	4
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	380/400V 3N 50/60Hz	380/400V 3N 50/60Hz	415/430V 3N 50/60Hz	415/430V 3N 50/60Hz

900XP Modular cooking

Electric Fryers with Tilting Heating Elements



	391094	391095	391178	391179	391311*
External dim. - mm					
width	400	800	400	800	800
depth	930	930	930	930	930
height	850	850	850	850	850
Electric power - kW	16,5	33	16,5	33	16,5
Wells - nr/lt	1x18	2x18	1x18	2x18	1x18
Baskets - nr	2	4	2	4	2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	230V 3 50/60Hz	230V 3 50/60Hz	400V 3N 50/60Hz

* for external oil collecting system

Electric Fryers with Electronic Control



	391339	391340	391341	391386	391387	391388
External dim. - mm						
width	400	400	400	400	400	400
depth	930	930	930	930	930	930
height	1200	1200	1200	1200	1200	1200
Electric power - kW	18	18	18	17,2	17,2	17,2
Wells - nr/lt	1x23	1x23	1x23	1x23	1x23	1x23
Baskets - nr	2	2	2	2	2	2
Programmable	•	•	•	•	•	•
Mechanized oil filtering		•	•		•	•
Prearranged for Advanced filtering system		•	•		•	•
Automatic lifting system			•			•
Electrical connection	380/400V 3N 50/60Hz	380/400V 3N 50/60Hz	380/400V 3N 50/60Hz	415/430V 3N 50/60Hz	415/430V 3N 50/60Hz	415/430V 3N 50/60Hz

900XP Modular cooking

Electric Fryer with Automatic Cooking Mode



	391345	391390
External dim. - mm		
width	400	400
depth	930	930
height	1200	1200
Electric power - kW	18	17,2
Wells - nr/lt	1x23	1x23
Baskets - nr	2	2
Programmable	•	•
Mechanized oil filtering	•	•
Prearranged for Advanced filtering system	•	•
Automatic lifting system	•	•
Automatic cooking programs	5	5
Electrical connection	380/400V 3N 50/60Hz	415/430V 3N 50/60Hz

Electric Chip Scuttle Top



	391098
External dim. - mm	
width	400
depth	930
height	250
Electric power - kW	1
Wells - nr	1
Electrical connection	230V 1N 50/60Hz

900XP Modular cooking

Pasta Cookers



	391111	391112	391126	391273	391127
External dim. - mm					
width	400	800	400	400	800
depth	930	930	930	930	930
height	850	850	850	850	850
Gas power - kW	16,5	33			
Electric power - kW			10	10	20
Wells - nr/lt	1x40	2x40	1x40	1x40	2x40
Electrical connection			400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Energy saving device*				•	

* Available as optional accessory for all models

Electric Rethermalizer



	391352	391999
External dim. - mm		
width	400	400
depth	933	933
height	850	850
Electric power - kW	10	3,5
Wells - nr/l	1x40	1x40
Electrical connection	415V 3N 50Hz	240V 1 50Hz

Gas Automatic Pasta Cookers



	391113	391115	391116	391114
External dim. - mm				
width	800	1200	1200	1600
depth	930	930	930	930
height	850	850	850	850
Gas power - kW	23	30	30	46
Electric power - kW	0,3	0,3	0,5	0,5
Wells - nr/lt	1x150	1x190	1x190	2x150
Baskets - nr	1	1	2	2
Electrical connection	230V 1N 50Hz	230V 1N 50Hz	230V 1N 50Hz	230V 1N 50Hz

900XP Modular cooking

Electric Automatic Pasta Cookers



	391128	391130	391131	391129
External dim. - mm				
width	800	1200	1200	1600
depth	930	930	930	930
height	850	850	850	850
Electric power - kW	15	23	23	30
Wells - nr/lt	1x150	1x190	1x190	2x150
Baskets - nr	1	1	2	2
Electrical connection	400V 3N 50Hz	400V 3N 50Hz	400V 3N 50Hz	400V 3N 50Hz

Steam Automatic Pasta Cookers



	391132	391133
External dim. - mm		
width	800	1200
depth	930	930
height	850	850
Electric power - kW	0,3	0,5
Wells - nr/lt	1x150	1x190
Baskets - nr	1	2
Electrical connection	230V 1N 50Hz	230V 1N 50Hz

Gas Fry Tops (half module)



	391402	391354	391053
External dim. - mm			
width	400	400	400
depth	930	930	930
height	250	250	250
Cooking surface (wxd) mm	344x647	344x647	344x647
Gas power - kW	10	10	10
Smooth plate	•		•
Ribbed plate		•	
Brushed chrome plate	•	•	
Polished chrome plate			•
Horizontal plate	•		
Thermostatic control	•	•	•

900XP Modular cooking

Gas Fry Tops (full module)



	391401	391403	391054	391055
External dim. - mm				
width	800	800	800	800
depth	930	930	930	930
height	250	250	250	250
Cooking surface (wxd) mm	744x647	744x647	744x647	744x647
Gas power - kW	20	20	20	20
Smooth plate	•		•	
Smooth and ribbed plate		•		•
Brushed chrome plate	•	•		
Polished chrome plate			•	•
Horizontal plate	•			
Thermostatic control	•	•	•	•

NitroChrome³ Gas Fry Tops - HP



	391406	391407
External dim. - mm		
width	1200	1200
depth	930	930
height	250	250
Cooking surface (wxd) mm	1170x610	1170x610
Gas power - kW	33	33
Smooth plate	•	
Smooth and ribbed plate		•
Scratch resistant chromium plate	•	•
Thermostatic control	•	•

900XP Modular cooking

Electric Fry Tops (half module)



	391357	391356	391072	391398	392395	391175
External dim. - mm						
width	400	400	400	400	400	400
depth	930	930	930	930	930	930
height	250	250	250	250	250	250
Cooking surface (wxd) mm	330x700	330x700	330x700	330x700	330x700	330x700
Electric power - kW	7,5	7,5	7,5	7,5	7,5	7,5
Smooth plate	•		•	•		•
Ribbed plate		•			•	
Brushed chrome plate	•	•		•	•	
Polished chrome plate			•			•
Horizontal plate	•			•		
Thermostatic control	•	•	•	•	•	•
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	230V 3 50/60Hz	230V 3 50/60Hz	230V 3 50/60Hz

Electric Fry Tops (full module)



	391400	391358	391073	391074
External dim. - mm				
width	800	800	800	800
depth	930	930	930	930
height	250	250	250	250
Cooking surface (wxd) mm	730x700	730x700	730x700	730x700
Electric power - kW	15	15	15	15
Smooth plate	•		•	
Smooth and ribbed plate		•		•
Brushed chrome plate	•	•		
Polished chrome plate			•	•
Horizontal plate	•			
Thermostatic control	•	•	•	•
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz

900XP Modular cooking

Electric Fry Tops (full module)



	391399	391359	391176	391177
External dim. - mm				
width	800	800	800	800
depth	930	930	930	930
height	250	250	250	250
Cooking surface (wxd) mm	730x700	730x700	730x700	730x700
Electric power - kW	15	15	15	15
Smooth plate	•		•	
Smooth and ribbed plate		•		•
Brushed chrome plate	•	•		
Polished chrome plate			•	•
Thermostatic control	•	•	•	•
Electrical connection	230V 3 50/60Hz	230V 3 50/60Hz	230V 3 50/60Hz	230V 3 50/60Hz

NitroChrome³ Electric Fry Tops - HP



	391404	391405
External dim. - mm		
width	1200	1200
depth	930	930
height	250	250
Cooking surface (wxd) mm	1194x610	1194x610
Electric power - kW	20	20
Smooth plate	•	
Smooth and ribbed plate		•
Scratch resistant chromium plate	•	•
Thermostatic control	•	•
Electrical connection	400V 3N 50/60HZ	400V 3N 50/60Hz

900XP Modular cooking

Gas Grill Tops - HP (Powergrill)



	391219	391065	391066
External dim. - mm			
width	400	800	1200
depth	930	930	930
height	250	250	250
Cooking surface (wxd) mm	371x644	742x644	1113x644
Gas power - kW	10,5	21	31,5
Powergrill	•	•	•

Electric Grill Tops - HP (Powergrill)



	391346	391347	391348	391362	391361	391360
External dim. - mm						
width	400	800	1200	400	800	1200
depth	930	930	930	930	930	930
height	250	250	250	250	250	250
Cooking surface (wxd) mm	345x598	705x598	1065x598	345x598	705x598	1065x598
Well capacity (lt)	6,7	13	20	6,7	13	20
Electric power - kW	5,8	11,6	17,4	5,8	11,6	17,4
Electric connection	415V 3N 50/60Hz	415V 3N 50/60Hz	415V 3N 50/60Hz	230V 3N 50/60Hz	230V 3N 50/60Hz	230V 3N 50/60Hz
Powergrill	•	•	•	•	•	•
Tilting heating elements	•	•	•	•	•	•

Grills Freestanding



	391266	391267	391268	391269	391270	391271
External dim. - mm						
width	400	800	400	800	400	800
depth	930	930	930	930	930	930
height	850	850	850	850	850	850
Cooking surface (wxd) mm	316x640	631x640	316x640	631x640	316x640	631x640
Gas power - kW	11	22	10	20		
Electric power - kW					7,5	15
Town gas			•	•		
Tilting heating elements					•	•
Electrical connection					400V 3N 50/60Hz	400V 3N 50/60Hz

900XP Modular cooking

Multifunctional Cookers



	391142	391151
External dim. - mm		
width	800	800
depth	930	930
height	850	850
Power supply	Gas	Electric
Gas power - kW	14	
Electric power - kW		10
Well capacity - lt	22	22
Electrical connection		400V 3N 50/60Hz

Bain-Marie Tops



	391109	391110	391124	391125
External dim. - mm				
width	400	800	400	800
depth	930	930	930	930
height	250	250	250	250
Power supply	Gas	Gas	Electric	Electric
Gas power - kW	3	6,2		
Electric power - kW			2,2	4,4
Well capacity	GN1/1+ GN1/3	GN2/1+ 2xGN1/3	GN1/1+ GN1/3	GN2/1+ 2xGN1/3
Electrical connection			230V 1N 50/60Hz	400V 3N 50/60Hz

Gas Tilting Braising Pans (80lt and 100 lt)



	391136	391137	391140	391141
External dim. - mm				
width	800	800	1000	1000
depth	930	930	930	930
height	850	850	850	850
Gas power - kW	21	21	27	27
Electric power - kW	0,25	0,25	0,25	0,25
Nominal well capacity - lt	80	80	100	100
Duomat bottom	•	•	•	•
Motorized lifting		•		•
Electrical connection	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz

900XP Modular cooking

Electric Tilting Braising Pans (80lt and 100 lt)



	391145	391146	391149	391150
External dim. - mm				
width	800	800	1000	1000
depth	930	930	930	930
height	850	850	850	850
Electric power - kW	13	13	17	17
Nominal well capacity - lt	80	80	100	100
Duomat bottom	•	•	•	•
Motorized lifting		•		•
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz

Gas Boiling Pans (Cylindrical)



	391106	391107	391108	391232	391100	391104
External dim. - mm						
width	800	800	800	800	800	800
depth	930	930	930	930	930	930
height	850	850	850	850	850	850
Gas power - kW	21	24	24	14	21	24
Electric power - kW	0,1	0,1	0,1	0,1	0,1	0,1
Well capacity - lt	100	150	150	60	100	150
Direct heating	•	•	•			
Indirect heating				•	•	•
Autoclave			•			•
Electrical connection	230V 1N 50Hz	230V 1N 50Hz	230V 1N 50Hz	230V 1N 50Hz	230V 1N 50Hz	230V 1N 50Hz

Gas Boiling Pans (Cylindrical)



	391101	391102	391103
External dim. - mm			
width	800	800	800
depth	930	930	930
height	850	850	850
Gas power - kW	21	24	24
Electric power - kW	0,2	0,2	0,2
Well capacity - lt	100	150	150
Indirect heating	•	•	•
Automatic jacket refilling	•		•
Electrical connection	230V 1N 50Hz	230V 1N 50Hz	230V 1N 50Hz

900XP Modular cooking

Electric Boiling Pans (Cylindrical)



	391117	391118	391119	391120	391121	391122
External dim. - mm						
width	800	800	800	800	800	800
depth	930	930	930	930	930	930
height	850	850	850	850	850	850
Electric power - kW	9,4	21,5	21,5	21,5	21,5	21,5
Well capacity - lt	60	100	100	150	150	150
Indirect heating	•	•	•	•	•	•
Automatic jacket refilling			•		•	
Autoclave						•
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz

Boiling Pans (Rectangular)



	391105	391123
External dim. - mm		
width	1200	1200
depth	930	930
height	850	850
Power supply	Gas	Electric
Gas power - kW	35	
Electric power - kW	0,05	24
Well capacity - lt	250	250
Indirect heating	•	•
Electrical connection	230V 1N 50/60Hz	400V 3N 50/60Hz

Ref-freezer Base



	727982
External dim. - mm	
width	1200
depth	900
height	600
Drawers - nr/width	2x800mm
Temperature - °C	+8 / -22
Convertible refr/ freezer	•
Refrigerant type	R452A
Electrical connection	230V 1 50Hz
Automatic evaporation	•

900XP Modular cooking

Refrigerated Base



	391602	391601	391600
External dim. - mm			
width	1200	1600	1600
depth	830	830	830
height	600	600	600
Drawers - nr/width	2x400mm	3x400mm	6x400mm
Temperature - °C	+10 / -2	+10 / -2	+10 / -2
Refrigerant type	R290	R290	R290
Electrical connection	230V 1 50Hz	230V 1 50Hz	230V 1 50Hz
Automatic evaporation	•	•	•

Ambient Worktops



	391156	391157	391158	391159	391160	391161
External dim. - mm						
width	200	200	400	400	800	800
depth	930	930	930	930	930	930
height	250	250	250	250	250	250
Drawer		•		•		•

Top with Water Column



	206378
External dim. - mm	
width	200
depth	930
height	250
Digital flow meter	•
Electric power - kW	0,2
Electrical connection	230V 1N 50Hz

Sink Unit



	391236	391312
External dim. - mm		
width	400	400
depth	930	930
height	250	250
Ambient GN well		•

900XP Modular cooking

Bases



	391152	391153	391154	391155
External dim. - mm				
width	200	400	800	1200
depth	785	785	785	785
height	600	600	600	600
Open		•	•	•
Drawer for bottles	•			

Other non-modular

Electric Fryers 600mm Deep



	285561	285562	285563	285564
External dim. - mm				
width	200	200	200	200
depth	600	600	600	600
height	850	850	850	850
Electric power - kW	7,4	7,4	7,4	7,4
Well - nr/lit	1x9	1x9	1x9	1x9
Baskets - nr	1	1	1	1
Eco mode	•	•	•	•
Oil pump		•		•
Tilting heating elements	•	•	•	•
Reversible door	•	•	•	•
Warning led	•	•	•	•
Electrical connection	240V 1 50/60Hz	240V 1 50/60Hz	415V 3 50/60Hz	415V 3 50/60Hz



Excellence is central to everything we do.
By anticipating our customers' needs, we strive for
Excellence with our people, innovations, solutions and services.
To be the OnE making our customers' work-life easier,
more profitable - and truly sustainable every day.

Follow us on



professional.electrolux.com

Excellence with the environment in mind

- ▶ All our factories are ISO 14001-certified
- ▶ All our solutions are designed for low consumption of water, energy, detergents and harmful emissions
- ▶ In recent years over 70% of our product features have been updated with the environmental needs of our customers in mind
- ▶ Our technology is ROHS and REACH compliant and over 95% recyclable
- ▶ Our products are 100% quality tested by experts

