



A Skellerup Industries Company

# Solar Solutions

## SolarDek Silicone



## SolarDek EPDM



FS 520679  
QUALITY ISO9001

## Deks Solar Solution

### The specialty flashing for solar panels

Don't waste time or risk call-backs by filling holes with silicone (which may break down quickly with exposure to UV)

Use a purpose designed Dektite from our Solar Range - the professional choice for flashing solar panels on both tile and metal roofs.



## Deks Solar Solutions makes life easy

CHECK THE BENEFITS!

- Won't stain or corrode
- High grade, long-life polymer Dektite®
- Nu-Lead® tray for safe handling
- Can be painted to match the roof colour
- Long Life Warranty  
Just fit it and forget it – we've got you covered

[www.deks.com.au](http://www.deks.com.au)

## Fast • Efficient • Safe

THE choice of professionals

### On Tile Roofs

Deks Solar Solutions combines the quality polymer Dektite with a Nu-lead base featuring a unique acrylic coated apron, which prevents leaching of lead oxides.

This stops corrosion and staining and makes handling much safer for installers.



DNL 200

### On Metal Roofs

The Dektite® Mini (DFE 100)

Fixing is fast and easy and with a warranty of 20 years, you are assured of a long-lasting, quality product designed for high resistance to weather and UV exposure.



DFE100

## SolarDek™ - The speciality flashing for solar panels

Designed specifically for solar panel installation on both metal and tile roofs. Fast. Efficient. Safe.

Product Code	Pipe External	Base size		Pitch
DNL100	0-35mm	490 x 410mm	19 x 16"	0-45° or 1 <sup>1</sup> / <sub>2</sub>
DNL200	0-35mm	490 x 410mm	19 x 16"	0-45° or 1 <sup>1</sup> / <sub>2</sub>
DFE	0-35mm	99 x 99mm	4 x 4"	0-60° or 1 <sup>1</sup> / <sub>2</sub>
SDA100	12-70mm	500 x 600mm	19.5 x 23.5"	0-60° or 1 <sup>1</sup> / <sub>2</sub>

SolarDek™ EPDM is also available with an aluminium base (TFA 100).

#### Available in Black and Grey EPDM or Red Silicone

EPDM will withstand constant temperatures at the roofline of -50°C (-122°F) to 115°C (239°F) & up to 150°C (302°F) intermittently.

Red Silicone will withstand constant temperatures at the roofline of -50°C (-122°F) to 200°C (392°F) & up to 250°C (482°F) intermittently.

For higher temperatures always use the Dektite Silicone range go to [www.deks.com.au](http://www.deks.com.au) for more information on the full range.