





# HORIZON



To view colour swatches for each state refer to [www.monier.com.au](http://www.monier.com.au)

A sleek, flat profile is finished with a clean nose delivering streamlined roof lines in a palette of earthy, natural tones.



**TILES USAGE WITH WASTAGE (+/-2%)**  
Approx. 11.6 tiles per sqm.

**TILE COVERAGE (±2%)**  
Approx. 10.0 tiles per sqm.

**DIMENSIONS (±2%)**  
Length 420mm (415mm in NSW)  
Width 329mm

**MASS (±2%)**  
Per tile 5.20kg  
Per m<sup>2</sup> 52.0kg

**HEAD LAP ADJUSTMENT (MM)**  
80\* – 100 (\*With the use of sarking)

**FEATURE**  
Flat

**COLOUR APPLICATION**  
Colour On

**RECOMMENDED BONDING**  
Cross bond

**ROOF PITCH**  
Minimum Pitch with Sarking: 15°  
VIC ONLY – Minimum Pitch without Sarking: 20°



Please consult the Design Guide at [Monier.com.au](http://Monier.com.au) for installation requirements applicable to your project.

Please refer to AS2049 for acceptable tolerance to these measurements stated above.



# CONCRETE ACCESSORIES

ACCESSORY	LENGTH (MM)	WIDTH (MM)	HEIGHT (MM)	ANGLE (DEGREE)	WEIGHT (KG)
<b>Parbarge</b> 	420	248	126	84	4.9
<b>Starter</b> 	420	250	80	120	2.8
<b>3-Way Apex (butt &amp; overlapping)</b> 	391.7	413.3	135	135	3.8
<b>Ridge</b> 	420	250	80	120	3.4
<b>Ridge Saddle</b> 	205	250	175	120	3.3
<b>Gable Finial — Scroll</b> 	245	240	280	120	5.1
<b>Apex Finial — Scroll</b> 	385	420	320	120	6
<b>Spoon- Starter</b> 	410	395	125	120	6