

IMPORTANT COPY PROOF

Read this layout proof carefully. It is your guarantee of accuracy. Infolink does not accept responsibility for material once it has been approved by you for publication.

Please check the copy and return immediately by email, or contact Tracy Engle on (02) 9422 2707

Approved for Publication by _____

Date / /11

Email: tracy.engle@reedbusiness.com.au

76AX – Card Enquiry

Shingle Roofs By American Shingles

AMERICAN Shingles are providing a point of difference for Architects, Designers and Builders for their projects. American Shingles offers an alternative to our conventional roof linings with greater benefits against slate, timber shingles, metal deck, terracotta and concrete tiles.

American Shingles can provide slate and timber shingle aesthetics at a fraction of the cost with warranties up to 50 years and with wind resistance up to 175km/h. The security of all American Shingles roofs is the plywood substrate that provides greater resistance to hail and increasing the structural integrity of the building in general.

American Shingles roofs can be laid on pitches as low as 9.5 degrees and weigh as little as 17kg/m² fully laid.

The flexible nature of the shingles allows for the easy ability to apply them to curved and organic roof planes unlike conventional roofing materials. American Shingles conform with the Building Code of Australia and come in a dozen different profiles and colourways to suit any design application.



Is your product new?

If you wish to have this icon displayed, please tick this box.