

FLETCHER INSULATION™ LAUNCHES ADDITIONS TO THE ROOF RACK® RANGE

Fletcher Insulation™ has launched the Roof Rack® 100mm Spacer and Roof Rack® Cover Plate to accommodate new BCA requirements.

The BCA 2010 now states that in climate zone 7 a minimum R-value of R3.7 is required in a commercial metal roof application.

The Roof Rack® 100mm Spacer allows for building blanket to recover to its full nominal thickness achieving a total R-value of R3.7. This cost effective solution is endorsed by leading roofing manufacturers and uses standard self-drilling screws.

The introduction of the Roof Rack® Cover Plate allows roofers to utilise the Roof Rack® range of products for either concealed or pierce fixed roof applications.

Roof Rack® range of products also includes the Roof Rack® 75mm Spacer for use in Climate Zones 1-6 to achieve a total R-value of R3.2.

The Roof Rack® Cover Plate can accommodate both the 75mm and 100mm Roof Rack Spacer for use in pierce fixed roofing applications.

Product Information:

Roof Rack® Products	Product Code	Size	Base Unit of Measure	Qty Per Box	Weight (Box)
Roof Rack® 100mm	393077	100mm x 726mm	Box	20	15.0kg
Roof Rack® 75mm	393076	75mm x 726mm	Box	20	13.5kg
Roof Rack® Cover Plate	393002	n/a	Box	420	8.0kg
Roof Rack® 100mm End Clip	394076	n/a	Box	50	6.4kg
Roof Rack® 75mm End Clip	394075	n/a	Box	50	5.3kg

