

Dulux®

Introducing

AcraTex® Green Render Sealer

**Anti-Efflorescence Primer-Sealer
for fresh cement render.**

Eliminate project delays and unsightly efflorescence.

- ✓ **Fast Track - coat Render after only 2 days
(No more 28 day project delays)**
- ✓ **Stops Efflorescence**
- ✓ **Superior Adhesion**
- ✓ **Water Based - low VOC**

Dulux Warranted System for cement render
with AcraTex AcraSkin crackbridging topcoat.

**SAFE TO PAINT
OVER RENDER
IN 2 DAYS**
- No more delays



Features & Benefits

Paint with CONFIDENCE over render after only 2 days

Fresh or "green" cement render and concrete is HIGHLY ALKALINE, traditionally requiring time to stabilise before painting, resulting in costly project delays and extended scaffolding costs.

In the real world, project schedules compress and painting sooner often results in coating failures or unsightly alkali staining (white salts or "efflorescence").

AcraTex® GREEN RENDER SEALER eliminates the "28 Day" wait cycle - meaning project dollar savings and enhanced durability.

Safe, Durable & Assured

- Water Based, Applicator and Environment friendly
- AcraTex® GREEN RENDER SEALER chemically reacts with free cement alkali to bind and block its migration
- Paint after only 2 days render drying - instead of waiting 28 days
- Superior adhesion to masonry

Safe to paint over render In 2 days - No more delays

Dulux Approved System for Cement Render

Cement render is highly alkaline and rigid due to the inherent nature of the cement binder. Coating systems for cement render must block alkali (salts) leaching and expand and contract to accommodate render shrinkage cracks. Low build (conventional) paint coatings are NOT recommended for cement render

System Component	Dulux Warranted System	Feature Benefits
Primer Sealer	AcraTex Green Render Sealer Suitable for application over 2 day old cement render	- Blocks Cement Efflorescence - Reduces Project Delays - Optimises System Performance
Crack Bridging Topcoat	AcraTex AcraSkin Available across the full Dulux exterior colour range	High Build - Crack Bridging Protection Nap Roller - Paint Like Appearance Superior Application - Low Roller Spatter

Note: GRS is "Safe to paint after only 2 days" based on adequate drying of the substrate to a stable moisture content.

* When correctly applied by a fully trained AcraTex® applicator. 15 year warranty applicable on installations which include AcraTex® Green Render Sealer plus 2 coats of AcraSkin® weatherproofing topcoat.



Visit acratex.com.au for full system and information.
For general enquiries call **13 23 77**

Dulux® AcraTex® is a division of Dulux Group (Australia) ABN 67 000 049 427. Dulux® and AcraTex® are registered trademarks.



Scaffolding costs reduced



Eliminate unsightly efflorescence



Performance Coatings for Masonry