

TREND[®]
WINDOWS

& DOORS



PROTECT YOUR
HOME WITH XTREME
BUSHFIRE PROTECTION
WINDOWS & DOORS
BAL-40

Xtreme[®]
windows
& doors
Bushfire Protection

BAL-40 BAL-40 BAL-40 BAL-40 BAL-40 BAL-40

features & benefits

Trend® Windows & Doors was the first Australian window company to have their Xtreme® Bushfire window and door system tested by the CSIRO to rate upto BAL-40

Modern Clean Contemporary Designs

- Quantum Xtreme bushfire windows and doors withstand up to 40kw/m² (BAL-40)
- All Quantum Xtreme windows and doors are manufactured with sturdy 102mm outer frame (also available in 48mm Trend Synergy® windows)
- Fully compliant to Bushfire standard AS3959-2009 & AS1530.8.1
- Fully complies to Australian Standards AS2047
- Energy efficient solutions are available
- Double glazing option for windows and doors are available
- Satin chrome hardware supplied as standard
- Ask our Trend® Windows & Doors sales consultants for further information on custom made sizes
- Pyro-Protec seals and sealing system, act to protect the home against wind, water, noise, dust and bushfire penetration

energy efficiency

Thermashield® by Trend® utilises double glazed, toughened combinations of clear or toned glass, as well as low-e and gas filled IGU's. This offers significant savings by reducing expensive energy bills for all Xtreme® products.

Uniquely designed smooth sill deters the collection of dust and debris



AUSTRALIAN OWNED - OPERATED
MANUFACTURER & SUPPLIER



window range

Xtreme® bushfire windows are available in awning, casement, sliding and fixed lite

- Double glazing option for windows are available in 24mm (5-14-5) toughened integrated glazing unit
- Maximum glass area is 2.4m²
- Windows are manufactured with 5mm toughened glass as standard
- Window sash stile widths are:
62mm - awning, casement and fixed lite windows
55mm - sliding window



door range

Xtreme® bushfire doors are available in sliding, sliding stacker, bifold and hinged doors

- Double glazing option for doors are available in 18mm (6-6-6) toughened integrated glazing unit
- Maximum glass area is 2.4m²
- Doors are manufactured with 6mm toughened glass as standard
- Door stile widths are:
62mm – bifold and hinged doors
55mm – sliding, sliding stacker doors
- Maximum door height is 2400mm
- Xtreme doors meet BAL-40 without screens



Showrooms:

NSW - Girraween - Chatswood - South Nowra -
Cardiff - Ourimbah - Port Macquarie - Tamworth - Dubbo

ACT - Hume

VIC - Hawthorn - Bayswater North - Seaford - Ballarat

QLD - Coorparoo - Ormeau - Caboolture - Hervey Bay

SA - Regency Park

TAS - Spreyton



13 72 74

Trend® National Customer Assistance Centre
(8:30am - 4:30pm EST, M-F)

www.trendwindows.com.au
info@trendwindows.com.au



NOTE: Hardware displayed in photography may vary from state to state due to supplier or availability. Trend® Windows & Doors Pty Ltd reserve the right to make changes to product(s) without notice.

Trend® Windows & Doors Pty Limited, ABN 96 000 433 492. TM denotes a trademark and ® denotes a registered trademark owned by Trend® Windows & Doors Pty Limited.
© Owned by Trend® Windows & Doors Pty Limited. TREND178_FEB14