



Monarch

Renlita Overhead Doors

CLEARFOLD SIDE STACKABLE DOORS

Look - No Floor Tracks

A giant leap in smart design that completely eliminates the need for a floor track as it glides smoothly along an overhead track tucked neatly away in the ceiling. Tailor made to suit individual specifications, it takes minimum advantage of floor space extending your business opportunities.



Applications:

The Clearfold Side Trackable Doors are suitable for many commercial applications including the following:

- Shopping centres
- Bar tops
- Shop fronts
- Bottle shops
- Clubs
- Arcades
- Countertops
- Doorways
- Sports complexes

Maximum height - 4.0 metres.

Features:

The Clearfold stacking door is designed to enable vision of your merchandise whilst providing security and smooth effortless operation for large openings.

Specifications:

Track - Two part extruded aluminium 100mm high x 68mm profile. Tracks can be curved to provide smooth operation and accommodate irregular apertures.

Curtain - The curtain is constructed from a three part extruded continuous aluminium hinge joined to 100mm top and bottom rails. A mid rail can be fitted and is recommended for openings over 2000mm high. Standard glazing of 6.38mm laminated glass is fitted between the aluminium panels and secured with specially designed co-extrusions glazing wedges. Opening width is divided into an even number of panels. Panel widths are fabricated to suit each individual opening.


Stack Bay - Purpose fabricated to each job the bifurcated track allows the panels to be slid along the track locus and stack neatly into the stack bay. The fact that the panels can only bi-fold at the stack bay allows the door to travel in close proximity to obstructions without hampering door operation.

Locking - Locking up and down is provided at curtain ends and locking to floor is provided on consecutive hinges.

Finish - The clearfold door can be supplied in any powder coat or anodised finish.

The overhead structure must be designed to support the weight of the doors in the open and closed positions.

OPSM



Contact Details

NSW Office

58 Box Road, Taren Point NSW 2229
Phone: (02) 9526 1222 Fax: (02) 9525 1114

QLD Office

56/58 Nestor Drive, Meadowbrook QLD 4131
Phone: (07) 3805 7314 Fax: (07) 3805 7315

VIC Office

39 Nicholas Drive, Dandenong VIC 3175
Phone: (03) 9768 2562 Fax: (03) 9768 2563

Visit our website: www.monarchdoors.com.au